

TPMath
Math library for Pascal compilers

Jean Debord

December 10, 2010

Contents

1	Installation and compilation	11
1.1	Introduction	11
1.2	Unpacking the archive	11
1.3	Compilation with a 32-bit compiler	11
1.4	Compilation of a program	12
1.5	Linking to individual units	13
1.6	Compilation with a 16-bit compiler	13
2	Numeric precision	15
2.1	Numeric precision	15
2.2	Type Float	16
2.3	Type Complex	16
2.4	Size of types	16
2.5	Machine-dependent constants	16
2.6	Demo program	17
3	Elementary functions	19
3.1	Constants	19
3.2	Error handling	20
3.3	Min, max and exchange	20
3.4	Sign	21
3.5	Rounding functions	21
3.6	Logarithms and exponentials	21
3.7	Power functions	22
3.8	Trigonometric functions	22
3.9	Hyperbolic functions	23
3.10	Demo programs	23
3.10.1	Function accuracy	23
3.10.2	Computation speed	23

4	Special functions	25
4.1	Factorial	25
4.2	Gamma function	25
4.3	Polygamma functions	26
4.4	Beta function	27
4.5	Error function	27
4.6	Lambert's function	27
4.7	Demo programs	28
5	Probability distributions	29
5.1	Binomial distribution	29
5.2	Poisson distribution	30
5.3	Standard normal distribution	30
5.4	Student's distribution	31
5.5	Khi-2 distribution	32
5.6	Snedecor's distribution	32
5.7	Exponential distribution	33
5.8	Beta distribution	33
5.9	Gamma distribution	34
5.10	Demo program	34
6	Matrices and linear equations	35
6.1	Using vectors and matrices	35
6.2	Maximal array sizes	37
6.3	Array initialization	37
6.4	Programming conventions	37
6.5	Error codes	38
6.6	Gauss-Jordan elimination	38
6.7	LU decomposition	39
6.8	QR decomposition	40
6.9	Singular value decomposition	41
6.10	Eigenvalues and eigenvectors	42
	6.10.1 Definitions	42
	6.10.2 Symmetric matrices	42
	6.10.3 General square matrices	43
6.11	Demo programs	44
	6.11.1 Determinant and inverse of a square matrix	44
	6.11.2 Hilbert matrices	45
	6.11.3 Gauss-Jordan method: single constant vector	45
	6.11.4 Gauss-Jordan method: multiple constant vectors	46
	6.11.5 LU, QR and SV decompositions	46

6.11.6	Cholesky decomposition	46
6.11.7	Eigenvalues of a symmetric matrix	47
6.11.8	Eigenvalues of a general square matrix	47
6.11.9	Eigenvalues and eigenvectors of a general square matrix	47
7	Function minimization	51
7.1	Functions of one variable	51
7.2	Functions of several variables	52
7.2.1	Minimization along a line	53
7.2.2	Newton-Raphson method	53
7.2.3	Marquardt method	55
7.2.4	BFGS method	56
7.2.5	Simplex method	57
7.2.6	Log files	57
7.3	Demo programs	57
7.3.1	Function of one variable	57
7.3.2	Minimization along a line	58
7.3.3	Newton-Raphson method	58
7.3.4	Other programs	59
8	Nonlinear equations	61
8.1	Equations in one variable	61
8.1.1	Bisection method	61
8.1.2	Secant method	62
8.1.3	Newton-Raphson method	62
8.2	Equations in several variables	63
8.2.1	Newton-Raphson method	63
8.2.2	Broyden's method	65
8.3	Demo programs	65
8.3.1	Equations in one variable	65
8.3.2	Equations in several variables	66
9	Polynomials	67
9.1	Polynomials	67
9.2	Rational fractions	67
9.3	Roots of polynomials	67
9.3.1	Analytical methods	67
9.3.2	Iterative method	68
9.4	Ancillary functions	68
9.5	Demo programs	69
9.5.1	Evaluation of a polynomial	69

9.5.2	Evaluation of a rational fraction	69
9.5.3	Roots of a polynomial	69
10	Numerical integration and differential equations	71
10.1	Integration	71
10.1.1	Trapezoidal rule	71
10.1.2	Gauss-Legendre integration	71
10.2	Convolution	72
10.3	Differential equations	72
10.4	Demo programs	75
11	Fast Fourier Transform	79
11.1	Introduction	79
11.2	Programming	80
11.2.1	Array dimensioning	80
11.2.2	FFT procedures	80
11.3	Demo program	81
12	Random numbers	83
12.1	Random numbers	83
12.1.1	Introduction	83
12.1.2	Types	84
12.1.3	Generic functions	84
12.1.4	Specific functions	85
12.1.5	Gaussian random numbers	86
12.2	Markov Chain Monte Carlo	87
12.3	Simulated Annealing	90
12.4	Genetic Algorithm	92
12.5	Demo programs	94
12.5.1	Test of MWC generator	94
12.5.2	Test of MT generator	94
12.5.3	Test of UVAG generator	94
12.5.4	File of random numbers	94
12.5.5	Gaussian random numbers	94
12.5.6	Multinormal distribution	95
12.5.7	Multi-lognormal distribution	95
12.5.8	Markov Chain Monte-Carlo	95
12.5.9	Simulated Annealing	96
12.5.10	Genetic Algorithm	96

13 Statistics	97
13.1 Descriptive statistics	97
13.2 Comparison of means	99
13.2.1 Student's test for independent samples	99
13.2.2 Student's test for paired samples	100
13.2.3 One-way analysis of variance (ANOVA)	101
13.2.4 Two-way analysis of variance	102
13.3 Comparison of variances	104
13.3.1 Comparison of two variances	104
13.3.2 Comparison of several variances	104
13.4 Non-parametric tests	105
13.4.1 Mann-Whitney test	105
13.4.2 Wilcoxon test	106
13.4.3 Kruskal-Wallis test	106
13.5 Statistical distribution	107
13.6 Comparison of distributions	108
13.6.1 Observed and theoretical distributions	108
13.6.2 Several observed distributions	109
13.7 Demo programs	109
13.7.1 Descriptive statistics, comparison of means and variances	110
13.7.2 Student's test for paired samples	110
13.7.3 One-way analysis of variance	110
13.7.4 Two-way analysis of variance	110
13.7.5 Statistical distribution	110
13.7.6 Comparison of distributions	111
 14 Linear regression	 113
14.1 Straight line fit	113
14.2 Analysis of variance	115
14.3 Precision of parameters	116
14.4 Probabilistic interpretation	116
14.5 Weighted regression	117
14.6 Programming	118
14.6.1 Regression procedures	118
14.6.2 Quality of fit	119
14.7 Demo programs	119
14.7.1 Unweighted linear regression	120
14.7.2 Weighted linear regression	120

15 Multilinear regression and principal component analysis	121
15.1 Multilinear regression	121
15.1.1 Normal equations	121
15.1.2 Analysis of variance	122
15.1.3 Precision of parameters	123
15.1.4 Probabilistic interpretation	123
15.1.5 Weighted regression	123
15.1.6 Programming	124
15.2 Principal component analysis	125
15.2.1 Theory	125
15.2.2 Programming	126
15.3 Demo programs	126
15.3.1 Multilinear regression	127
15.3.2 Polynomial regression	128
15.3.3 Principal component analysis	128
16 Nonlinear regression	131
16.1 Theory	131
16.2 Monte-Carlo simulation	133
16.3 Regression procedures	134
16.3.1 Optimization methods	134
16.3.2 Maximal number of parameters	134
16.3.3 Parameter bounds	134
16.3.4 Nonlinear regression	135
16.3.5 Monte-Carlo simulation	136
16.4 Demo programs	136
16.4.1 Nonlinear regression	136
16.4.2 Monte-Carlo simulation	138
17 Library of nonlinear regression models	139
17.1 Common features	140
17.1.1 Procedures	140
17.1.2 Optimization methods and initial parameters	140
17.2 Regression models	141
17.2.1 Rational fractions	141
17.2.2 Sums of exponentials	142
17.2.3 Increasing exponential	142
17.2.4 Exponential + Linear	143
17.2.5 Logistic functions	143
17.2.6 Power function	144
17.2.7 Gamma distribution	144

17.2.8	Michaelis equation	145
17.2.9	Integrated Michaelis equation	145
17.2.10	Hill equation	146
17.2.11	Acid-base titration curve	147
17.3	Demo programs	147
17.3.1	Examples	147
17.3.2	Validation program	148
18	String functions	151
18.1	Trim functions	151
18.2	Fill functions	151
18.3	Character replacement	152
18.4	Parsing	152
18.5	Formatting functions	152
19	Graphic functions	153
19.1	Introduction	153
19.2	BGI graphics	153
19.2.1	Initializing graphics	153
19.2.2	Coordinate axes	154
19.2.3	Titles and fonts	155
19.2.4	Clipping	156
19.2.5	Curves	156
19.2.6	Function plot	159
19.2.7	Legends	159
19.2.8	Contour plots	159
19.2.9	Coordinate conversion	160
19.2.10	Leaving graphics	160
19.3	Delphi graphics	160
19.3.1	Initializing graphics	160
19.3.2	Coordinate axes	161
19.3.3	Titles and fonts	161
19.3.4	Curves	161
19.3.5	Other functions	162
19.4	L ^A T _E X graphics	162
19.4.1	Initializing graphics	162
19.4.2	Axes and titles	163
19.4.3	Curves	164
19.4.4	Other functions	164
19.5	Demo programs	165
19.5.1	BGI programs	165

19.5.2	Delphi programs	165
19.5.3	L ^A T _E Xprogram	166
20	Expression evaluation	167
20.1	Numbers	167
20.2	Operators	168
20.3	Parentheses	168
20.4	Variables	169
20.5	Functions	169
20.6	Exported functions	169
20.6.1	InitEval	169
20.6.2	Eval	170
20.6.3	SetVariable	170
20.6.4	SetFunction	170
20.7	Demo programs	171

Chapter 1

Installation and compilation

1.1 Introduction

Welcome to TPMath, a mathematical package for Pascal compilers. This chapter explains how to install this library and how to compile a program which uses it.

1.2 Unpacking the archive

Extract the archive `tpmat[...].zip` (where [...] stands for version number) in a given directory.

Be sure to preserve the directory structure. For instance, if you use `pkunzip`, add the option `-d` (i. e. `pkunzip -d tpmat[...].zip`).

1.3 Compilation with a 32-bit compiler

TPMath can be compiled with Delphi under Windows and with FreePascal (FPC) under Windows and Linux.

By default, TPMath is intended to be used as a shared library, such as a Windows DLL. Compilation scripts are supplied in the `dll` subdirectory to generate the shared library file, the interface file and (in the case of FPC) the object files. The following table displays the different possibilities:

Compiler / OS	Script	Shared lib.	Interface	Object
Delphi / Windows	<code>dcompil.bat</code>	<code>tpmath.dll</code>	<code>tpmath.dcu</code>	
FPC / Windows	<code>fpcompil.bat</code>	<code>tpmath.dll</code>	<code>tpmath.ppu</code>	<code>tpmath.o</code>
FPC / Linux	<code>fpcompil.sh</code>	<code>libtpmath.so</code>	<code>tpmath.ppu</code>	<code>tpmath.o</code>

Notes:

1. The only difference between the FPC and Delphi versions concerns the graphic library. With FPC it uses the Borland Graphics Interface (BGI) by means of the built-in `graph` unit, while with Delphi it uses the graphic components (e. g. a `TImage` component).
2. BGI graphics will work under Linux only if `SVGAlib` is installed and functional.
3. Some FPC versions may generate an additional file: `libimptpmath.a` which is an import library.

In order to compile the library:

1. Run the appropriate script from the command line in the `d11` subdirectory.
2. Copy the shared library file to the appropriate directory, e. g. `\Windows\System` or `/usr/lib`
3. Copy the interface file, the object file and the import library (if any) to the directory where the compiler stores its units (or to any directory which is in the unit search path)

1.4 Compilation of a program

In order to use the library in a program, add the line:

```
uses tpmath;
```

at the beginning of the program.

Note: with FPC, the library is compiled in the Delphi mode (option `-Mdelphi`) to ensure that the `Integer` type is 32-bit. The programs should be compiled with the same option (modify the FPC configuration file if necessary).

1.5 Linking to individual units

If you use only a small number of procedures, it may be more efficient to call the individual units rather than the shared library. This may be done by replacing the reference to unit `tpmath` by references to the individual units. Unit `utypes` should always be present, together with the units containing the routines called by the program (see file `filelist.txt` in the `units` sub-directory for a list of available units and procedures).

1.6 Compilation with a 16-bit compiler

In order to use the library with a 16-bit compiler (such as Turbo Pascal or Delphi 1.0) :

1. Make sure that the options ‘Force far calls’ and ‘8087’ (or emulation) are activated. On the command line:

`-$F+ -$N+`

2. Define the symbol `_16BIT` in the ‘Conditional defines’. On the command line:

`-D_16BIT`

3. Link to individual units

Chapter 2

Numeric precision

This chapter explains how to set the mathematical precision for the computations involving real numbers.

2.1 Numeric precision

TPMath allows you to use three floating point types `Single` (4-byte real, about 6 significant digits), `Double` (8-byte real, about 15 significant digits), or `Extended` (10-byte real, about 18 significant digits).

The choice of a given type is done by defining a compilation symbol: `SINGLEREAL`, `DOUBLEREAL` or `EXTENDEDREAL`.

The symbol may be defined on the command line, using the `-d` option (e. g. `dcc32 prog.pas -dEXTENDEDREAL ...`) or in the IDE.

If no symbol is defined, then type `Double` will be automatically selected. It is therefore the default type.

If another type is desired, it will be necessary to recompile the library.

Also, if you wish to compare the results given by a TPMATH program with those of a reference program written in another language (e. g. Fortran), be sure that the two programs have been compiled with the same numeric precision.

2.2 Type Float

TPmath defines a type `Float` for real numbers. It corresponds to `Single`, `Double` or `Extended`, according to the compilation options.

So, a program which uses real variables should begin with something like:

```
uses
  tpmath;
var
  X : Float;
```

2.3 Type Complex

For complex numbers, a `Complex` type is defined as follows:

```
type Complex = record
  X, Y : Float;
end;
```

2.4 Size of types

The sizes (in bytes) of the different types are given by the following constants:

```
FltSize   for Float
CompSize  for Complex
IntSize   for Integer
BoolSize  for Boolean
StrSize   for String
PtrSize   for Pointer
```

2.5 Machine-dependent constants

TPMath defines the following constants:

Constant	Meaning
MachEp	The smallest real number such that $(1.0 + \text{MachEp})$ has a different representation (in the computer memory) than 1.0; it may be viewed as a measure of the numeric precision which can be reached within the given floating point type.
MaxNum	The highest real number which can be represented.
MinNum	The lowest positive real number which can be represented.
MaxLog	The highest real number X for which Exp(X) can be computed without overflow.
MinLog	The lowest (negative) real number X for which Exp(X) can be computed without underflow.
MaxFac	The highest integer for which the factorial can be computed.
MaxGam	The highest real number for which the Gamma function can be computed.
MaxLgm	The highest real number for which the logarithm of the Gamma function can be computed.

2.6 Demo program

The program `testmach.pas` located in the `demo\fmath` subdirectory checks that the machine-dependent constants are correctly handled by the computer.

This program lists the sizes of the integer and floating point types, together with the values of the machine-dependent constants, and computes the following quantities:

Exp(MinLog)	Should be approximately equal to MinNum
Ln(MinNum)	Should be approximately equal to MinLog
Exp(MaxLog)	Should be approximately equal to MaxNum
Ln(MaxNum)	Should be approximately equal to MaxLog
Fact(MaxFac)	
Gamma(MaxGam)	Should be computed without overflow.
LnGamma(MaxLgm)	

The following results were obtained with FPC in double precision:

```

Integer type           = Integer (4 bytes)
Long Integer type      = LongInt (4 bytes)
Floating point type    = Double (8 bytes)
Complex type           = Complex (16 bytes)

```

MachEp	=	2.2204460492503130E-0016
MinNum	=	2.2250738585072020E-0308
Exp(MinLog)	=	2.2250738585072152E-0308
MinLog	=	-7.0839641853226410E+0002
Ln(MinNum)	=	-7.0839641853226411E+0002
MaxNum	=	1.7976931348623150E+0308
Exp(MaxLog)	=	1.7976931348623216E+0308
MaxLog	=	7.0978271289338400E+0002
Ln(MaxNum)	=	7.0978271289338400E+0002
MaxFac	=	170
Fact(MaxFac)	=	7.257415615307999E+306
MaxGam	=	1.7162437695630200E+0002
Gamma(MaxGam)	=	1.797693134862315E+308
MaxLgm	=	2.5563480000000000E+0305
LnGamma(MaxLgm)	=	1.795136671459441E+308

Chapter 3

Elementary functions

This chapter describes the mathematical constants and elementary mathematical functions available in TPMath.

3.1 Constants

The following mathematical constants are defined:

Constant	Value	Meaning
Pi	3.14159...	π
Ln2	0.69314...	$\ln 2$
Ln10	2.30258...	$\ln 10$
LnPi	1.14472...	$\ln \pi$
InvLn2	1.44269...	$1/\ln 2$
InvLn10	0.43429...	$1/\ln 10$
TwoPi	6.28318...	2π
PiDiv2	1.57079...	$\pi/2$
SqrtPi	1.77245...	$\sqrt{\pi}$
Sqrt2Pi	2.50662...	$\sqrt{2\pi}$
InvSqrt2Pi	0.39894...	$1/\sqrt{2\pi}$
LnSqrt2Pi	0.91893...	$\ln \sqrt{2\pi}$
Ln2PiDiv2	0.91893...	$(\ln 2\pi)/2$
Sqrt2	1.41421...	$\sqrt{2}$
Sqrt2Div2	0.70710...	$\sqrt{2}/2$
Gold	1.61803...	Golden Ratio = $(1 + \sqrt{5})/2$
CGold	0.38196...	

Note : The constants are stored with 20 to 21 significant digits. So, they will match the highest degree of precision available (i.e. type **Extended**).

3.2 Error handling

The function `MathErr()` returns the error code from the last function evaluation. It must be checked immediately after a function call:

```
Y := f(X); { f is one of the functions of the library }  
if MathErr = FOk then ...
```

If an error occurs, a default value is attributed to the function. The possible error codes are the following:

Error code	Value	Meaning
FOk	0	No error
FDomain	-1	Argument domain error
FSing	-2	Function singularity
FOverflow	-3	Overflow range error
FUnderflow	-4	Underflow range error
FTLoss	-5	Total loss of precision
FPLoss	-6	Partial loss of precision

3.3 Min, max and exchange

- Function `FMin(X, Y)` returns the minimum of two real numbers X, Y .
- Function `IMin(X, Y)` returns the minimum of two integer numbers X, Y .
- Function `FMax(X, Y)` returns the maximum of two real numbers X, Y .
- Function `IMax(X, Y)` returns the maximum of two integer numbers X, Y .
- Function `FSwap(X, Y)` exchanges two real numbers X, Y .
- Function `ISwap(X, Y)` exchanges two integer numbers X, Y .

3.4 Sign

- Function **Sgn**(*X*) returns 1 if $X \geq 0$, -1 if $X < 0$.
- Function **Sgn0**(*X*) returns 1 if $X > 0$, 0 if $X = 0$, -1 if $X < 0$.
- Function **DSgn**(*A*, *B*) transfers the sign of *B* to *A*. It is therefore equivalent to: **Sgn**(*B*) * **Abs**(*A*)

3.5 Rounding functions

- Function **RoundN**(*X*, *N*) will round *X* to *N* decimal places. *N* must be between 0 and 16.
- Function **Floor**(*X*) returns the lowest integer $\geq X$
- Function **Ceil**(*X*) returns the highest integer $\leq X$

3.6 Logarithms and exponentials

The functions **Expo** and **Log** may be used instead of the standard functions **Exp** and **Ln**, when it is necessary to check the range of the argument. The new function performs the required tests and calls the standard function if the argument is within the acceptable limits (for instance, $X > 0$ for **Ln**(*X*)); otherwise, the function returns a default value and **MathErr**() will return the appropriate error code.

Calling these functions is more time-consuming than calling the standard **Exp** and **Ln**, because each function involves several tests and two procedure calls (one to the function itself and another to the standard **Exp** or **Ln**). Hence, if the program must compute lots of logarithms or exponentials, it may be more efficient to use the standard functions **Exp** and **Ln**. In this case, however, the error handling must be done by the main program.

The same remark applies to the other logarithmic and exponential functions defined in the library:

Function	Definition	Pascal code
Exp2 (<i>X</i>)	2^X	Exp (<i>X</i> * Ln2)
Exp10 (<i>X</i>)	10^X	Exp (<i>X</i> * Ln10)
Log2 (<i>X</i>)	$\log_2 X$	Ln (<i>X</i>) * InvLn2
Log10 (<i>X</i>)	$\log_{10} X$	Ln (<i>X</i>) * InvLn10
LogA (<i>X</i> , <i>A</i>)	$\log_A X$	Ln (<i>X</i>) / Ln (<i>A</i>)

Here, too, it may be more efficient to use the Pascal code *inline* rather than calling the `TPMath` function, but the error control will be lost.

3.7 Power functions

- Function `Power(X, Y)` returns X^Y . Y may be integer or real, but if Y is real then X cannot be negative.
- Function `IntPower(X, N)` returns X^N where N is integer.

Note: To ensure the continuity of the function X^X when $X \rightarrow 0$, the value 0^0 has been set to 1.

3.8 Trigonometric functions

In addition to the standard Pascal functions `Sin`, `Cos` and `ArcTan`, `TPMath` provides the following functions:

Function	Definition
<code>Tan(X)</code>	$\frac{\sin X}{\cos X} \quad X \neq (2k+1)\frac{\pi}{2}$
<code>ArcSin(X)</code>	$\arctan \frac{X}{\sqrt{1-X^2}} \quad (-1 < X < 1)$
<code>ArcCos(X)</code>	$\frac{\pi}{2} - \arcsin X \quad (-1 < X < 1)$
<code>Pythag(X, Y)</code>	$\sqrt{X^2 + Y^2}$
<code>ArcTan2(Y, X)</code>	$\arctan \frac{Y}{X}$, result in $[-\pi, \pi]$
<code>FixAngle(Theta)</code>	Returns the angle <code>Theta</code> in the range $[-\pi, \pi]$

Note: If (X, Y) are the cartesian coordinates of a point in the plane, its polar coordinates are:

```
R := Pythag(X, Y);
Theta := ArcTan2(Y, X)
```

3.9 Hyperbolic functions

The following functions are available:

Function	Definition
Sinh(X)	$\frac{1}{2}(e^X - e^{-X})$
Cosh(X)	$\frac{1}{2}(e^X + e^{-X})$
Tanh(X)	$\frac{\sinh X}{\cosh X}$
ArcSinh(X)	$\ln(X + \sqrt{X^2 + 1})$
ArcCosh(X)	$\ln(X + \sqrt{X^2 - 1}) \quad X > 1$
ArcTanh(X)	$\frac{1}{2} \ln \frac{X+1}{X-1} \quad -1 < X < 1$

In addition, the subroutine **SinhCosh(X, SinhX, CoshX)** computes the hyperbolic sine and cosine simultaneously, saving the computation of one exponential.

3.10 Demo programs

These program are located in the `demo\fmath` subdirectory.

3.10.1 Function accuracy

Program `testfunc.pas` checks the accuracy of the elementary functions. For each function, 20 random arguments are picked, then the function is computed, the reciprocal function is applied to the result, and the relative error between this last result and the original argument is computed. This error should be around 10^{-15} in double precision.

3.10.2 Computation speed

Program `speed.pas` measures the execution time of the built-in mathematical functions, as well as the additional functions provided in **TPMath**. The results are printed on the screen and saved in a text file named `speed.out`.

Chapter 4

Special functions

This chapter describes the special functions available in **TPMath**. Most of them have been adapted from C codes in the Cephès library by S. Moshier (<http://www.moshier.net>).

4.1 Factorial

Function **Fact(N)** returns the factorial of the non-negative integer N , also noted $N!$:

$$N! = 1 \times 2 \times \cdots \times N \quad 0! = 1$$

The constant **MaxFac** defines the highest integer for which the factorial can be computed (See chapter 2, p. 16).

4.2 Gamma function

- Function **Gamma(X)** returns the Gamma function, defined by:

$$\Gamma(X) = \int_0^{\infty} t^{X-1} e^{-t} dt$$

This function is related to the factorial by:

$$N! = \Gamma(N + 1)$$

The Gamma function is indefinite for $X = 0$ and for negative integer values of X . It is positive for $X > 0$. For $X < 0$ the Gamma function changes its sign whenever X crosses an integer value. More precisely, if X is an even negative integer, $\Gamma(X)$ is positive on the interval $]X, X+1[$, otherwise it is negative.

- Function **SgnGamma(X)** returns the sign of the Gamma function for a given value of X .
- Function **LnGamma(X)** returns the natural logarithm of the Gamma function.
- Function **Stirling(X)** approximates **Gamma(X)** with Stirling's formula, for $X \geq 30$.
- Function **StirLog(X)** approximates **LnGamma(X)** with Stirling's formula, for $X \geq 13$.

The constants **MaxGam** and **MaxLgm** define the highest values for which the Gamma function and its logarithm, respectively, can be computed (See chapter 2, p. 16).

- Function **IGamma(A, X)** returns the incomplete Gamma function, defined by:

$$\frac{1}{\Gamma(A)} \int_0^X t^{A-1} e^{-t} dt \quad A > 0, X > 0$$

- Function **JGamma(A, X)** returns the complement of the incomplete Gamma function, defined by:

$$\frac{1}{\Gamma(A)} \int_X^\infty t^{A-1} e^{-t} dt$$

Although formally equivalent to $1.0 - \text{IGamma}(A, X)$, this function uses specific algorithms to minimize roundoff errors.

- Function **InvGamma(A, Y)** returns X such that $\text{IGamma}(A, X) = Y$

4.3 Polygamma functions

The polygamma function of order n , denoted $\psi_n(x)$, is the n -th derivative of the logarithm of the gamma function:

$$\psi_n(x) = \frac{d^n}{dx^n} \ln \Gamma(x)$$

The cases $n = 1$ and $n = 2$ are implemented in **TPMath** as **DiGamma(X)** and **TriGamma(X)**

4.4 Beta function

- Function `Beta(X, Y)` returns the Beta function, defined by:

$$\mathcal{B}(X, Y) = \int_0^1 t^{X-1}(1-t)^{Y-1} dt = \frac{\Gamma(X)\Gamma(Y)}{\Gamma(X+Y)}$$

(Here \mathcal{B} denotes the uppercase greek letter ‘Beta’ !)

- Function `IBeta(A, B, X)` returns the incomplete Beta function, defined by:

$$\frac{1}{\mathcal{B}(A, B)} \int_0^X t^{A-1}(1-t)^{B-1} dt \quad A > 0, B > 0, 0 \leq X \leq 1$$

- Function `InvBeta(A, B, Y)` returns X such that `IBeta(A, B, X) = Y`

4.5 Error function

- Function `Erf(X)` returns the error function, defined by:

$$\text{erf}(X) = \frac{2}{\sqrt{\pi}} \int_0^X \exp(-t^2) dt$$

- Function `Erfc(X)` returns the complement of the error function, defined by:

$$\text{erfc}(X) = \frac{2}{\sqrt{\pi}} \int_X^\infty \exp(-t^2) dt$$

4.6 Lambert’s function

Lambert’s W function is the reciprocal of the function xe^x . That is, if $y = W(x)$, then $x = ye^y$. Lambert’s function is defined for $x \geq -1/e$, with $W(-1/e) = -1$. When $-1/e < x < 0$, the function has two values; the value $W(x) > -1$ defines the *upper branch*, the value $W(x) < -1$ defines the *lower branch*.

The function `LambertW(X, UBranch, Offset)` computes Lambert’s function.

- X is the argument of the function (must be $\geq -1/e$)

- **UBranch** is a boolean parameter which must be set to **True** for computing the upper branch of the function and to **False** for computing the lower branch.
- **Offset** is a boolean parameter indicating if **X** is an offset from $-1/e$. In this case, $W(X - 1/e)$ will be computed (with $X > 0$). Using offsets improves the accuracy of the computation if the argument is near $-1/e$.

The code for Lambert's function has been translated from a Fortran program written by Barry *et al* (<http://www.netlib.org/toms/743>).

4.7 Demo programs

- Program **specfunc.pas**, located in the **demo\fmath** subdirectory, checks the accuracy of the functions **Fact**, **Binomial**, **Gamma**, **IGamma**, **Erf**, **Erfc**, **Beta**, **IBeta**, **DiGamma** and **TriGamma**

Most of the data come from *Numerical Recipes* (<http://www.nr.com>), but the reference values have been re-computed to 20 significant digits with the **Maple** software (<http://www.maplesoft.com>) and the Gamma values for negative arguments have been corrected.

Each program computes the values of a given function for a set of predefined arguments and compares the results to the reference values. Then it displays the number of correct digits found. This number should be between 14 and 16 in double precision.

- Program **testw.pas** checks the accuracy of the Lambert function.

The program computes Lambert's function for a set of pre-defined arguments and compares the results with reference values. It displays the number of exact digits found. This number should correspond with the numeric precision used (14-16 digits in double precision).

This program has been translated from a Fortran program written by Barry *et al* (<http://www.netlib.org/toms/743>).

Chapter 5

Probability distributions

This chapter describes the functions available in `TPMath` to compute probability distributions. Most of them are applications of the special functions studied in chapter 4.

5.1 Binomial distribution

Binomial distribution arises when a trial has two possible outcomes: ‘failure’ or ‘success’. If the trial is repeated N times, the random variable X is the number of successes.

- Function `Binomial(N, K)` returns the binomial coefficient $\binom{N}{K}$, which is defined by:

$$\binom{N}{K} = \frac{N!}{K!(N-K)!} \quad 0 \leq K \leq N$$

- Function `PBinom(N, P, K)` returns the probability of obtaining K successes among N repetitions, if the probability of success is P .

$$\text{Prob}(X = K) = \binom{N}{K} P^K Q^{N-K} \quad \text{with } Q = 1 - P$$

- Function `FBinom(N, P, K)` returns the probability of obtaining at most K successes among N repetitions, i. e. $\text{Prob}(X \leq K)$. This is called the *cumulative probability function* and is defined by:

$$\text{Prob}(X \leq K) = \sum_{k=0}^K \binom{N}{k} P^k Q^{N-k} = 1 - I_{\mathcal{B}}(K+1, N-K, P)$$

where $I_{\mathcal{B}}$ denotes the incomplete Beta function.

The mean of the binomial distribution is $\mu = NP$, its variance is $\sigma^2 = NPQ$. The standard deviation is therefore $\sigma = \sqrt{NPQ}$.

5.2 Poisson distribution

The Poisson distribution can be considered as the limit of the binomial distribution when $N \rightarrow \infty$ and $P \rightarrow 0$ while the mean $\mu = NP$ remains small (say $N \geq 30$, $P \leq 0.1$, $NP \leq 10$)

- Function `PPoisson(Mu, K)` returns the probability of observing the value K if the mean is μ . It is defined by:

$$\text{Prob}(X = K) = e^{-\mu} \frac{\mu^K}{K!}$$

- Function `FPoisson(Mu, K)` gives the cumulative probability function, defined by:

$$\text{Prob}(X \leq K) = \sum_{k=0}^K e^{-\mu} \frac{\mu^k}{k!} = 1 - I_{\Gamma}(K+1, \mu)$$

where I_{Γ} denotes the incomplete Gamma function.

5.3 Standard normal distribution

The normal distribution (a. k. a. Gauss distribution or Laplace-Gauss distribution) corresponds to the classical bell-shaped curve. It may also be considered as a limit of the binomial distribution when N is sufficiently ‘large’ while P and Q are sufficiently different from 0 or 1. (say $N \geq 30$, $NP \geq 5$, $NQ \geq 5$).

The normal distribution with mean μ and standard deviation σ is denoted $\mathcal{N}(\mu, \sigma)$ with $\mu = NP$ and $\sigma = \sqrt{NPQ}$. The special case $\mathcal{N}(0, 1)$ is called the standard normal distribution.

- Function `DNorm(X)` returns the probability density of the standard normal distribution, defined by:

$$f(X) = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{X^2}{2}\right)$$

The graph of this function is the bell-shaped curve.

- Function **FNorm(X)** returns the cumulative probability function:

$$\Phi(X) = \text{Prob}(U \leq X) = \int_{-\infty}^X f(x)dx = \frac{1}{2} \left[1 + \text{erf} \left(X \frac{\sqrt{2}}{2} \right) \right]$$

where U denotes the standard normal variable and erf the error function.

- Function **PNorm(X)** returns the probability that the standard normal variable exceeds X in absolute value, i. e. $\text{Prob}(|U| > X)$.
- Function **InvNorm(P)** returns the value X such that $\Phi(X) = P$.

5.4 Student's distribution

Student's distribution is widely used in Statistics, for instance to estimate the mean of a population from a sample taken from this population. The distribution depends on an integer parameter ν called the *number of degrees of freedom* (in the mean estimation problem, $\nu = n - 1$ where n is the number of individuals in the sample). When ν is large (say > 30) the Student distribution is approximately equal to the standard normal distribution.

- Function **DStudent(Nu, X)** returns the probability density of the Student distribution with Nu degrees of freedom, defined by:

$$f_{\nu}(X) = \frac{1}{\nu^{1/2} \mathcal{B}\left(\frac{\nu}{2}, \frac{1}{2}\right)} \cdot \left(1 + \frac{X^2}{\nu}\right)^{-\frac{\nu+1}{2}}$$

where \mathcal{B} denotes the Beta function.

- Function **FStudent(Nu, X)** returns the cumulative probability function:

$$\Phi_{\nu}(X) = \text{Prob}(t \leq X) = \int_{-\infty}^X f_{\nu}(x)dx = \begin{cases} I/2 & \text{if } X \leq 0 \\ 1 - I/2 & \text{if } X > 0 \end{cases}$$

where t denotes the Student variable and $I = I_{\mathcal{B}}\left(\frac{\nu}{2}, \frac{1}{2}, \frac{\nu}{\nu+X^2}\right)$

- Function **PStudent(Nu, X)** returns the probability that the Student variable t exceeds X in absolute value, i. e. $\text{Prob}(|t| > X)$.
- Function **InvStudent(Nu, P)** returns the value X such that $\Phi_{\nu}(X) = P$.

5.5 Khi-2 distribution

The χ^2 distribution is a special case of the Gamma distribution (see below). It depends on an integer parameter ν which is the number of degrees of freedom.

- Function `DKhi2(Nu, X)` returns the probability density of the χ^2 distribution with `Nu` degrees of freedom, defined by:

$$f_\nu(X) = \frac{1}{2^{\frac{\nu}{2}} \Gamma\left(\frac{\nu}{2}\right)} \cdot X^{\frac{\nu}{2}-1} \cdot \exp\left(-\frac{X}{2}\right) \quad (X > 0)$$

- Function `FKhi2(Nu, X)` returns the cumulative probability function:

$$\Phi_\nu(X) = \text{Prob}(\chi^2 \leq X) = \int_0^X f_\nu(x) dx = I_\Gamma\left(\frac{\nu}{2}, \frac{X}{2}\right)$$

where I_Γ denotes the incomplete Gamma function.

- Function `PKhi2(Nu, X)` returns the probability that the χ^2 variable exceeds X , i. e. $\text{Prob}(\chi^2 > X)$.
- Function `InvKhi2(Nu, P)` returns the value X such that $\Phi_\nu(X) = P$.

5.6 Snedecor's distribution

The Snedecor (or Fisher-Snedecor) distribution is used mainly to compare two variances. It depends on two integer parameters ν_1 and ν_2 which are the degrees of freedom associated with the variances.

- Function `DSnedecor(Nu1, Nu2, X)` returns the probability density of the Snedecor distribution with `Nu1` and `Nu2` degrees of freedom, defined by:

$$f_{\nu_1, \nu_2}(X) = \frac{1}{\mathcal{B}\left(\frac{\nu_1}{2}, \frac{\nu_2}{2}\right)} \cdot \left(\frac{\nu_1}{\nu_2}\right)^{\frac{\nu_1}{2}} \cdot X^{\frac{\nu_1}{2}-1} \cdot \left(1 + \frac{\nu_1}{\nu_2} X\right)^{-\frac{\nu_1+\nu_2}{2}} \quad (X > 0)$$

- Function `FSnedecor(Nu1, Nu2, X)` returns the cumulative probability function:

$$\Phi_{\nu_1, \nu_2}(X) = \text{Prob}(F \leq X) = \int_0^X f_{\nu_1, \nu_2}(x) dx = 1 - I_{\mathcal{B}}\left(\frac{\nu_2}{2}, \frac{\nu_1}{2}, \frac{\nu_2}{\nu_2 + \nu_1 X}\right)$$

where F denotes the Snedecor variable.

- Function `PSnedecor(Nu1, Nu2, X)` returns the probability that the Snedecor variable F exceeds X , i. e. $\text{Prob}(F > X)$.
- Function `InvSnedecor(Nu1, Nu2, P)` returns the value X such that $\Phi_{\nu_1, \nu_2}(X) = P$.

5.7 Exponential distribution

The exponential distribution is used in many applications (radioactivity, chemical kinetics...). It depends on a positive real parameter A .

- Function `DExpo(A, X)` returns the probability density of the exponential distribution with parameter A , defined by:

$$f_A(X) = A \exp(-AX) \quad (X > 0)$$

- Function `FExpo(A, X)` returns the cumulative probability function:

$$\Phi_A(X) = \int_0^X f_A(x) dx = 1 - \exp(-AX)$$

5.8 Beta distribution

The Beta distribution is often used to describe the distribution of a random variable defined on the unit interval $[0, 1]$. It depends on two positive real parameters A and B .

- Function `DBeta(A, B, X)` returns the probability density of the Beta distribution with parameters A and B , defined by:

$$f_{A,B}(X) = \frac{1}{\mathcal{B}(A, B)} \cdot X^{A-1} \cdot (1 - X)^{B-1} \quad (0 \leq X \leq 1)$$

- Function `FBeta(A, B, X)` returns the cumulative probability function:

$$\Phi_{A,B}(X) = \int_0^X f_{A,B}(x) dx = I_B(A, B, X)$$

5.9 Gamma distribution

The Gamma distribution is often used to describe the distribution of a random variable defined on the positive real axis. It depends on two positive real parameters A and B .

- Function `DGamma(A, B, X)` returns the probability density of the Gamma distribution with parameters A and B , defined by:

$$f_{A,B}(X) = \frac{B^A}{\Gamma(A)} \cdot X^{A-1} \cdot \exp(-BX) \quad (X > 0)$$

- Function `FGamma(A, B, X)` returns the cumulative probability function:

$$\Phi_{A,B}(X) = \int_0^X f_{A,B}(x)dx = I_\Gamma(A, BX)$$

The χ^2 distribution is a special case of the Gamma distribution, with $A = \nu/2$ and $B = 1/2$.

5.10 Demo program

Program `binom.pas`, located in the `demo\proba` subdirectory, compares the cumulative probabilities of the binomial distribution, estimated by function `FBinom`, with the values obtained by summing up the individual probabilities.

Chapter 6

Matrices and linear equations

This chapter describes the procedures and functions available in `TPMath` to perform vector and matrix operations, and to solve systems of linear equations.

6.1 Using vectors and matrices

`TPMath` defines the following dynamic array types:

Vector type	Matrix type	Base variable
<code>PVector</code>	<code>PMatrix</code>	Floating point number (type <code>Float</code>)
<code>PIntVector</code>	<code>PIntMatrix</code>	Integer
<code>PCompVector</code>	<code>PCompMatrix</code>	Complex number (type <code>Complex</code>)
<code>PBoolVector</code>	<code>PBoolMatrix</code>	Boolean
<code>PStrVector</code>	<code>PStrMatrix</code>	String

To use these arrays in your programs, you must:

1. Declare variables of the appropriate type, then allocate each array *before* using it:

```
var
  V : PVector;
  A : PMatrix;
begin
  DimVector(V, N);      { creates vector V[0..N] }
  DimMatrix(A, N, M);   { creates matrix A[0..N, 0..M] }
                        { N, M are integer variables }
  ...
end.
```

If the allocation does not succeed, the array is given the value `nil`. So, it is possible to test the result:

```
DimVector(V, 10000);
if V = nil then
  Write('Not enough memory!');
```

Note that this allocation step is mandatory, because these dynamic arrays are, in fact, pointers. Unlike standard Pascal arrays, it is not sufficient to declare the variables!

2. Use arrays as in standard Pascal, noting that:
 - (a) You must use the indirection operator (\wedge) to reference any array element, i.e. write $V^\wedge[I]$ and $A^\wedge[I]^\wedge[J]$ instead of $V[I]$ and $A[I, J]$.
 - (b) You cannot use the assignment operator ($:=$) to copy the contents of an array into another array. Writing $B := A$ simply makes B point to the same memory block than A .
 - (c) All arrays begin at index 0, so that the 0-indexed element is always present, even if you don't use it.
 - (d) A matrix is declared as an array of vectors, so that $A^\wedge[I]$ denotes the I -th vector of matrix A and may be used as any vector.
 - (e) Vector and matrix parameters must be passed to functions or procedures with the `var` attribute when these parameters are dimensioned inside the procedure. Otherwise, this attribute is not necessary.

3. To deallocate an array, use the `Del...` procedures:

```
DelVector(V, N);
DelMatrix(A, N, M);
```

See file `tpmath.pas` in the `d11` subdirectory for a list of available `Dim...` and `Del...` procedures.

6.2 Maximal array sizes

The maximal array size depends on the maximal size of a variable ($2^{16} = 65536$ (64 kilo) bytes for a 16-bit compiler, $2^{31} = 2147483648$ (2 giga) bytes for a 32-bit compiler), and on the size of the base type. For an `array[0..N]` of type `T`, the maximal value of `N` is given by the formula:

```
N := Trunc(MaxSize / SizeOf(T)) - 2;
```

The sizes for the different base types are given by the following constants:

```
MAX_FLT   for Float
MAX_COMP  for Complex
MAX_INT   for Integer
MAX_BOOL  for Boolean
MAX_STR   for String
```

For a matrix, the maximal size in the second dimension, i. e. the number of vectors in the matrix, is given by the constant `MAX_VEC`. This value can also be computed from the previous formula, by defining `T` as `Pointer`, since a matrix is in fact an array of pointers.

6.3 Array initialization

If the allocation succeeds, all array elements are initialized to zero (for numeric arrays), `False` (for boolean arrays), or the null string (for string arrays).

This initialization step may be too slow for large arrays. It can be skipped with the statement `SetAutoInit(False)` and reactivated with `SetAutoInit(True)`.

6.4 Programming conventions

The following conventions have been adopted:

- Parameters `Lb` and `Ub` denote the lower and upper bounds of the indices, for a vector `V[Lb..Ub]` or a square matrix `A[Lb..Ub, Lb..Ub]`.
- Parameters `Lb1`, `Ub1` and `Lb2`, `Ub2` denote the lower and upper bounds of the indices, for a rectangular matrix `A[Lb1..Ub1, Lb2..Ub2]`.
- With the exception of the memory allocation routines (`DimVector`, `DimMatrix` ...), the procedures do not allocate the vectors or matrices present in their parameter lists. These allocations must therefore be performed by the main program, before calling the procedures.

6.5 Error codes

The following error codes are defined:

Error code	Value	Meaning
MatOk	0	No error
MatNonConv	-1	Non-convergence of an iterative procedure
MatSing	-2	Quasi-singular matrix
MatErrDim	-3	Non-compatible dimensions
MatNotPD	-4	Matrix not positive definite

6.6 Gauss-Jordan elimination

If $\mathbf{B}(n \times n)$ and $\mathbf{C}(n \times m)$ are two real matrices, the Gauss-Jordan elimination can compute the inverse matrix \mathbf{B}^{-1} , the solution \mathbf{X} to the system of linear equations $\mathbf{B}\mathbf{X} = \mathbf{C}$, and the determinant of \mathbf{B} .

This procedure is implemented in `TPMath` as the following procedure:

`GaussJordan(A, Lb, Ub1, Ub2, Det)`

where:

- On input, `A[Lb..Ub1, Lb..Ub2]` is the global matrix $[\mathbf{B}|\mathbf{C}]$, which means that:
 - the first n columns of \mathbf{A} contain the matrix \mathbf{B}
 - the other columns of \mathbf{A} contain the matrix \mathbf{C}
- On output, \mathbf{A} is transformed into the global matrix $[\mathbf{B}^{-1}|\mathbf{X}]$, which means that:
 - the first n columns of \mathbf{A} contain the inverse matrix \mathbf{B}^{-1}
 - the other columns of \mathbf{A} contain the solution matrix \mathbf{X}
- `Det` is the determinant of \mathbf{B}

Notes:

- \mathbf{C} may be a vector, in this case $m = 1$ and \mathbf{X} is also a vector.

- The original matrix **A** is overwritten by the procedure. If necessary, the calling program must save a copy of it.

After a call to `GaussJordan`, the function `MathErr` will return the error code:

- `MatOk` if no error
- `MatErrDim` if `Ub1 > Ub2`
- `MatSing` if **B** is quasi-singular

6.7 LU decomposition

The LU decomposition algorithm factors the square matrix **A** as a product **LU**, where **L** is a lower triangular matrix (with unit diagonal terms) and **U** is an upper triangular matrix.

The linear system $\mathbf{AX} = \mathbf{B}$ is then solved by:

$$\mathbf{LY} = \mathbf{B} \tag{6.1}$$

$$\mathbf{UX} = \mathbf{Y} \tag{6.2}$$

System 6.1 is solved for vector **Y**, then system 6.2 is solved for vector **X**. The solutions are simplified by the triangular nature of the matrices.

TPMath provides the following procedures:

- procedure `LU_Decomp(A, Lb, Ub)` performs the LU decomposition of matrix `A[Lb..Ub, Lb..Ub]`.

The matrices **L** and **U** are stored in **A**, which is therefore destroyed.

After a call to `LU_Decomp`, the function `MathErr` will return one of the following error codes:

- `MatOk` if no error
- `MatSing` if **A** is quasi-singular
- procedure `LU_Solve(A, B, Lb, Ub, X)` solves the system $\mathbf{AX} = \mathbf{B}$, where **X** and **B** are real vectors, once the matrix **A** has been transformed by `LU_Decomp`.

6.8 QR decomposition

This method factors a matrix \mathbf{A} as a product of an orthogonal matrix \mathbf{Q} by an upper triangular matrix \mathbf{R} :

$$\mathbf{A} = \mathbf{Q}\mathbf{R}$$

The linear system $\mathbf{A}\mathbf{X} = \mathbf{B}$ then becomes:

$$\mathbf{Q}\mathbf{R}\mathbf{X} = \mathbf{B}$$

Denoting the transpose of \mathbf{Q} by \mathbf{Q}^\top and left-multiplying by this transpose, one obtains:

$$\mathbf{Q}^\top \mathbf{Q}\mathbf{R}\mathbf{X} = \mathbf{Q}^\top \mathbf{B}$$

or:

$$\mathbf{R}\mathbf{X} = \mathbf{Q}^\top \mathbf{B}$$

since the transpose of an orthogonal matrix is equal to its inverse.

The last system is solved by making advantage of the triangular nature of matrix \mathbf{R} .

Note : The QR decomposition may be applied to a rectangular matrix $n \times m$ (with $n > m$). In this case, \mathbf{Q} has dimensions $n \times m$ and \mathbf{R} has dimensions $m \times m$. For a linear system $\mathbf{A}\mathbf{X} = \mathbf{B}$, the solution minimizes the norm of the vector $\mathbf{A}\mathbf{X} - \mathbf{B}$. It is called the *least squares* solution.

TPMath provides the following procedures:

- procedure `QR_Decomp(A, Lb, Ub1, Ub2, R)` performs the QR decomposition on the input matrix `A[Lb..Ub1, Lb..Ub2]`.

The matrix \mathbf{Q} is stored in \mathbf{A} , which is therefore destroyed.

After a call to `QR_Decomp`, the function `MathErr` will return one of the following error codes:

- `MatOk` if no error
- `MatErrDim` if `Ub2 > Ub1`
- `MatSing` if \mathbf{A} is quasi-singular

- procedure `QR_Solve(Q, R, B, Lb, Ub1, Ub2, X)` solves the system $\mathbf{Q}\mathbf{R}\mathbf{X} = \mathbf{B}$.

6.9 Singular value decomposition

Singular value decomposition (SVD) factors a matrix \mathbf{A} as a product:

$$\mathbf{A} = \mathbf{U}\mathbf{S}\mathbf{V}^\top$$

where \mathbf{U} et \mathbf{V} are orthogonal matrices. \mathbf{S} is a diagonal matrix. Its diagonal terms S_{ii} are all ≥ 0 and are called the *singular values* of \mathbf{A} . The *rank* of \mathbf{A} is equal to the number of non-null singular values.

- If \mathbf{A} is a regular matrix, all S_{ii} are > 0 . The inverse matrix is given by:

$$\mathbf{A}^{-1} = (\mathbf{U}\mathbf{S}\mathbf{V}^\top)^{-1} = (\mathbf{V}^\top)^{-1}\mathbf{S}^{-1}\mathbf{U}^{-1} = \mathbf{V} \times \text{diag}(1/S_{ii}) \times \mathbf{U}^\top$$

since the inverse of an orthogonal matrix is equal to its transpose.

So the solution of the system $\mathbf{A}\mathbf{X} = \mathbf{B}$ is given by $\mathbf{X} = \mathbf{A}^{-1}\mathbf{B}$

- If \mathbf{A} is a singular matrix, some S_{ii} are null. However, the previous expressions remain valid provided that, for each null singular value, the term $1/S_{ii}$ is replaced by zero.

It may be shown that the solution so calculated corresponds:

- in the case of an under-determined system, to the vector \mathbf{X} having the least norm.
- in the case of an impossible system, to the least-squares solution.

Note : Just like the QR decomposition, the SVD may be applied to a rectangular matrix $n \times m$ (with $n > m$). In this case, \mathbf{U} has dimensions $n \times m$, \mathbf{S} and \mathbf{V} have dimensions $m \times m$. For a linear system $\mathbf{A}\mathbf{X} = \mathbf{B}$, the SVD method gives the least squares solution.

TPMath provides the following procedures:

- procedure `SV_Decomp(A, Lb, Ub1, Ub2, S, V)` performs the singular value decomposition on the input matrix $\mathbf{A}[\text{Lb}..\text{Ub1}, \text{Lb}..\text{Ub2}]$.

The matrix \mathbf{U} (such that $\mathbf{A} = \mathbf{U}\mathbf{S}\mathbf{V}^\top$) is stored in \mathbf{A} , which is therefore destroyed.

After a call to `SV_Decomp`, the function `MathErr` will return one of the following error codes:

- **MatOk** if no error
- **MatErrDim** if $Ub2 > Ub1$
- **MatNonConv** if the iterative process does not converge
- procedure **SV_SetZero**(**S**, **Lb**, **Ub**, **Tol**) sets to zero the singular values S_i which are lower than a fraction **Tol** of the highest singular value. This procedure may be used when solving a system with a near-singular matrix.
- procedure **SV_Solve**(**U**, **S**, **V**, **B**, **Lb**, **Ub1**, **Ub2**, **X**) solves the system $\mathbf{USV}^T \mathbf{X} = \mathbf{B}$.
- procedure **SV_Approx**(**U**, **S**, **V**, **Lb**, **Ub1**, **Ub2**, **A**) approximates a matrix **A** by the product \mathbf{USV}^T , after the lowest singular values have been set to zero by **SV_SetZero**.

6.10 Eigenvalues and eigenvectors

6.10.1 Definitions

A square matrix **A** is said to have an eigenvalue λ , associated to an eigenvector **V**, if and only if:

$$\mathbf{A} \cdot \mathbf{V} = \lambda \cdot \mathbf{V}$$

A symmetric matrix of size n has n distinct real eigenvalues and n orthogonal eigenvectors.

A non-symmetric matrix of size n has also n eigenvalues but some of them may be complex, and some may be equal (they are said to be degenerate).

6.10.2 Symmetric matrices

- Procedure **EigenSym**(**A**, **Lb**, **Ub**, **V**, **Lambda**) computes the eigenvalues and eigenvectors of the real symmetric positive semi-definite matrix **A**[**Lb**..**Ub**, **Lb**..**Ub**] by singular value decomposition.

The eigenvectors are returned in matrix **V**; the eigenvalues are returned in vector **Lambda**.

The eigenvectors are stored along the columns of **V**. They are normalized, with their first component always positive.

The error codes are those of the **SV_Decom** procedure.

- Procedure `Jacobi(A, Lb, Ub, MaxIter, Tol, V, Lambda)` computes the eigenvalues and eigenvectors of the real symmetric matrix `A[Lb..Ub, Lb..Ub]`, using the iterative method of Jacobi. The eigenvalues and eigenvectors are ordered and normalized as with the previous procedure.

`MaxIter` is the maximum number of iterations, `Tol` is the required precision on the eigenvalues.

After a call to `Jacobi`, function `MathErr` returns one of two error codes:

- `MatOk` if all goes well.
- `MatNonConv` if the iterative process does not converge.

These procedures destroy the original matrix `A`.

6.10.3 General square matrices

- procedure `EigenVals(A, Lb, Ub, Lambda)` computes the eigenvalues of the real square matrix `A[Lb..Ub, Lb..Ub]`.

Eigenvalues are stored in the complex vector `Lambda`. The real and imaginary parts of the i^{th} eigenvalue are stored in `Lambda(i).X` and `Lambda(i).Y`, respectively. The eigenvalues are unordered, except that complex conjugate pairs appear consecutively with the value having the positive imaginary part first.

Function `MathErr` returns the following error codes:

- 0 if no error
- (-i) if an error occurred during the determination of the i^{th} eigenvalue. The eigenvalues should be correct for the indices $> i$.

This procedure destroys the original matrix `A`.

- procedure `EigenVect(A, Lb, Ub, Lambda, V)` computes the eigenvalues and eigenvectors of the real square matrix `A[Lb..Ub, Lb..Ub]`.

Eigenvalues are stored in the *complex* vector `Lambda`, just like with `EigenVals`.

Eigenvectors are stored along the columns of the *real* matrix `V`.

If the i^{th} eigenvalue is real, the i^{th} column of \mathbf{V} contains its eigenvector. If the i^{th} eigenvalue is complex with positive imaginary part, the i^{th} and $(i+1)^{th}$ columns of \mathbf{V} contain the real and imaginary parts of its eigenvector. The eigenvectors are unnormalized.

Function **MathErr** returns the same error codes than **EigenVals**. If the error code is not null, none of the eigenvectors has been found.

This procedure destroys the original matrix \mathbf{A} .

6.11 Demo programs

These programs are located in the `demo\matrices` subdirectory.

6.11.1 Determinant and inverse of a square matrix

Program `detinv.pas` computes the determinant and inverse of a square matrix. The inverse matrix is re-inverted and the result (which should be equal to the original matrix) is printed. The determinant of the inverse matrix is also evaluated and the product of the two determinants (which should be -1) is displayed.

The example matrix is:

$$\mathbf{A} = \begin{bmatrix} 1 & 2 & 0 & -1 \\ -1 & 4 & 3 & -0.5 \\ 2 & 2 & 1 & -3 \\ 0 & 0 & 3 & -4 \end{bmatrix}$$

The inverse is:

$$\mathbf{A}^{-1} = \begin{bmatrix} -\frac{41}{21} & \frac{4}{21} & \frac{11}{7} & -\frac{5}{7} \\ \frac{16}{21} & \frac{1}{21} & -\frac{5}{14} & \frac{1}{14} \\ -\frac{40}{21} & \frac{8}{21} & \frac{8}{7} & -\frac{3}{7} \\ -\frac{10}{7} & \frac{2}{7} & \frac{6}{7} & -\frac{4}{7} \end{bmatrix}$$

or, in approximate form:

$$\mathbf{A}^{-1} \approx \begin{bmatrix} -1.9523 & 0.1905 & 1.5714 & -0.7143 \\ 0.7619 & 0.0476 & -0.3571 & 0.0714 \\ -1.9048 & 0.3810 & 1.1429 & -0.4286 \\ -1.4286 & 0.2857 & 0.8571 & -0.5714 \end{bmatrix}$$

The determinant is -21.

6.11.2 Hilbert matrices

Program `hilbert.pas` tests the Gauss-Jordan method by solving a series of Hilbert systems of increasing order. Such systems have matrices of the form:

$$\mathbf{A} = \begin{bmatrix} 1 & \frac{1}{2} & \frac{1}{3} & \frac{1}{4} & \cdots & \frac{1}{N} \\ \frac{1}{2} & \frac{1}{3} & \frac{1}{4} & \frac{1}{5} & \cdots & \frac{1}{N+1} \\ \frac{1}{3} & \frac{1}{4} & \frac{1}{5} & \frac{1}{6} & \cdots & \frac{1}{N+2} \\ \frac{1}{4} & \frac{1}{5} & \frac{1}{6} & \frac{1}{7} & \cdots & \frac{1}{N+3} \\ \vdots & & & & & \vdots \\ \frac{1}{N} & \frac{1}{N+1} & \frac{1}{N+2} & \frac{1}{N+3} & \cdots & \frac{1}{2N-1} \end{bmatrix}$$

Each element of the constant vector (stored in the $(N+1)^{th}$ column of matrix \mathbf{A}) is equal to the sum of the terms in the corresponding line of the matrix :

$$A_{i,N+1} = \sum_{j=1}^N A_{ij}$$

The solution of such a system is $[1, 1, 1, \dots, 1]$

The determinant of the Hilbert matrix tends towards zero when the order increases. The program stops when the determinant becomes too low with respect to the numerical precision of the floating point numbers. This occurs at order 13 in double precision.

6.11.3 Gauss-Jordan method: single constant vector

Program `lineq1.pas` solves the linear system $\mathbf{AX} = \mathbf{B}$. After a call to `LinEq`, \mathbf{A} contains the inverse matrix and \mathbf{B} contains the solution vector.

The example system matrix is:

$$\mathbf{A} = \begin{bmatrix} 2 & 1 & 5 & -8 \\ 7 & 6 & 2 & 2 \\ -1 & -3 & -10 & 4 \\ 2 & 2 & 2 & 1 \end{bmatrix}$$

The constant vector is:

$$\mathbf{B} = \begin{bmatrix} 0 \\ 17 \\ -10 \\ 7 \end{bmatrix}$$

The solution vector is:

$$\mathbf{X} = \begin{bmatrix} 1 \\ 1 \\ 1 \\ 1 \end{bmatrix}$$

The determinant is -135

6.11.4 Gauss-Jordan method: multiple constant vectors

Program `lineqm.pas` solves a series of linear systems with the same system matrix and several constant vectors. The system matrix is stored in the first n columns of matrix **A**; the constant vectors are stored in the following columns. After a call to `GaussJordan`, the first n columns of **A** contain the inverse matrix and the following columns contain the solution vectors.

The example system matrix from the previous program is used. The matrix of constant vectors is:

$$\begin{bmatrix} 0 & -15 & 14 & -13 & 5 \\ 17 & 50 & 1 & 84 & 30 \\ -10 & -5 & -12 & -51 & -15 \\ 7 & 17 & 1 & 37 & 10 \end{bmatrix}$$

The solution matrix is:

$$\begin{bmatrix} 1 & 2 & 1 & 4 & 0 \\ 1 & 5 & -1 & 5 & 5 \\ 1 & 0 & 1 & 6 & 0 \\ 1 & 3 & -1 & 7 & 0 \end{bmatrix}$$

6.11.5 LU, QR and SV decompositions

The demo programs `test_lu.pas`, `test_qr.pas` and `test_svd.pas` solve the linear system used by `lineq1.pas` (paragraph 6.11.3) with the LU, QR, and singular value decompositions, respectively.

6.11.6 Cholesky decomposition

Program `cholesk.pas` performs the Cholesky decomposition of a positive definite symmetric matrix. The matrix is decomposed then the program computes the product \mathbf{LL}^\top which must give the original matrix.

The example matrix is:

$$\mathbf{A} = \begin{bmatrix} 60 & 30 & 20 \\ 30 & 20 & 15 \\ 20 & 15 & 12 \end{bmatrix}$$

Its Cholesky factor is:

$$\mathbf{L} = \begin{bmatrix} 2\sqrt{15} & 0 & 0 \\ \sqrt{15} & \sqrt{5} & 0 \\ \frac{2}{3}\sqrt{15} & \sqrt{5} & \frac{1}{3}\sqrt{3} \end{bmatrix}$$

or, in approximate form:

$$\mathbf{L} \approx \begin{bmatrix} 7.745967 & 0 & 0 \\ 3.872983 & 2.236068 & 0 \\ 2.581989 & 2.236068 & 0.577350 \end{bmatrix}$$

6.11.7 Eigenvalues of a symmetric matrix

Program `eigensym.pas` computes the eigenvalues and eigenvectors of Hilbert matrices (see program `hilbert.pas`) by the SVD or Jacobi methods. Such matrices are very ill-conditioned, which can be seen from the high ratio between the highest and lowest eigenvalues (the *condition number*).

6.11.8 Eigenvalues of a general square matrix

Program `eigenval.pas` computes the eigenvalues of a general square matrix.

The example matrix from the `detinv.pas` program is used. It has two real and two complex (conjugate) eigenvalues:

```
-1.075319 +      1.709050 * i
-1.075319 -      1.709050 * i
-1.000000
 5.150639
```

6.11.9 Eigenvalues and eigenvectors of a general square matrix

Program `eigenvec.pas` computes both the eigenvalues and eigenvectors of a general square matrix. The same example matrix is used.

The eigenvectors are stored columnwise in a matrix \mathbf{V} . In order to retrieve the eigenvectors associated with complex eigenvalues, the program takes into account the following properties:

- Complex conjugate pairs of eigenvalues are stored consecutively in vector **Lambda**, with the value having the positive imaginary part first.
- If the i^{th} eigenvalue is complex with positive imaginary part, the i^{th} and $(i+1)^{th}$ columns of matrix **V** contain the real and imaginary parts of its eigenvector.
- Eigenvectors associated with complex conjugate eigenvalues are themselves complex conjugate.

Hence the algorithm:

```

if Lambda^[I].Y = 0.0 then
  { Eigenvector is in column I of V }
else if Lambda^[I].Y > 0.0 then
  { Real and imag. parts of eigenvector are in columns I and (I+1)
    For component K: real part = V^K^[I],
                      imag. part = V^K^[I+1] }
else
  { Real and imag. parts of eigenvector are in columns (I-1) and I
    For component K: real part = V^K^[I-1],
                      imag. part = - V^K^[I] }

```

The results obtained with the example matrix are the following:

Eigenvalue:

-1.075319 + 1.709050 * i

Eigenvector:

-0.220224 + 0.394848 * i
 0.078289 - 0.303345 * i
 0.029348 + 0.787594 * i
 0.374358 + 0.589119 * i

Eigenvalue:

-1.075319 - 1.709050 * i

Eigenvector:

-0.220224 -	0.394848 * i
0.078289 +	0.303345 * i
0.029348 -	0.787594 * i
0.374358 -	0.589119 * i

Eigenvalue:

-1.000000

Eigenvector:

2.605054
-1.042021
3.126065
3.126065

Eigenvalue:

5.150638

Eigenvector:

0.345194
0.788801
0.441744
0.144823

Chapter 7

Function minimization

This chapter describes the procedures and functions available in TPMath to minimize functions of one or several variables. Only deterministic optimizers are considered here. Stochastic optimization will be studied in another chapter.

7.1 Functions of one variable

Let `Func` be a function of a real variable `X`. In TPMath such a function is declared as:

```
function Func(X : Float) : Float;
```

There is a special type `TFunc` for this kind of functions.

The problem is to find the real `Xmin` for which `Func(X)` is minimal.

Procedure `GoldSearch(Func, A, B, MaxIter, Tol, Xmin, Ymin)` performs the minimization by the ‘golden search’ method. This means that, at each iteration, the number `Xmin` is ‘bracketed’ by a triplet (`A`, `B`, `C`) such that:

- $A < B < C$
- A, B, C are within the golden mean ϕ , i.e.

$$\frac{B - A}{C - B} = \frac{C - A}{B - A} = \phi = \frac{1 + \sqrt{5}}{2} \approx 1.618$$

- `Func(B) < Func(A)` and `Func(B) < Func(C)`.

The user must provide two numbers **A** and **B** which define the ‘unit vector’ on the **X** axis. The number **C** is found by the program itself. It is not necessary that the interval **[A, B]** contains the minimum.

The user must also provide:

- the maximum number of iterations **MaxIter**
- the tolerance **Tol** with which the minimum must be located. This value should not be higher than the square root of the machine precision ($\text{MachEp}^{1/2} \approx 1.5 \times 10^{-8}$ in double precision)

The procedure returns the coordinates (**Xmin**, **Ymin**) of the minimum.

After a call to **GoldSearch**, function **MathErr()** will return one of two error codes:

- **OptOk** if no error occurred
- **OptNonConv** (non-convergence) if the number of iterations exceeds the maximum value **MaxIter**

The determination of the bracketing triplet **A**, **B**, **C** is performed within **GoldSearch** by a call to a procedure **MinBrack**. This procedure may be called independently. Its syntax is:

```
MinBrack(Func, A, B, C, Fa, Fb, Fc)
```

The user must provide the first two numbers **A** and **B**. The number **C** is found by the procedure. The corresponding values of the function are returned in **Fa**, **Fb**, **Fc**.

7.2 Functions of several variables

Let **Func** be a function of a real vector **x** such that $\mathbf{x} = [x_1, x_2, \dots]$. In **TPMath** such a function is declared as:

```
function Func(X : PVector) : Float;
```

There is a special type **TFuncNVar** for this kind of functions.

The problem is to find the vector **X** for which **Func(X)** is minimal.

7.2.1 Minimization along a line

If \mathbf{x}^0 is a starting point and $\delta\mathbf{x}$ is a constant vector, minimizing f from \mathbf{x}^0 along the direction specified by $\delta\mathbf{x}$ is equivalent to finding the number r such that $g(r) = f(\mathbf{x}^0 + r \cdot \delta\mathbf{x})$ is minimal.

The following procedure:

```
LinMin(Func, X, DeltaX, Lb, Ub, R, MaxIter, Tol, F_min)
```

will minimize function `Func` from point `X[Lb..Ub]` in the direction specified by vector `DeltaX[Lb..Ub]`. `R` is the initial step in that direction, expressed as a fraction of the norm of `DeltaX`. If `R` is set to 0 or a negative value, the procedure will use the default value `R = 1`. The user must also provide the maximum number of iterations `MaxIter` and the tolerance `Tol`, as for procedure `GoldSearch`.

On output, `LinMin` returns:

- the coordinates of the minimum in `X()`
- the step corresponding to the minimum in `R`
- the function value at the minimum in `F_min`

After a call to `LinMin`, function `MathErr()` will return one of the error codes `OptOk` or `OptNonConv`, as with `GoldSearch`.

7.2.2 Newton-Raphson method

The Newton-Raphson method starts with an approximation \mathbf{x}^0 for the coordinates of the minimum and generates a new approximation \mathbf{x} by using the second-order Taylor series expansion of function f around \mathbf{x}^0 :

$$f(\mathbf{x}) = f(\mathbf{x}^0) + (\mathbf{x} - \mathbf{x}^0)^\top \cdot \mathbf{g}(\mathbf{x}^0) + \frac{1}{2}(\mathbf{x} - \mathbf{x}^0)^\top \cdot \mathbf{H}(\mathbf{x}^0) \cdot (\mathbf{x} - \mathbf{x}^0) \quad (7.1)$$

\mathbf{g} denotes the gradient vector (vector of first partial derivatives) and \mathbf{H} denotes the hessian matrix (matrix of second partial derivatives). For instance, for a function of two variables $f(x_1, x_2)$:

$$\mathbf{g}(\mathbf{x}^0) = \begin{bmatrix} \frac{\partial f}{\partial x_1}(x_1^0, x_2^0) \\ \frac{\partial f}{\partial x_2}(x_1^0, x_2^0) \end{bmatrix}$$

$$\mathbf{H}(\mathbf{x}^0) = \begin{bmatrix} \frac{\partial^2 f}{\partial x_1^2}(x_1^0, x_2^0) & \frac{\partial^2 f}{\partial x_1 \partial x_2}(x_1^0, x_2^0) \\ \frac{\partial^2 f}{\partial x_2 \partial x_1}(x_1^0, x_2^0) & \frac{\partial^2 f}{\partial x_2^2}(x_1^0, x_2^0) \end{bmatrix}$$

By differentiating eq. (1) we obtain the gradient of f at point \mathbf{x} :

$$\mathbf{g}(\mathbf{x}) = \mathbf{g}(\mathbf{x}^0) + \mathbf{H}(\mathbf{x}^0) \cdot (\mathbf{x} - \mathbf{x}^0) \quad (7.2)$$

If \mathbf{x} is sufficiently close to the minimum, $\mathbf{g}(\mathbf{x}) \approx 0$ so:

$$\mathbf{x} = \mathbf{x}^0 - \mathbf{H}^{-1}(\mathbf{x}^0) \cdot \mathbf{g}(\mathbf{x}^0)$$

In practice, it is better to determine the step k which minimizes the function in the direction specified by $-\mathbf{H}^{-1}(\mathbf{x}^0) \cdot \mathbf{g}(\mathbf{x}^0)$:

$$\mathbf{x} = \mathbf{x}^0 - k \cdot \mathbf{H}^{-1}(\mathbf{x}^0) \cdot \mathbf{g}(\mathbf{x}^0)$$

The determination of k is performed by line minimization.

The following procedure:

`Newton(Func, HessGrad, X, Lb, Ub, MaxIter, Tol, F_min, G, H_inv, Det)`

minimizes function `Func` by the Newton-Raphson method.

The user must provide a procedure `HessGrad` to compute the gradient `G` and the hessian `H` of the function at point `X`. This procedure is declared as:

```
procedure HessGrad(X, G : PVector; H : PMatrix);
```

which corresponds to type `THessGrad`.

`MaxIter` and `Tol` have their usual meaning.

On output, `Newton` returns:

- the coordinates of the minimum in `X`
- the function value at the minimum in `F_min`
- the gradient at the minimum in `G` (should be near 0)
- the inverse hessian matrix at the minimum in `H_inv`
- the determinant of the hessian matrix at the minimum in `Det`

After a call to `Newton`, function `MathErr()` will return one of three error codes:

- `OptOk` if no error occurred
- `OptNonConv` (non-convergence) if the number of iterations exceeds the maximum value `MaxIter`
- `OptSing` if the hessian matrix is quasi-singular

Approximate gradient and hessian

Although it is recommended to compute the gradient and hessian from analytical derivatives, approximate values may be found using finite difference approximations:

$$\frac{\partial f}{\partial x_i}(\mathbf{x}) \approx \frac{f(x_i + h_i) - f(x_i - h_i)}{2h_i}$$

$$\frac{\partial^2 f}{\partial x_i^2}(\mathbf{x}) \approx \frac{f(x_i + h_i) + f(x_i - h_i) - 2f(x_i)}{h_i^2}$$

$$\frac{\partial^2 f}{\partial x_i \partial x_j}(\mathbf{x}) \approx \frac{f(x_i + h_i, x_j + h_j) - f(x_i + h_i, x_j) - f(x_i, x_j + h_j) + f(x_i, x_j)}{h_i h_j}$$

The increment h_i is such that $h_i = \eta |x_i|$ where η is a constant which should not be less than the cube root of the machine epsilon ($\text{MachEp}^{1/3} \approx 6.06 \times 10^{-6}$ in double precision).

This method is illustrated in the demo programs `testnewt.pas` and `testmarq.pas` (see paragraph 7.3).

7.2.3 Marquardt method

This method is a variant of the Newton-Raphson method, in which each diagonal term of the hessian matrix is multiplied by a scalar equal to $(1 + \lambda)$, where λ is the Marquardt parameter. This parameter is initialized at some small value (e.g. 10^{-2}) at the beginning of the iterations, then it is decreased by a factor 10 if the iteration leads to a decrease of the function, otherwise it is increased by a factor 10. If the method converges, λ is set to zero and an additional iteration (equivalent to a Newton-Raphson step) is performed.

This procedure is implemented as:

`Marquardt(Func, HessGrad, X, Lb, Ub, MaxIter, Tol, F_min, G, H_inv, Det)`

It is used like `Newton`, except that an additional error code, `OptBigLambda`, may be returned by `MathErr` if the Marquard parameter increases beyond a predefined value (10^3 in this implementation).

7.2.4 BFGS method

The BFGS (Broyden-Fletcher-Goldfarb-Shanno) method is another variant of the Newton method in which the hessian matrix does not need to be computed explicitly. It is said a *quasi-Newton* method.

The BFGS algorithm uses the following formula to construct the inverse hessian matrix iteratively:

$$\mathbf{H}_{i+1}^{-1} = \mathbf{H}_i^{-1} + \frac{\delta \mathbf{x} \cdot \delta \mathbf{x}^\top}{\delta \mathbf{x}^\top \cdot \delta \mathbf{g}} - \frac{(\mathbf{H}_i^{-1} \cdot \delta \mathbf{g}) \cdot (\mathbf{H}_i^{-1} \cdot \delta \mathbf{g})^\top}{\delta \mathbf{g}^\top \cdot \mathbf{H}_i^{-1} \cdot \delta \mathbf{g}} + (\delta \mathbf{g}^\top \cdot \mathbf{H}_i^{-1} \cdot \delta \mathbf{g}) \cdot \mathbf{u} \cdot \mathbf{u}^\top$$

with:

$$\delta \mathbf{x} = \mathbf{x}_{i+1} - \mathbf{x}_i \quad \delta \mathbf{g} = \mathbf{g}(\mathbf{x}_{i+1}) - \mathbf{g}(\mathbf{x}_i) \quad \mathbf{u} = \frac{\delta \mathbf{x}}{\delta \mathbf{x}^\top \cdot \delta \mathbf{g}} - \frac{\mathbf{H}_i^{-1} \cdot \delta \mathbf{g}}{\delta \mathbf{g}^\top \cdot \mathbf{H}_i^{-1} \cdot \delta \mathbf{g}}$$

The algorithm is usually started with the identity matrix ($\mathbf{H}_0^{-1} = \mathbf{I}$).

This procedure is implemented as:

`BFGS(Func, Gradient, X, Lb, Ub, MaxIter, Tol, F_min, G, H_inv)`

The user must provide a procedure `Gradient` to compute the gradient `G` of the function at point `X`. This procedure is declared as:

```
procedure Gradient(X, G : PVector);
```

which corresponds to type `TGradient`.

The other parameters have the same meaning than in `Newton`.

Approximate gradient

It is possible to estimate the gradient of function `Func` by finite difference approximations, as described for the Newton method. Here the relative increment η should not be less than the square root of the machine epsilon (about 1.5×10^{-8} in double precision).

See demo program `testbfgs.pas` for an example.

As usual, it is recommended to use analytical derivatives whenever possible.

7.2.5 Simplex method

Unlike previous methods, the simplex method of Nelder and Mead does not use derivatives to locate the minimum. Instead it constructs a geometrical figure (the ‘simplex’) having $(n + 1)$ vertices, if n is the number of variables. For instance, in the two-dimensional space ($n = 2$), the simplex would be a triangle. Depending on the function values at the vertices, the simplex is reduced or expanded until it comes close to the minimum.

This method is implemented as:

```
Simplex(Func, X, Lb, Ub, MaxIter, Tol, F_min)
```

where the parameters have their usual meaning.

7.2.6 Log files

It is possible to create ‘log files’ which save the progress of the iterations. If the algorithm terminates abnormally, checking these files may help finding the error. For each method (Newton, Marquard, BFGS, Simplex) there is a **Save...** procedure which creates the log file. Each procedure accepts the name of the file as its parameter (e.g. **SaveBFGS('bfgs.txt')**). The file is automatically closed when the optimization procedure ends.

See the demo programs for examples using such files.

7.3 Demo programs

These programs are located in the `demo\optim` subdirectory.

7.3.1 Function of one variable

Program `minfunc.pas` performs the golden search minimization on the function:

$$f(x) = e^{-2x} - e^{-x}$$

The minimum is at $(\ln 2, -1/4)$.

The minimum found by `GoldSearch` is compared with the true minimum.

7.3.2 Minimization along a line

Program `minline.pas` applies line minimization to the function of 3 variables (taken from the *Numerical Recipes* example book) :

$$f(x_1, x_2, x_3) = (x_1 - 1)^2 + (x_2 - 1)^2 + (x_3 - 1)^2$$

The minimum is $f(1, 1, 1) = 0$, i. e. for a step $r = 1$ from $\mathbf{x} = [0, 0, 0]$ in the direction $\delta\mathbf{x} = [1, 1, 1]$.

The program tries a series of directions:

$$\delta\mathbf{x} = \left[\sqrt{2} \cos\left(i \frac{\pi}{20}\right), \sqrt{2} \sin\left(i \frac{\pi}{20}\right), 1 \right] \quad i = 1..10$$

For each pass, the location of the minimum, and the value of the function at the minimum, are printed. The true minimum is found at $i = 5$.

7.3.3 Newton-Raphson method

Program `testnewt.pas` uses the Newton-Raphson method to minimize Rosenbrock's function (H. Rosenbrock, *Comput. J.*, 1960, **3**, 175):

$$f(x, y) = 100(y - x^2)^2 + (1 - x)^2$$

for which the gradient and hessian are:

$$\mathbf{g}(x, y) = \begin{bmatrix} -400(y - x^2)x - 2 + 2x \\ 200y - 200x^2 \end{bmatrix}$$

$$\mathbf{H}(x, y) = \begin{bmatrix} 1200x^2 - 400y + 2 & -400x \\ -400x & 200 \end{bmatrix}$$

and the determinant of the hessian is:

$$\det \mathbf{H}(x, y) = 80000(x^2 - y) + 400$$

The minimum is $f(1, 1) = 0$, where:

$$\mathbf{g}(1, 1) = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

$$\mathbf{H}^{-1}(1, 1) = \begin{bmatrix} \frac{1}{2} & 1 \\ 1 & \frac{401}{200} \end{bmatrix}$$

$$\det \mathbf{H}(1, 1) = 400$$

In the demo program, the gradient and hessian are computed analytically. You can compare with the numerical computations by including file `numhess.inc` in the program.

7.3.4 Other programs

Programs `testmarq.pas`, `testbfgs.pas` and `testsimp.pas` minimize Rosenbrock's function with the Marquardt, BFGS and Simplex methods, respectively.

Chapter 8

Nonlinear equations

This chapter describes the procedures available in TPMath to solve nonlinear equations in one or several variables. Only general methods are considered here. Polynomial equations will be studied in the next chapter.

8.1 Equations in one variable

The goal is to solve the nonlinear equation $f(x) = 0$, or, in other terms, find a root of function f .

8.1.1 Bisection method

Procedure `Bisect(Func, X, Y, MaxIter, Tol, F)` finds a root of function `Func` by the bisection method. At each iteration, the root is bounded by two numbers `(X, Y)` such that the function has opposite signs. Then, a new approximation to the root is generated by taking the mean of these numbers.

The function `Func` must be declared as:

```
function Func(X : Float) : Float;
```

The user must provide initial values for `X` and `Y`. It is not necessary that the interval `[X, Y]` contains the root.

The user must also provide:

- the maximum number of iterations `MaxIter`
- the tolerance `Tol` with which the root must be located.

The procedure returns the refined values of **X** and **Y** and the function value **Func(X)** in **F**.

After a call to **Bisect**, function **MathErr()** will return one of two error codes:

- **OptOk** if no error occurred
- **OptNonConv** (non-convergence) if the number of iterations exceeds the maximum value **MaxIter**

If the starting interval **[X, Y]** does not contain the root, **Bisect** will expand it by calling a procedure **RootBrack**. This procedure may be called independently. Its syntax is:

RootBrack(Func, X, Y, FX, FY)

The user must provide initial values for the two numbers **X** and **Y**, which will be refined by the procedure. The corresponding function values are returned in **FX** and **FY**.

8.1.2 Secant method

The secant method also starts with two approximations x and y and generates a new approximation z from the formula:

$$z = \frac{xf(y) - yf(x)}{f(y) - f(x)}$$

z is the intersection of the Ox axis with the line connecting the points $(x, f(x))$ and $(y, f(y))$, i. e. the secant.

This method is implemented as:

Secant(Func, X, Y, MaxIter, Tol, F)

The parameters and error codes are the same than in **Bisect**. Here too, it is not necessary that the interval **[X, Y]** contains the root.

8.1.3 Newton-Raphson method

The Newton-Raphson method starts with an approximate root x^0 and generates a new approximation x by using the first-order Taylor series expansion of function f around x^0 :

$$f(x) \approx f(x^0) + f'(x^0) \cdot (x - x^0)$$

If x is sufficiently close to the root, $f(x) \approx 0$ so:

$$x = x^0 - \frac{f(x^0)}{f'(x^0)}$$

This method is implemented as:

`NewtEq(Func, Deriv, X, MaxIter, Tol, F)`

where `Func` and `Deriv` are the procedures which compute the function and its derivative, respectively (they have the same syntax). The user must provide the initial approximation `X`.

After a call to `NewtEq`, function `MathErr()` will return one of three error codes:

- `OptOk` if no error occurred
- `OptNonConv` (non-convergence) if the number of iterations exceeds the maximum value `MaxIter`
- `OptSing` if the derivative becomes zero

8.2 Equations in several variables

The goal is to solve a system of n nonlinear equations in n unknowns x_1, x_2, \dots, x_n :

$$\begin{aligned} f_1(x_1, x_2, \dots, x_n) &= 0 \\ f_2(x_1, x_2, \dots, x_n) &= 0 \\ &\dots\dots\dots \\ f_n(x_1, x_2, \dots, x_n) &= 0 \end{aligned}$$

or, in matrix notation:

$$\mathbf{f}(\mathbf{x}) = \mathbf{0}$$

where \mathbf{f} is a function vector.

8.2.1 Newton-Raphson method

The Newton-Raphson method starts with an approximate root \mathbf{x}^0 and generates a new approximation \mathbf{x} by using the first-order Taylor series expansion of function \mathbf{f} around \mathbf{x}^0 :

$$\mathbf{f}(\mathbf{x}) \approx \mathbf{f}(\mathbf{x}^0) + \mathbf{D}(\mathbf{x}^0) \cdot (\mathbf{x} - \mathbf{x}^0)$$

\mathbf{D} denotes the jacobian matrix (matrix of first partial derivatives). For instance, for a system of 2 equations in two variables:

$$f_1(x_1, x_2) = 0$$

$$f_2(x_1, x_2) = 0$$

the jacobian matrix is:

$$\mathbf{D}(\mathbf{x}^0) = \begin{bmatrix} \frac{\partial f_1}{\partial x_1}(x_1^0, x_2^0) & \frac{\partial f_1}{\partial x_2}(x_1^0, x_2^0) \\ \frac{\partial f_2}{\partial x_1}(x_1^0, x_2^0) & \frac{\partial f_2}{\partial x_2}(x_1^0, x_2^0) \end{bmatrix}$$

If \mathbf{x} is sufficiently close to the root, $\mathbf{f}(\mathbf{x}) \approx 0$ so:

$$\mathbf{x} = \mathbf{x}^0 - \mathbf{D}^{-1}(\mathbf{x}^0) \cdot \mathbf{f}(\mathbf{x}^0)$$

In practice, it is better to determine a step k in the direction specified by $\mathbf{D}^{-1}(\mathbf{x}^0) \cdot \mathbf{f}(\mathbf{x}^0)$:

$$\mathbf{x} = \mathbf{x}^0 - k \cdot \mathbf{D}^{-1}(\mathbf{x}^0) \cdot \mathbf{f}(\mathbf{x}^0)$$

The determination of k is performed by line minimization applied to the sum of squared functions:

$$S(\mathbf{x}) = \sum_{i=1}^n f_i(\mathbf{x})^2$$

This method is implemented as:

```
NewtEqs(Equations, Jacobian, X, F, Lb, Ub, MaxIter, Tol)
```

where `Equations` and `Jacobian` are the procedures which compute the function vector and the jacobian matrix, respectively. Their syntaxes are:

```
procedure Equations(X, F : PVector);
procedure Jacobian(X : PVector; D : PMatrix);
```

They correspond to types `TEquations` and `TJacobian`, respectively.

The user must provide the initial approximations to the roots in vector `X[Lb..Ub]`. After refinement by the procedure, the corresponding function values are returned in vector `F`.

The possible error codes returned by `MathErr` are:

- `OptOk` if no error occurred
- `OptNonConv` (non-convergence) if the number of iterations exceeds the maximum value `MaxIter`
- `OptSing` if the jacobian matrix is quasi-singular

Approximate jacobian

Approximate values of the jacobian matrix may be computed using finite difference approximations:

$$\frac{\partial f_i}{\partial x_j}(\mathbf{x}) \approx \frac{f_i(x_j + h_j) - f_i(x_j - h_j)}{2h_j}$$

The increment h_j is such that $h_j = \eta |x_j|$ where η is a constant which should not be less than the square root of the machine epsilon ($\text{MachEp}^{1/2}$).

The demo program `testnr.pas` gives an example of using such a procedure.

As usual, it is recommended to use analytical expressions for the derivatives whenever possible.

8.2.2 Broyden's method

This method is similar to the BFGS method of function minimization. It can also be viewed as a multidimensional version of the secant method.

Broyden's algorithm uses the following formula to construct the inverse jacobian matrix iteratively:

$$\mathbf{D}_{i+1}^{-1} = \mathbf{D}_i^{-1} + \frac{[(\delta\mathbf{x} - \mathbf{D}_i^{-1} \cdot \delta\mathbf{f}) \cdot \delta\mathbf{x}^\top] \cdot \mathbf{D}_i^{-1}}{\delta\mathbf{x}^\top \cdot \mathbf{D}_i^{-1} \cdot \delta\mathbf{f}}$$

with:

$$\delta\mathbf{x} = \mathbf{x}_{i+1} - \mathbf{x}_i \quad \delta\mathbf{f} = \mathbf{f}(\mathbf{x}_{i+1}) - \mathbf{f}(\mathbf{x}_i)$$

The algorithm is usually started with the identity matrix ($\mathbf{D}_0^{-1} = \mathbf{I}$).

This method is implemented as: `Broyden(Equations, X, F, Lb, Ub, MaxIter, Tol)`, where the parameters have the same significance than in `NewtEqs`.

The possible error codes returned by `MathErr` are `OptOk` and `OptNonConv`.

8.3 Demo programs

8.3.1 Equations in one variable

The demo programs `testbis.pas`, `testsec.pas` and `testnr1.pas` demonstrate the bisection, secant and Newton-Raphson methods, respectively, on the equation:

$$f(x) = x \ln x - 1 = 0$$

for which the derivative is:

$$f'(x) = \ln x + 1$$

The true solution is $x = 1.763222834\dots$

8.3.2 Equations in several variables

The demo programs `testnr.pas` and `testbrdn.pas` demonstrate the Newton-Raphson and Broyden methods, respectively, on the following system (taken from the *Numerical Recipes* example book) :

$$f(x, y) = x^2 + y^2 - 2 = 0$$

$$g(x, y) = \exp(x - 1) + y^3 - 2 = 0$$

for which the jacobian is:

$$\mathbf{D}(x, y) = \begin{bmatrix} 2x & 2y \\ \exp(x - 1) & 3y^2 \end{bmatrix}$$

The true solution is $(x, y) = (1, 1)$.

Chapter 9

Polynomials

This chapter describes the procedures and functions related to polynomials and rational fractions.

9.1 Polynomials

Function `Poly(X, Coef, Deg)` evaluates the polynomial:

$$P(X) = \text{Coef}[0] + \text{Coef}[1] \cdot X + \text{Coef}[2] \cdot X^2 + \cdots + \text{Coef}[\text{Deg}] \cdot X^{\text{Deg}}$$

9.2 Rational fractions

Function `RFrac(X, Coef, Deg1, Deg2)` evaluates the rational fraction:

$$F(X) = \frac{\text{Coef}[0] + \text{Coef}[1] \cdot X + \cdots + \text{Coef}[\text{Deg1}] \cdot X^{\text{Deg1}}}{1 + \text{Coef}[\text{Deg1} + 1] + \cdots + \text{Coef}[\text{Deg1} + \text{Deg2}] \cdot X^{\text{Deg2}}}$$

9.3 Roots of polynomials

Analytical methods can be used to compute the roots of polynomials up to degree 4. For higher degrees, iterative methods must be used.

9.3.1 Analytical methods

- Function `RootPol1(A, B, X)` solves the linear equation $A + BX = 0$. The function returns 1 if no error occurs ($B \neq 0$), -1 if X is undetermined ($A = B = 0$), -2 if there is no solution ($A \neq 0, B = 0$).

- Functions `RootPoln(Coef, Z)`, with $n = 2, 3, 4$, solve the equation:

$$\text{Coef}[0] + \text{Coef}[1] \cdot X + \text{Coef}[2] \cdot X^2 + \cdots + \text{Coef}[N] \cdot X^N = 0$$

The roots are stored in the complex vector `Z`. The real part of the i^{th} root is in `Z[i].X`, the imaginary part in `Z[i].Y`.

If no error occurs, the function returns the number of real roots, otherwise it returns (-1) or (-2) just like `RootPol1`.

9.3.2 Iterative method

Function `RootPol(Coef, Deg, Z)` solves the polynomial equation:

$$a_0 + a_1x + a_2x^2 + \cdots + a_nx^n = 0$$

by the method of the *companion matrix*.

The companion matrix **A** is defined by:

$$\mathbf{A} = \begin{bmatrix} -\frac{a_{n-1}}{a_n} & -\frac{a_{n-2}}{a_n} & \cdots & -\frac{a_1}{a_n} & -\frac{a_0}{a_n} \\ 1 & 0 & \cdots & 0 & 0 \\ 0 & 1 & \cdots & 0 & 0 \\ \vdots & & & & \vdots \\ 0 & 0 & \cdots & 1 & 0 \end{bmatrix}$$

It may be shown that the eigenvalues of this matrix are equal to the roots of the polynomial (Eigenvalues are treated in § 6.10).

The coefficients of the polynomial are passed in vector `Coef`, such that `Coef[0] = a0`, `Coef[2] = a1` etc. The degree of the polynomial is passed in `Deg`. The roots are returned in the complex vector `Z` as described before.

If no error occurred, the function returns the number of real roots.

If an error occurred during the search for the i^{th} root, the function returns (-i). The roots should be correct for indices `(i+1)..Deg`. The roots are unordered.

9.4 Ancillary functions

Two procedures have been added to facilitate the handling of polynomials roots:

- Function `SetRealRoots(Deg, Z, Tol)` allows to set the imaginary part of a root to zero if it is less than a fraction `Tol` of the real part. The function returns the total number of real roots.

Due to roundoff errors, some real roots may be computed with a very small imaginary part, e.g. $1 + 10^{-8}i$. The function `SetRealRoots` tries to correct this problem.

- Procedure `SortRoots(Deg, Z)` sort the roots such that:
 1. The N real roots are stored in elements $1..N$ of vector Z , in increasing order.
 2. The complex roots are stored in elements $(N + 1)..Deg$ of vector Z and are unordered.

9.5 Demo programs

These programs are located in the `demo\polynom` subdirectory.

9.5.1 Evaluation of a polynomial

Program `evalpoly.pas` evaluates a polynomial for a series of user-specified values. Entering 0 stops the program.

9.5.2 Evaluation of a rational fraction

Program `evalfrac.pas` performs the same task as the previous program, but with a rational fraction.

9.5.3 Roots of a polynomial

Program `polyroot.pas` computes the roots of a polynomial with real coefficients. Analytical methods are used up to degree 4, otherwise the method of the companion matrix is used.

The example polynomial is:

$$x^6 - 21x^5 + 175x^4 - 735x^3 + 1624x^2 - 1764x + 720$$

for which the roots are 1, 2 ... 6

Chapter 10

Numerical integration and differential equations

This chapter describes the procedures available in TPMath to integrate a function of one variable, and to solve systems of differential equations.

10.1 Integration

10.1.1 Trapezoidal rule

The trapezoidal rule approximates the integral I of a tabulated function by the formula:

$$I \approx \frac{1}{2} \sum_{i=0}^{N-1} (x_{i+1} - x_i)(y_{i+1} + y_i)$$

where (x_i, y_i) are the coordinates of the i^{th} point.

This procedure is implemented as function `TrapInt(X, Y, N)`. Note that the lower bound of the arrays must be 0.

10.1.2 Gauss-Legendre integration

This method approximates the integral of a function f in an interval $[a, b]$ by:

$$\int_a^b f(x)dx \approx \frac{b-a}{2} \sum_{i=1}^N w_i f(y_i)$$
$$y_i = \frac{b-a}{2}x_i + \frac{b+a}{2}$$

The abscissae x_i and weights w_i are predefined values for a given number of points N .

This method is implemented as function `GausLeg(Func, A, B)` for $N = 16$. Function `Func` must be declared as:

```
function Func(X : Float) : Float;
```

For the special case $A = 0$ there is a variant `GausLeg0(Func, B)`.

10.2 Convolution

The convolution product of two functions f and g is defined by:

$$(f * g)(t) = \int_0^t f(u)g(t-u)du$$

This product is often used to describe the output of a linear system when $f(t)$ is the input signal (function of time) and $g(t)$ is the impulse response of the system.

Function `Convol(Func1, Func2, T)` approximates the convolution product of the two functions `Func1` and `Func2` at time `T` by the Gauss-Legendre method. The functions must be declared as above.

10.3 Differential equations

The Runge-Kutta-Fehlberg (RKF) method allows to compute numerical solutions to systems of first-order differential equations of the form:

$$\begin{aligned} y_1'(t) &= f_1[t, y_1(t), y_2(t), \dots] \\ y_2'(t) &= f_2[t, y_1(t), y_2(t), \dots] \\ &\dots\dots\dots \end{aligned}$$

where the f_i are known functions and the y_i are to be determined.

The RKF procedure is an extension of the classical Runge-Kutta method. For instance, in the case of a single differential equation

$$y'(t) = f[t, y(t)]$$

this method generates a sequence $\{t_n, y_n\}$ which approximates the function $y(t)$.

The order of the method corresponds to the number of points used in the interval $[t_n, t_{n+1}]$. For instance, the sequence generated by the 4-th order Runge-Kutta method is defined by:

$$y_{n+1} = y_n + \frac{k_1}{6} + \frac{k_2}{3} + \frac{k_3}{3} + \frac{k_4}{6}$$

with:

$$\begin{aligned} k_1 &= h \cdot f(t_n, y_n) \\ k_2 &= h \cdot f\left(t_n + \frac{h}{2}, y_n + \frac{k_1}{2}\right) \\ k_3 &= h \cdot f\left(t_n + \frac{h}{2}, y_n + \frac{k_2}{2}\right) \\ k_4 &= h \cdot f(t_n + h, y_n + k_3) \end{aligned}$$

with $h = t_{n+1} - t_n$

In the RKF method, the step size h is automatically varied so as to maintain a given level of precision on the estimated y values.

The implementation used in TPMath is a translation of a Fortran program by H. A. Watts and L. F. Shampine (http://www.csit.fsu.edu/~burkardt/f_src/rkf45/rkf45.f90). It is intermediate between the 4-th and 5-th order Runge-Kutta methods, hence the name RKF45.

In order to use RKF45 you must:

1. Define the following variables (the names are optional):

```
var
  Neqn          : Integer; { Number of equations }
  Y, Yp         : PVector; { Functions and derivatives }
  Tstart, Tstop  : Float;   { Integration interval }
  Nstep         : Integer;  { Number of steps }
  StepSize      : Float;    { Step size }
  AbsErr, RelErr : Float;    { Abs. and relative errors }
  Flag          : Integer;  { Error flag }
  T, Tout       : Float;    { Integration times }
  I             : Integer;  { Loop variable }
```

2. Define a procedure for computing the system of differential equations:

```

procedure DiffEq(T : Float; Y, Yp : PVector);
begin
  Yp^[1] := Y^[2];
  Yp^[2] := - Y^[1];
end;

```

(There is a special type TDiffEqs for such procedures)

3. Initialize variables, compute the step size and call RKF45 for each integration step (the initial values are given as examples, except for Flag which must be initialized to 1):

```

begin
  Neqn := 2;

  DimVector(Y, Neqn);
  DimVector(Yp, Neqn);

  Y^[1] := 1;  { Initial conditions }
  Y^[2] := 0;

  Tstart := 0;
  Tstop  := 2 * Pi;
  Nstep  := 12;

  StepSize := (Tstop - Tstart) / Nstep;

  AbsErr := 1.0E-6;
  RelErr := 1.0E-6;

  Flag := 1;

  T := Tstart;

  for I := 1 to Nstep do
    begin
      Tout := T + StepSize;
      RKF45(DiffEq, Neqn, Y, Yp, T, Tout, RelErr, AbsErr, Flag);
      T := Tout;
    end;
  end.

```

Upon return from RKF45:

- **Y**, **Yp** contain the values of the functions and their first derivatives at **Tout**
- **Flag** contains an error code:
 - * 2 : no error
 - * 3 : too small **RelErr** value
 - * 4 : too much function evaluations needed
 - * 5 : too small **AbsErr** value
 - * 6 : the requested accuracy could not be achieved
 - * 7 : the method was unable to solve the problem
 - * 8 : invalid input parameters

If an error occurs, it should be possible in most cases to restart the computation, using the values returned by the subroutine in **RelErr** and **AbsErr**.

Note : RKF45 may be used to compute a definite integral:

$$\int_a^b f(t)dt = F(b) - F(a)$$

since this is equivalent to integrate the differential equation:

$$F'(t) = f(t)$$

between a and b , with the initial condition specified by $f(a)$.

10.4 Demo programs

These programs are located in the `demo\integral` subdirectory.

- Program `trap.pas` applies the trapezoidal rule to a tabulated function.

The example function $f(x) = e^{-x}$ is tabulated for $x = 0$ to 1 by steps of 0.1. The integral is:

$$\int_0^1 e^{-x}dx = 1 - e^{-1} \approx 0.6321$$

- Program `gauss.pas` demonstrates the Gauss-Legendre integration method.

The example function is $f(x) = xe^{-x}$. The integral is:

$$\int_0^x f(t)dt = 1 - (x+1)e^{-x}$$

- Program `conv.pas` computes the convolution of two functions by the Gauss-Legendre method.

The example functions are $f(x) = xe^{-x}$ and $g(x) = e^{-2x}$. The convolution product is:

$$(f * g)(x) = \int_0^x f(u)g(x-u)du = e^{-2x} \int_0^x ue^u du = (x-1)e^{-x} - e^{-2x}$$

- Program `test_rkf.pas` solves 3 systems of differential equations by the RKF method:

1. A single nonlinear equation:

$$y'(t) = 0.25 \cdot y(t) \cdot [1 - 0.05 \cdot y(t)]$$

with the initial condition $y(0) = 1$.

The analytic solution is:

$$y(t) = \frac{20}{1 + 19 \exp(-0.25t)}$$

2. A system of two linear equations:

$$y_1'(t) = y_2(t)$$

$$y_2'(t) = -y_1(t)$$

with the initial conditions $y_1(0) = 1, y_2(0) = 0$.

The analytic solution is:

$$y_1(t) = \cos t \quad y_2(t) = -\sin t$$

3. A system of 5 equations with one nonlinear:

$$y_1'(t) = y_2(t)$$

$$y_2'(t) = y_3(t)$$

$$y_3'(t) = y_4(t)$$

$$y_4'(t) = y_5(t)$$

$$y_5'(t) = 45 \cdot y_3(t) \cdot y_4(t) \cdot y_5(t) - \frac{40[y_4(t)]^3}{9[y_3(t)]^2}$$

with initial conditions $y_i(0) = 1 \quad \forall i$

The program prints the numeric solution, and, if possible, the analytic one.

Chapter 11

Fast Fourier Transform

11.1 Introduction

Fourier transform is a mathematical method which allows to determine the frequency spectrum of a given signal (for instance a sound). The mathematical definition is the following :

$$y(f) = \int_{-\infty}^{\infty} x(t) \exp(2\pi i f t) dt = \int_{-\infty}^{\infty} x(t) (\cos 2\pi f t + i \sin 2\pi f t) \quad (11.1)$$

where $x(t)$ is the input signal (function of time), f the frequency, and i the complex number such that $i^2 = -1$. y is the Fourier transform of x .

The input signal may have real or complex values. However, the Fourier transform is always a complex number. For each frequency f , the modulus of $y(f)$ represents the energy associated with this frequency. A plot of this modulus as a function of f gives the frequency spectrum of the input signal.

If the input signal is sampled as a sequence of n values x_0, x_1, \dots, x_{n-1} , taken at constant time intervals, the Fourier transform is a sequence of complex number y_0, y_1, \dots, y_{n-1} , such that:

$$y_p = \sum_{k=0}^{n-1} x_k \left[\cos \left(2\pi \frac{kp}{n} \right) + i \sin \left(2\pi \frac{kp}{n} \right) \right] \quad (11.2)$$

This formula allows, in principle, to compute the transform y_p at any point. In practice, a faster algorithm called the Fast Fourier Transform (FFT) is used.

11.2 Programming

11.2.1 Array dimensioning

The FFT algorithm requires that the number of points n is a power of 2. Moreover, the arrays must be dimensioned from 0 to $(n - 1)$. For instance:

```
const
  NumSamples = 512;           { Buffer size must be power of 2 }
  MaxIndex   = NumSamples - 1; { Max. array index }

var
  InArray, OutArray : PCompVector;

begin
  DimCompVector(InArray, MaxIndex); { FFT input }
  DimCompVector(OutArray, MaxIndex); { FFT output }
  ...
```

The maximal value of n depends on the maximal array size `MAX_COMP` for an array of type `Complex` (see § 6.2). The maximal value of p such that $n = 2^p$ is given by the formula:

$$p := \text{Trunc}(\text{Ln}(\text{MAX_COMP}) / \text{Ln}(2))$$

For a 32-bit compiler in double precision, $p = 26$, thus allowing $2^{26} = 67108864$ (64 mega) points.

11.2.2 FFT procedures

- Procedure `FFT(NumSamples, InArray, OutArray)` calculates the Fast Fourier Transform of the array of complex numbers `InArray` to produce the output complex numbers in `OutArray`.
- Procedure `IFFT(NumSamples, InArray, OutArray)` calculates the Inverse Fast Fourier Transform of the array of complex numbers represented by `InArray` to produce the output complex numbers in `OutArray`.

In other words, this procedure reconstitutes the input signal from its FFT.

- Procedure `FFT_Integer(NumSamples, RealIn, ImagIn, OutArray)` computes the Fast Fourier Transform on integer data. Here the real and imaginary parts of the data are stored in two integer arrays `RealIn` and `ImagIn`, while the results are stored in the complex array `OutArray`.
- Procedure `FFT_Integer_Cleanup` clears the memory after a call to `FFT_Integer`.
- Procedure `CalcFrequency(NumSamples, FrequencyIndex, InArray, FT)` calculates the complex frequency sample at a given index directly, by means of eq. 11.2. The answer is returned in the complex variable `FT`. Use this instead of `FFT` when you only need one or two frequency samples, not the whole spectrum. It is also useful for calculating the Fourier Transform of a number of data which is not an integer power of 2. For example, you could calculate the transform of 100 points instead of rounding up to 128 and padding the extra 28 array slots with zeroes.

11.3 Demo program

Program `test_fft.pas`, located in the `demo\fourier` subdirectory, shows how the Fourier transform may be used to filter a signal. The program plots several graphics and writes its results to the output file `fftout.txt`

The example is a 200 Hz sine wave contaminated by a 2000 Hz parasitic signal. The sampling frequency `SamplingRate` is 22050 Hz, the number of points `NumSamples` is 512 ($= 2^9$). These two numbers determine the time and frequency units:

```
DT := 1 / SamplingRate;           { Time unit }
DF := SamplingRate / NumSamples;  { Frequency unit }
```

so that the entry `InArray^[I]` in the input array of procedure `FFT` corresponds to the signal value at time $I * DT$, and that the entry `OutArray^[I]` in the output array corresponds to the Fourier transform at frequency $I * DF$.

The highest frequency which may be detected is equal to `SamplingRate/2` and is called *Nyquist's frequency*. Hence, only the first half of array `OutArray` needs to be plotted (the second half contains symmetric values).

The program generates the input signal, plots it, then performs the FFT and plots the real and imaginary parts as a function of frequency. The plot

shows two peaks, corresponding to the 5-th and 46-th entries in `OutArray` (as seen from the file `fftout.txt`). The corresponding frequencies are:

$$5 \times \frac{22050}{512} \approx 215 \text{ Hz}$$

$$46 \times \frac{22050}{512} \approx 1981 \text{ Hz}$$

The high peak corresponds to the main signal and the small peak to the parasite. To filter the last one, the program sets to zero all the FFT values corresponding to the frequencies higher than 1000 Hz, according to the following code:

```

FreqIndex := Trunc(1000.0 / DF);
MidIndex := NumSamples div 2;
SymIndex := NumSamples - FreqIndex;

for I := FreqIndex to SymIndex do
begin
  OutArray^[I].X := 0.0;
  OutArray^[I].Y := 0.0;
end;
```

(note that the two halves of the output array, on either side of Nyquist's frequency, must be treated).

The program then calls procedure `IFFT` to compute the inverse Fourier transform of the modified data and plots the result, showing that the parasite has been removed, at the expense of a slight distortion of the main signal.

In addition, the program performs a direct computation of the Fourier transform of a set of random complex values, using function `CalcFrequency`, and stores the results in the output file, for comparison with the FFT computed on the same data.

Chapter 12

Random numbers

This chapter describes the procedures and functions available to generate random numbers and perform stochastic simulation and optimization.

12.1 Random numbers

12.1.1 Introduction

TPMath provides three random number generators (RNG) :

- the ‘Multiply With Carry’ (MWC) generator of George Marsaglia.
- the ‘Mersenne Twister’ (MT) generator of Takuji Nishimura and Makoto Matsumoto (<http://www.math.sci.hiroshima-u.ac.jp/~m-mat/MT/emt.html>).
- the ‘Universal Virtual Array Generator’ (UVAG) contributed by Alex Hay.

The first method produces a sequence $\{I_n\}$ of integer numbers by means of the following recurrence relationships:

$$I_{n+1} = (aI_n + c_n) \bmod b$$

$$c_{n+1} = (aI_n + c_n) \operatorname{div} b$$

where a is the *multiplier*, b the *base* (such that $b = 2^k$), c_n the *carry*. One may start with $c_0 = 0$.

If a is properly chosen, the period of the generator is $a \times 2^{k-1} - 1$. In our implementation, a 32-bit integer is generated by concatenating two 16-bit

integers, with $a_1 = 18000$ and $a_2 = 30903$. The period of the 32-bit generator is therefore:

$$(a_1 \times 2^{15} - 1) \times (a_2 \times 2^{15} - 1) \approx 6 \times 10^{17}$$

The second method is more complex and slightly slower but it may be safer for intensive simulations since it has a much longer period (about 10^{6000}) and produces uncorrelated numbers in 623 dimensions.

We have verified that the three generators pass Marsaglia's DIEHARD battery of tests (<http://stat.fsu.edu/pub/diehard/>).

12.1.2 Types

TPMath defines the following types:

- `RNG.Type` which defines the type of generator, with 3 possible values: `RNG_MWC`, `RNG_MT`, `RNG_UVAG`
- `RNG.IntType` which is a 32-bit signed integer
- `RNG.LongType` which is a 32-bit signed or unsigned integer

The correspondence between these integer types and the original ones depends on the compiler, as shown in the following table:

TPMath type	16-bit compiler	32-bit compiler
<code>RNG.IntType</code>	<code>LongInt</code> (32-bit signed)	<code>Integer</code> (32-bit signed)
<code>RNG.LongType</code>	<code>LongInt</code> (32-bit signed)	<code>Cardinal</code> (32-bit unsigned)

12.1.3 Generic functions

These functions may be used with any of the three generators.

Choice of generator

The generator is chosen by using one of the statements: `SetRNG(RNG_MWC)`, `SetRNG(RNG_MT)` or `SetRNG(RNG_UVAG)`. A default initialization is performed at the same time.

Initialization

The selected generator can be initialized with the statement `InitGen(Seed)` where `Seed` is of type `(RNG.IntType)`.

Uniform random numbers

The following functions are available:

Function	Type	Bits	Domain
IRanGen	RNG_IntType	32	[-2147483648, 2147483647]
IRanGen31	RNG_IntType	31	[0, 2147483647]
RanGen1	Float	32	[0, 1]
RanGen2	Float	32	[0, 1)
RanGen3	Float	32	(0, 1)
RanGen53	Float	53	[0, 1)

12.1.4 Specific functions

The following functions are specific of a given generator:

- Subroutine **InitMWC(Seed)** initializes the MWC generator with a **RNG_IntType** integer.

The default initialization performed by **SetRNG** corresponds to **Seed = 118105245**.

- Function **IRanMWC** returns a **RNG_IntType** random integer from the MWC generator.
- Subroutine **InitMT(Seed)** initializes the MT generator with a **RNG_IntType** integer.
- Subroutine **InitMTbyArray(InitKey, KeyLength)** initializes the MT generator with an array **InitKey[0..(KeyLength - 1)]** of **RNG_LongType** integers, with **KeyLength < 624**.

The default initialization performed by **SetRNG** corresponds to the vector (**\$123, \$234, \$345, \$456**).

- Function **IRanMT** returns a **RNG_IntType** random integer from the MT generator.
- Subroutine **InitUVAGbyString(KeyPhrase)** initializes the UVAG generator with a string **KeyPhrase**.

The default initialization performed by **SetRNG** corresponds to the string **'abcd'**.

- Subroutine `InitUVAG(Seed)` initializes the UVAG generator with a `RNG_IntType` integer.
- Function `IRanUVAG` returns a `RNG_IntType` signed integer from the UVAG generator.

12.1.5 Gaussian random numbers

These functions use the selected generator.

Normal distribution

- Function `RanGaussStd` generates a random number from the standard normal distribution.

The Box-Muller algorithm is used: if x_1 and x_2 are two uniform random numbers $\in (0, 1)$, the two numbers y_1 and y_2 defined by:

$$y_1 = \sqrt{-2 \ln x_1} \cos 2\pi x_2 \quad y_2 = \sqrt{-2 \ln x_1} \sin 2\pi x_2$$

follow the standard normal distribution.

- Function `RanGauss(Mu, Sigma)` generates a random number from the normal distribution with mean `Mu` and standard deviation `Sigma`.

Multinormal distribution

- Subroutine `RanMult(M, L, Lb, Ub, X)` generates a random vector `X` from a multidimensional normal distribution. `M[Lb..Ub]` is the mean vector, `L[Lb..Ub, Lb..Ub]` is the Cholesky factor of the variance-covariance matrix.

To simulate the n -dimensional multinormal distribution $\mathcal{N}(\mathbf{m}, \mathbf{V})$, where \mathbf{m} is the mean vector and \mathbf{V} the variance-covariance matrix, the following algorithm is used:

1. Let \mathbf{u} be a vector of n independent random numbers following the standard normal distribution,
 2. Let \mathbf{L} be the lower triangular matrix resulting from the Cholesky factorization of matrix \mathbf{V} ,
 3. Vector $\mathbf{x} = \mathbf{m} + \mathbf{L}\mathbf{u}$ follows the multinormal distribution $\mathcal{N}(\mathbf{m}, \mathbf{V})$.
- Subroutine `RanMultIndep(M, S, Lb, Ub, X)` generates a random number from an uncorrelated multidimensional distribution. Here `S` is simply the vector of standard deviations.

12.2 Markov Chain Monte Carlo

It is not always possible to simulate the distribution of a random variable with a direct algorithm such as the ones used for normal or multinormal distributions.

However, there exist iterative algorithms which generate a sequence of random variables for which the distribution tend towards the desired distribution, after starting from a standard distribution (e. g. uniform).

These random sequences are known as *Markov chains* and the iterative simulation method is therefore known as *Markov chain Monte-Carlo* (MCMC).

There are several MCMC variants. Here we will present the Metropolis-Hastings method.

Let \mathbf{X} a vector of random variables and $P(\mathbf{X})$ its probability density function (p.d.f.), which is to be simulated. The classical formulation of the Metropolis-Hastings algorithm is the following:

1. Choose an initial parameter vector \mathbf{X}_0
2. At iteration n :
 - (a) Draw a vector \mathbf{u} from the multinormal distribution $\mathcal{N}(\mathbf{X}_{n-1}, \mathbf{V})$ where \mathbf{V} is the variance-covariance matrix
 - (b) If $r = P(\mathbf{u})/P(\mathbf{X}_{n-1}) > 1$, set $\mathbf{X}_n = \mathbf{u}$
 otherwise if $\text{Random}(0, 1) < r$, set $\mathbf{X}_n = \mathbf{u}$
 where $\text{Random}(0, 1)$ denotes a uniform random number in the interval $[0, 1]$
3. Set $n = n + 1$; goto 2

It is convenient to introduce a function $F(\mathbf{X})$ such that:

$$P(\mathbf{X}) = C \exp \left[-\frac{F(\mathbf{X})}{T} \right] \quad \Longleftrightarrow \quad F(\mathbf{X}) = -T \ln \frac{P(\mathbf{X})}{C} \quad (12.1)$$

where C and T are positive constants. By analogy with statistical thermodynamics, T is known as the *temperature*.

From this equation, it may be seen that:

$$r = \frac{P(\mathbf{u})}{P(\mathbf{X}_{n-1})} = \exp \left(-\frac{\Delta F}{T} \right)$$

where

$$\Delta F = F(\mathbf{u}) - F(\mathbf{X}_{n-1})$$

so, the Metropolis-Hastings algorithm may be rewritten as:

1. Choose an initial parameter vector \mathbf{X}_0
2. At iteration n :
 - (a) Draw a vector \mathbf{u} from the multinormal distribution $\mathcal{N}(\mathbf{X}_{n-1}, \mathbf{V})$
Set $\Delta F = F(\mathbf{u}) - F(\mathbf{X}_{n-1})$
 - (b) if $\Delta F < 0$, set $\mathbf{X}_n = \mathbf{u}$
otherwise if $\text{Random}(0, 1) < \exp(-\Delta F/2)$, set $\mathbf{X}_n = \mathbf{u}$
3. Set $n = n + 1$; goto 2

The initial variance-covariance matrix \mathbf{V} may be diagonal and its elements may be given large values, so that the initial distribution spans a relatively large space. When the iterations progress, the matrix converges to the variance-covariance matrix of the simulated distribution. It is often useful to perform several cycles of the algorithm, with the variance-covariance matrix being re-evaluated at the end of each cycle.

The vector \mathbf{X} corresponding to the lowest value of F is recorded; hence, the algorithm may be used as a stochastic optimization algorithm for minimizing the function F . The advantage of such an algorithm is that it can ‘escape’ from a local minimum (with a probability equal to $e^{-\Delta F/T}$) and has therefore more chances to reach the global minimum, unlike the deterministic optimizers studied in chapter 7, for which only decreases of the function are acceptable. This application is however restricted by the fact that the function F must be linked to a p.d.f. by means of eq. (12.1).

This method is implemented in TPMath as:

```
Hastings(Func, T, X, V, Lb, Ub, Xmat, X_min, F_min)
```

The user must provide :

- the function **Func** to be minimized (defined as in paragraph 7.2, p. 52)
- the temperature **T**
- a starting vector **X[Lb..Ub]**
- a starting variance-covariance matrix **V[Lb..Ub, Lb..Ub]**.

On output, `Hastings` returns:

- the mean of the simulated distribution in `X`
- its variance-covariance matrix in `V`
- a matrix of simulated vectors in `Xmat` (one vector by line)
- the vector which minimizes the function in `X_min`
- the value of the function at the minimum in `F_min` (corresponds to the mode of the simulated distribution).

The behavior of the algorithm can be controlled with the following procedure:

```
InitMHPparams(NCycles, MaxSim, SavedSim)
```

where:

- `NCycles` is the number of cycles (default = 10)
- `MaxSim` is the maximum number of simulations at each cycle (default = 1000)
- `SavedSim` is the number of simulated vectors which are saved in matrix `Xmat`. Only the last `SavedSim` vectors from the last cycle are saved. (default = 1000)

The current values of these parameters can be retrieved with the procedure `GetMHPparams(NCycles, MaxSim, SavedSim)`.

After a call to `Hastings`, function `MathErr` will return one of the following codes:

- `OptOk` if no error occurred
- `MatNotPD` if the variance-covariance matrix is not positive definite

The random number generator is re-initialized at the start of the algorithm, so that a different result will be obtained for each call of the subroutine.

12.3 Simulated Annealing

Simulated annealing (SA) is an extension of the Metropolis-Hastings algorithm which tries to find the global minimum of any function (not necessarily a p.d.f.). Here the temperature starts from a high value and is progressively decreased as the algorithm progresses towards the minimum. The optimized parameters may then be refined with a local optimizer (chapter 7).

The implementations used in TPMath is a modification of a Fortran program written by B. Goffe (<http://www.netlib.org/simann>).

With the notations:

$F(\mathbf{X})$: function to be minimized
$\delta\mathbf{X}$: range of \mathbf{X}
F_{min}	: minimum of $F(\mathbf{X})$
T	: temperature
N_T	: number of loops at constant T
N_S	: number of loops before ajustement of $\delta\mathbf{X}$
R_T	: temperature reduction factor
N_{acc}	: number of accepted function increases

the algorithm may be described as follows:

-
- initialize $T, \mathbf{X}, \delta\mathbf{X}$
 - repeat
 - repeat N_T times
 - ★ repeat N_S times
 - for each parameter X_i :
 - ◊ pick a random value X'_i in the interval $X_i \pm \delta X_i$
 - ◊ compute $F(X'_i)$
 - ◊ accept or reject X'_i according to Metropolis criterion
 - ◊ update N_{acc}
 - ◊ update F_{min} if necessary
 - ★ adjust step length δX_i so as to maintain an acceptance ratio of about 50%
 - $T \leftarrow T \cdot R_T$
 - until $N_{acc} = 0$ or $T < T_{min}$ or $|F_{min}| < \epsilon$

The threshold values T_{min} and ϵ are fixed at 10^{-30} in our implementation.

At the beginning of the iterations, while we are away from the minimum, it makes sense to choose a high probability of acceptance, for instance $p = \frac{1}{2}$. It is then possible to perform a given number of random drawings and to compute the median M of the increases of function F , from which the initial temperature T_0 is deduced by:

$$p = \exp\left(-\frac{M}{T_0}\right) = \frac{1}{2} \quad \Rightarrow \quad T_0 = \frac{M}{\ln 2}$$

This procedure is implemented in the following subroutine:

`SimAnn(Func, X, Xmin, Xmax, Lb, Ub, F_min)`

where:

- `Func` is the function to be minimized (defined as in paragraph 7.2, p. 52)
- `X[Lb..Ub]` is the parameter vector
- `Xmin`, `Xmax` are the bound values of `X`

The optimized parameters are returned in `X` and the corresponding function value in `F_min`

The user must provide reasonable values of `Xmin` and `Xmax` as well as a starting value for `X`. It is convenient to pick a random value in the range specified by `Xmin` and `Xmax`.

The behavior of the algorithm can be controlled with the following procedure:

`InitSAParams(NT, NS, NCycles, RT)`

where:

- `NT`, `NS`, `RT` correspond to the variables N_T , N_S and R_T in the algorithm. Default values are 5, 15 and 0.9 respectively.
- `NCycles` is the number of cycles (default = 1).

In some difficult situations, it may be useful to perform several cycles of the algorithm. Each cycle will start with the optimized parameters \mathbf{X} from the previous cycle and the temperature will be re-initialized (the bound values \mathbf{X}_{\min} , \mathbf{X}_{\max} remaining the same).

It is possible to record the progress of the iterations in a log file. This file is created with:

```
SA_CreateLogFile(LogFileName)
```

If the file is created, the following information will be stored:

- iteration number (each iteration corresponds to a single temperature)
- temperature value
- lowest function value obtained at this temperature
- number of function increases
- number of accepted increases

The file will be automatically closed upon return from `SimAnn`.

12.4 Genetic Algorithm

Genetic Algorithms (GA) are another class of stochastic optimization methods which try to mimick the law of natural selection in order to optimize a function $F(\mathbf{X})$.

There are several implementations of these algorithms. We use a method described by E. Perrin *et al.* (*Recherche operationnelle / Operations Research*, 1997, **31**, 161-201). In this version, the vector \mathbf{X} is considered as the ‘phenotype’ of an ‘individual’ belonging to a ‘population’. This phenotype is determined by two ‘chromosomes’ \mathbf{C}_1 and \mathbf{C}_2 and a vector of ‘dominances’ \mathbf{D} such that:

$$X_i = D_i C_{1i} + (1 - D_i) C_{2i} \quad (0 < D_i < 1) \quad (12.2)$$

A population is defined by a matrix \mathbf{P} , such that each row of the matrix corresponds to a vector \mathbf{X} .

The population is initialized by taking vectors \mathbf{C}_1 and \mathbf{C}_2 at random in a given interval, vector \mathbf{D} at random in (0,1) then applying eq. (12.2) to obtain the corresponding \mathbf{X} vectors.

At each step (‘generation’) of the algorithm:

1. The function values $F(\mathbf{X})$ are computed for each vector \mathbf{X} and the N_S individuals having the lowest function values (the ‘survivors’) are selected.
2. The remaining individuals are discarded and replaced by new ones, generated as follows:
 - (a) Two ‘parents’ are chosen at random in the selected sub-population and a ‘child’ is generated by:
 - taking the vectors \mathbf{C}_1 and \mathbf{C}_2 at random from the parents
 - generating a new vector \mathbf{D}
 - computing the new \mathbf{X} according to eq. (12.2)
 This process is repeated until the function value for the child is lower than the lowest function value of the two parents.
 - (b) The child is ‘mutated’ (i. e. its vectors are reinitialized at random) with a probability M_R
 - (c) The child is made ‘homozygous’ (i. e. its vectors \mathbf{C}_1 and \mathbf{C}_2 are made identical to its vector \mathbf{X}) with a probability H_R

This procedure is implemented in the following subroutine:

`GenAlg(Func, X, Xmin, Xmax, Lb, Ub, F_min)`

where the parameters have the same meaning as in **SimAnn**.

The behavior of the algorithm can be controlled with the following procedure:

`InitGAParams(NP, NG, SR, MR, HR)`

where:

- NP is the population size (default = 200)
- NG is the number of generations (default = 40)
- SR is the survival rate (default = 0.5)
- MR is the mutation rate (default = 0.1)
- HR is the probability of homozygosis (default = 0.5)

A log file may also be created with:

`GA_CreateLogFile(LogFileName)`

The file will contain the iteration (generation) number and the optimized function value for this generation.

12.5 Demo programs

12.5.1 Test of MWC generator

Program `testmwc.pas` picks 20000 random numbers and displays the next 6 together with the correct values obtained with the default initialization.

12.5.2 Test of MT generator

Program `testmt.pas` writes 1000 integer numbers and 1000 real numbers from functions `IRanGen` and `RanGen2`, using the default initialization.

The output of this program should be similar to the contents of file `mt.txt`

12.5.3 Test of UVAG generator

Program `testuvag.pas` writes 1000 integer numbers from function `IRanGen`, using the default initialization. The output should be similar to the contents of file `uvag.txt`

12.5.4 File of random numbers

Program `randfile.pas` generates a binary file of 32-bit random integers to be used as input for the DIEHARD program. The user must specify the number of random integers to be generated (default is 3,000,000).

12.5.5 Gaussian random numbers

Program `testnorm.pas` picks a random sample of size N from a gaussian distribution with known mean and standard deviation (SD), estimates mean (m) and SD (s) from the sample, and computes a 95% confidence interval for the mean (i.e. an interval which has a probability of 0.95 to include the true mean), using the formula:

$$\left[m - 1.96 \frac{s}{\sqrt{N}}, m + 1.96 \frac{s}{\sqrt{N}} \right]$$

This formula is valid for $N > 30$.

12.5.6 Multinormal distribution

Program `ranmul.pas` simulates a multi-normal distribution. The example is a 3-dimensional distribution with the following means, standard deviations, and correlation matrix:

$$\mathbf{m} = \begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix} \quad \mathbf{s} = \begin{bmatrix} 0.1 \\ 0.2 \\ 0.3 \end{bmatrix} \quad \mathbf{R} = \begin{bmatrix} 1 & 0.25 & 0.5 \\ 0.25 & 1 & -0.25 \\ 0.5 & -0.25 & 1 \end{bmatrix}$$

These data are stored in the input file `ranmul.dat`. The results of the simulation are stored in file `ranmul.out`

12.5.7 Multi-lognormal distribution

A vector \mathbf{x} is said to follow a multi-lognormal distribution $\mathcal{LN}(\mathbf{m}, \mathbf{V})$ if the vector \mathbf{x}° defined by:

$$x_i^\circ = \ln(x_i)$$

follows a multinormal distribution $\mathcal{N}(\mathbf{m}^\circ, \mathbf{V}^\circ)$

It may be shown that:

$$m_i^\circ = \ln(x_i) - V_{ii}^\circ$$
$$V_{ij}^\circ = \ln \left(1 + \frac{V_{ij}}{m_i m_j} \right)$$

So, if \mathbf{x}° is a random vector drawn from $\mathcal{N}(\mathbf{m}^\circ, \mathbf{V}^\circ)$, $\mathbf{x} = \exp(\mathbf{x}^\circ)$ will be a vector from $\mathcal{LN}(\mathbf{m}, \mathbf{V})$

Program `ranmul1.pas` simulates a multi-lognormal distribution. The example is a 2-dimensional distribution with the following means, standard deviations, and correlation coefficient:

$$\mathbf{m} = \begin{bmatrix} 17.4178 \\ 5.3173 \end{bmatrix} \quad \mathbf{s} = \begin{bmatrix} 6.1259 \\ 2.5158 \end{bmatrix} \quad r = 0.5672$$

These data are stored in the input file `ranmul1.dat`. The results of the simulation are stored in file `ranmul1.out`

12.5.8 Markov Chain Monte-Carlo

Although MCMC methods are best suited when there is no direct simulation algorithm available, we will use the Metropolis-Hastings method to simulate the previous multinormal distribution (program `testmcmc.pas`).

First, we have to define the function to be optimized. The probability density for a n -dimensional normal distribution $\mathcal{N}(\mathbf{m}, \mathbf{V})$ is:

$$P(\mathbf{X}) = \frac{1}{\sqrt{(2\pi)^n |\mathbf{V}|}} \exp \left[-\frac{1}{2} (\mathbf{X} - \mathbf{m})^\top \mathbf{V}^{-1} (\mathbf{X} - \mathbf{m}) \right]$$

So, according to eq. 12.1, $T = 2$ and:

$$F(\mathbf{X}) = (\mathbf{X} - \mathbf{m})^\top \mathbf{V}^{-1} (\mathbf{X} - \mathbf{m})$$

Then, we have to define a starting vector \mathbf{X}_{sim} and variance-covariance matrix \mathbf{V}_{sim} . In order to show that the algorithm can converge from a point chosen relatively far away from the optimum, we have chosen $\mathbf{X}_{sim} = 3\mathbf{m}$ and $\mathbf{V}_{sim} = \text{diag}(10V_{ii})$.

With the default initializations (10 cycles of 1000 simulations each), the results of a typical run were:

$$\hat{\mathbf{m}} = \begin{bmatrix} 1.01 \\ 2.02 \\ 3.01 \end{bmatrix} \quad \hat{\mathbf{s}} = \begin{bmatrix} 0.099 \\ 0.210 \\ 0.320 \end{bmatrix} \quad \hat{\mathbf{R}} = \begin{bmatrix} 1 & 0.286 & 0.467 \\ 0.286 & 1 & -0.299 \\ 0.467 & -0.299 & 1 \end{bmatrix}$$

12.5.9 Simulated Annealing

Program `simann.pas` uses simulated annealing to minimize a set of 10 notoriously difficult functions (most of them presenting multiple minima). Several successive runs of the program may be necessary to have all functions minimized (the random number generator being reinitialized at each call of the `SimAnn` subroutine).

12.5.10 Genetic Algorithm

Program `genalg.pas` optimizes the same functions than the previous program but with genetic algorithm. Here, too, it may be necessary to run the program several times.

Chapter 13

Statistics

This chapter describes some of the statistical functions available in TPMath. The specific problem of curve fitting will be considered in subsequent chapters.

13.1 Descriptive statistics

The following functions are available:

- Function `Min(X, Lb, Ub)` returns the minimum of sample `X[Lb..Ub]`
- Function `Max(X, Lb, Ub)` returns the maximum of sample `X[Lb..Ub]`
- Function `Mean(X, Lb, Ub)` returns the mean of sample `X[Lb..Ub]`, defined by:

$$m = \frac{1}{n} \sum_{i=1}^n x_i$$

where n is the size of the sample.

- Function `Median(X, Lb, Ub, Sorted)` returns the median of `X`, defined as the number x_{med} which has equal numbers of values above it and below it. If the array `X` has been sorted, the median is:

$$x_{med} = x_{\frac{n+1}{2}} \quad (n \text{ odd})$$

$$x_{med} = \frac{1}{2} (x_{\frac{n}{2}} + x_{\frac{n}{2}+1}) \quad (n \text{ even})$$

The parameter **Sorted** indicates if array **X** has been sorted before calling function **Median**. If not, it will be sorted within the function (the array **X** will therefore be modified).

Sorting (in ascending order) is performed by calling a procedure **QSort(X, Lb, Ub)** which implements the ‘Quick Sort’ algorithm. Of course, this procedure may be called outside function **Median**. There is also a **DQSort** for sorting in descending order.

- Function **StDev(X, Lb, Ub, M)** returns the estimated standard deviation of the population from which sample **X** is extracted, **M** being the mean of the sample. This standard deviation is defined by:

$$s = \sqrt{\frac{1}{n-1} \sum_{i=1}^n (x_i - m)^2}$$

These estimated standard deviations are used in statistical tests.

- Function **StDevP(X, Lb, Ub, M)** returns the standard deviation of **X**, *considered as a whole population*. This standard deviation is defined by:

$$\sigma = \sqrt{\frac{1}{n} \sum_{i=1}^n (x_i - m)^2}$$

- Function **Correl(X, Y, Lb, Ub)** returns the correlation coefficient between **X** and **Y**:

$$r = \frac{\sum_{i=1}^n (x_i - m_x)(y_i - m_y)}{\sqrt{\sum_{i=1}^n (x_i - m_x)^2 \sum_{i=1}^n (y_i - m_y)^2}}$$

where m_x and m_y denote the means of the samples.

- Function **Skewness(X, Lb, Ub, M, Sigma)** returns the skewness of **X**, with mean **M** and standard deviation **Sigma**. This parameter is defined by:

$$\gamma_1 = \frac{1}{n\sigma^3} \sum_{i=1}^n (x_i - m)^3$$

Skewness is an indicator of the symmetric nature of the distribution. It is zero for a symmetric distribution (e. g. Gaussian), and positive (resp. negative) for an assymetric distribution with a tail extending towards positive (resp. negative) x values.

- Function `Kurtosis(X, Lb, Ub, M, Sigma)` returns the kurtosis of `X`, with mean `M` and standard deviation `Sigma`. This parameter is defined by:

$$\gamma_2 = \frac{1}{n\sigma^4} \sum_{i=1}^n (x_i - m)^4 - 3$$

Kurtosis is an indicator of the flatness of the distribution. It is zero for a Gaussian distribution, and positive (resp. negative) if the distribution is more (resp. less) ‘sharp’ than the Gaussian.

13.2 Comparison of means

13.2.1 Student’s test for independent samples

We have 2 independent samples with sizes n_1, n_2 , means m_1, m_2 , standard deviations s_1, s_2 . It is assumed that the samples are taken from gaussian populations with means μ_1, μ_2 and equal variances. The sample means are compared by computing the t -statistic:

$$t = \frac{m_1 - m_2}{s\sqrt{1/n_1 + 1/n_2}}$$

where s^2 is the estimation of the common variance:

$$s^2 = \frac{(n_1 - 1)s_1^2 + (n_2 - 1)s_2^2}{n_1 + n_2 - 2}$$

If $n_1 \geq 30$ and $n_2 \geq 30$, the conditions of normality and equal variances are no longer required and the formula becomes:

$$t = \frac{m_1 - m_2}{\sqrt{s_1^2/n_1 + s_2^2/n_2}}$$

The null hypothesis is $(H_0) : \mu_1 = \mu_2$

The alternative hypothesis (H_1) depends on the test:

One-tailed test	$(H_1) : \mu_1 > \mu_2$	\Rightarrow reject (H_0) if $t > t_{1-\alpha}$
	$(H_1) : \mu_1 < \mu_2$	\Rightarrow reject (H_0) if $t < t_{1-\alpha}$
Two-tailed test	$(H_1) : \mu_1 \neq \mu_2$	\Rightarrow reject (H_0) if $ t > t_{1-\alpha/2}$

where $t_{1-\alpha}$ is the value of the Student variable such that the cumulative probability function $\Phi_\nu(t) = 1 - \alpha$ at $\nu = n_1 + n_2 - 2$ d.o.f. (cf. chap. 5).

If H_0 is rejected, the difference of the means is considered significant at risk α

This test is implemented in the following procedure :

`StudIndep(N1, N2, M1, M2, S1, S2, T, DoF)`

where (N1, N2) are the sizes of the samples, (M1, M2) their means and (S1, S2) the estimated standard deviations (computed with `StDev`). The procedure returns Student's t in T and the number of degrees of freedom in DoF.

13.2.2 Student's test for paired samples

If the samples are paired (e. g. the same patients before and after a treatment), the t -statistic becomes:

$$t = \frac{m_d}{s_d} \sqrt{n}$$

where m_d and s_d are, respectively, the mean and standard deviations of the differences ($x_{1i} - x_{2i}$) between the paired values in the two samples, and n is the common size of the samples.

Apart from this, the test is carried out as with the independent case, with $(n - 1)$ d. o. f.

This test is implemented in the following procedure :

`StudPaired(X, Y, Lb, Ub, T, DoF)`

where `X[Lb..Ub]`, `Y[Lb..Ub]` are the two samples. The procedure returns Student's t in T and the number of degrees of freedom in DoF.

After a call to this procedure, function `MathErr` returns one of the following error codes:

- `F0k` (0) if no error occurred
- `FSing` (-2) if $s_d = 0$
- `MatErrDim` (-3) if X and Y have different sizes.

13.2.3 One-way analysis of variance (ANOVA)

We have k independent samples with sizes n_i , means m_i , standard deviations s_i . It is assumed that the samples are taken from gaussian populations with means μ_i and equal variances. The goal is to compare the k means.

The following equation holds:

$$SS_t = SS_f + SS_r \quad (13.1)$$

with:

$$SS_t = \sum_{i=1}^k \sum_{j=1}^{n_i} (x_{ij} - \bar{x})^2 \quad SS_f = \sum_{i=1}^k n_i (m_i - \bar{x})^2 \quad SS_r = \sum_{i=1}^k (n_i - 1) s_i^2$$

- \bar{x} is the global mean:

$$\bar{x} = \frac{1}{n} \sum_{i=1}^k n_i m_i \quad n = \sum_{i=1}^k n_i$$

- SS_t is the *total sum of squares*; it has $(n - 1)$ degrees of freedom
- SS_f is the *factorial sum of squares*; it has $(k - 1)$ degrees of freedom.
- SS_r is the *residual sum of squares*; it has $(n - k)$ degrees of freedom

Note that the degrees of freedom (d.o.f.) are additive, just like the sums of squares:

$$(n - 1) = (k - 1) + (n - k)$$

The *variances* are defined by dividing each sum of squares by the corresponding number of d.o.f.

$$V_t = \frac{SS_t}{n - 1} \quad V_f = \frac{SS_f}{k - 1} \quad V_r = \frac{SS_r}{n - k}$$

These are the total, factorial, and residual variances, respectively. Note that the variances, unlike the sum of squares, are *not* additive!

The comparison of means is performed by computing the F -statistic:

$$F = \frac{V_f}{V_r}$$

The null hypothesis is $(H_0) : \mu_1 = \mu_2 = \dots = \mu_k$

(H_0) is rejected if $F > F_{1-\alpha}$ where $F_{1-\alpha}$ is the value of the Fisher-Snedecor variable such that the cumulative probability function $\Phi_{\nu_1, \nu_2}(F) = 1 - \alpha$ at $\nu_1 = k - 1$ and $\nu_2 = n - k$ d.o.f. (cf. chap. 5).

This algorithm is implemented in the following procedure :

AnOVa1(Ns, N, M, S, V_f, V_r, F, DoF_f, DoF_r)

where **Ns** is the number of samples, **N**[1..**Ns**] are the sizes of the samples, **M**[1..**Ns**] their means and **S**[1..**Ns**] the estimated standard deviations (computed with **StDev**).

The procedure returns the factorial and residual variances in **V_f** and **V_r**, their ratio in **F** and their numbers of d. o. f. in **DoF_f** and **DoF_r**.

After a call to this procedure, function **MathErr** returns one of the following error codes:

- **F0k** (0) if no error occurred
- **FSing** (-2) if $n - k \leq 0$
- **MatErrDim** (-3) if the arrays have non-compatible dimensions

13.2.4 Two-way analysis of variance

We assume here that the means of the samples depend on two factors A and B, such that the sample corresponding to the i -th level of A and the j -th level of B has mean m_{ij} and standard deviation s_{ij} .

It is also assumed that all samples are taken from gaussian populations with equal variances, and that they have the same size n .

The previous equations become:

$$\bar{x} = \frac{1}{npq} \sum_{i=1}^p \sum_{j=1}^q nm_{ij}$$

$$SS_t = \sum_{i=1}^p \sum_{j=1}^q (x_{ij} - \bar{x})^2 \quad SS_f = \sum_{i=1}^p \sum_{j=1}^q n(m_{ij} - \bar{x})^2 \quad SS_r = \sum_{i=1}^p \sum_{j=1}^q (n-1)s_{ij}^2$$

with $npq - 1$, $pq - 1$, and $(n - 1)pq$ d.o.f., respectively.

In addition, the factorial sum of squares can be splitted into three terms:

$$SS_A = qn \sum_{i=1}^p (m_{i.} - \bar{x})^2 \quad ; \quad (p - 1) \text{ d.o.f.}$$

$$SS_B = pn \sum_{j=1}^q (m_{.j} - \bar{x})^2 \quad ; \quad (q - 1) \text{ d.o.f.}$$

$$SS_{AB} = n \sum_{i=1}^p \sum_{j=1}^q (m_{ij} - m_{i.} - m_{.j} + \bar{x})^2 \quad ; \quad (p - 1)(q - 1) \text{ d.o.f.}$$

where $m_{i.}$ and $m_{.j}$ are the conditional means:

$$m_{i.} = \frac{1}{q} \sum_{j=1}^q m_{ij} \quad m_{.j} = \frac{1}{p} \sum_{i=1}^p m_{ij}$$

that is, the means of the lines and columns of matrix $[m_{ij}]$

These sums of squares represent, respectively, the influence of factor A, the influence of factor B, and the interaction of the two factors (that is, the fact that the influence of one factor depends on the level of the other factor).

The variances are computed as before:

$$V_A = \frac{SS_A}{p-1} \quad V_B = \frac{SS_B}{q-1} \quad V_{AB} = \frac{SS_{AB}}{(p-1)(q-1)} \quad V_r = \frac{SS_r}{(n-1)pq}$$

There are three null hypotheses:

- $(H_0)_A$: The populations means do not depend on factor A
- $(H_0)_B$: The populations means do not depend on factor B
- $(H_0)_{AB}$: There is no interaction between the two factors

Each hypothesis is tested by computing the corresponding F -statistic (for instance, $F_A = V_A/V_r$ for testing $(H_0)_A$) and comparing with the critical value $F_{1-\alpha}$

Special case: $n = 1$. If there is only one observation per sample, the residual variance is zero. The null hypotheses $(H_0)_A$ and $(H_0)_B$ are tested with $F_A = V_A/V_{AB}$ and $F_B = V_B/V_{AB}$. The interaction of the factors cannot be tested.

This algorithm is implemented in the following procedure :

AnOVa2(NA, NB, Nobs, M, S, V, F, DoF)

where NA and NB are the number of levels of the factors A and B, Nobs the common number of observations, M[1..NA, 1..NB] the matrix of means and S[1..NA, 1..NB] the matrix of standard deviations, such that the rows correspond to factor A and the columns to factor B.

The procedure returns the variances in vector V[1..4] = $[V_A, V_B, V_{AB}, V_r]$, the variance ratios in F[1..3] = $[F_A, F_B, F_{AB}]$, and the degrees of freedom in DoF[1..4]. If N = 1, the last element of each vector disappears.

After a call to this procedure, function **MathErr** returns one of the following error codes:

- FOk (0) if no error occurred
- MatErrDim (-3) if the arrays have non-compatible dimensions.

13.3 Comparison of variances

13.3.1 Comparison of two variances

We have 2 independent samples with sizes n_1, n_2 , standard deviations s_1, s_2 . It is assumed that the samples are taken from gaussian populations with variances σ_1^2, σ_2^2 .

Snedecor's test uses the following statistic:

$$F = \frac{\max(s_1^2, s_2^2)}{\min(s_1^2, s_2^2)}$$

which is compared with the critical value $F_{1-\alpha/2}$ (two-tailed test).

This test is implemented in the following procedure :

`Snedecor(N1, N2, S1, S2, F, DoF1, DoF2)`

where (N1, N2) are the sizes of the samples and (S1, S2) the estimated standard deviations. The procedure returns the variance ratio in F and the numbers of d. o. f. in DoF1 and DoF2.

13.3.2 Comparison of several variances

We have k independent samples with sizes n_i , standard deviations s_i . It is assumed that the samples are taken from gaussian populations with variances σ_i^2 . The goal is to compare the k variances.

Bartlett's test uses the following statistic:

$$B = \frac{1}{\lambda} \left[(n - k) \ln V_r - \sum_{i=1}^k (n_i - 1) \ln s_i^2 \right]$$
$$\lambda = 1 + \frac{1}{3(k-1)} \left[\sum_{i=1}^k \frac{1}{n_i - 1} - \frac{1}{n - k} \right]$$

where $n = \sum n_i$ and V_r is the residual variance, as defined previously (§ 13.2.3).

The null hypothesis is:

$$(H_0) : \sigma_1^2 = \sigma_2^2 = \dots = \sigma_k^2$$

Under (H_0) , B follows approximately the χ^2 distribution with $(k - 1)$ d. o. f. The hypothesis is tested by comparing B with the value $\chi_{1-\alpha}^2$ such that the cumulative probability function $\Phi_\nu(\chi^2) = 1 - \alpha$ at $\nu = k - 1$ d.o.f. (cf. chap. 5).

This test is implemented in the following procedure :

`Bartlett(Ns, N, S, Khi2, DoF)`

where `Ns` is the number of samples, `N[1..Ns]` are the sizes of the samples and `S[1..Ns]` the estimated standard deviations. The procedure returns Bartlett's statistic in `Khi2` and the number of d. o. f. in `DoF`. The error codes are the same than for `AnOVA1`

13.4 Non-parametric tests

Non-parametric tests are used when the assumptions needed by the classical tests (gaussian populations with equal variances) are not fulfilled. They are also called *rank tests* because they work with the ranks of the values, rather than the values themselves.

13.4.1 Mann-Whitney test

This test compares the means of two independent samples. It is the non-parametric analog of Student's test for independent samples.

The test uses the following statistic:

$$U = \min(u_1, u_2)$$

with:

$$u_1 = n_1 n_2 + \frac{n_1(n_1 + 1)}{2} - r_1 \quad ; \quad u_2 = n_1 n_2 + \frac{n_2(n_2 + 1)}{2} - r_2$$

where (n_1, n_2) are the sample sizes, (r_1, r_2) the sums of the ranks of the two samples.

If $n_1 \geq 20$ and $n_2 \geq 20$, the variable:

$$\epsilon = \frac{U - \mu}{\sigma}$$

with:

$$\mu = \frac{n_1 n_2}{2} \quad ; \quad \sigma = \sqrt{\frac{n_1 n_2 (n_1 + n_2 + 1)}{12}}$$

follows the standard normal distribution under (H_0) .

This test is implemented in the following procedure :

`Mann_Whitney(N1, N2, X1, X2, U, Eps)`

where `N1` and `N2` are the sample sizes, `X1[1..N1]` and `X2[1..N2]` are the two samples. The procedure returns Mann-Whitney's statistic in `U` and the associated normal variable in `Eps`.

13.4.2 Wilcoxon test

This test compares the means of two paired samples. It is the non-parametric analog of Student's test for paired samples.

The test uses the following statistic:

$$T = \min(T_+, T_-)$$

where T_+ and T_- are the sums of the ranks of the positive and negative differences between the values of the two samples.

If the sample size is $N > 25$, the variable:

$$\epsilon = \frac{T - \mu}{\sigma}$$

with:

$$\mu = \frac{N(N+1)}{4} \quad ; \quad \sigma = \sqrt{\frac{N(N+1)(2N+1)}{24}}$$

follows the standard normal distribution under (H_0) .

This test is implemented in the following procedure :

`Wilcoxon(X, Y, Lb, Ub, Ndiff, T, Eps)`

where `X[Lb..Ub]` and `Y[Lb..Ub]` are the two samples. The procedure returns the number of non-zero differences in `Ndiff`, Wilcoxon's statistic in `T` and the associated normal variable in `Eps`.

13.4.3 Kruskal-Wallis test

This test compares the means of several independent samples. It is the non-parametric analog of one-way ANOVA.

The test uses the following statistic:

$$H = \frac{12}{n(n+1)} \sum_{i=1}^k \frac{r_i^2}{n_i} - 3(n+1)$$

where k is the number of samples, n_i the size of sample i , r_i the sum of the ranks for sample i and n the total size.

If $n_i > 5 \forall i$, H follows the χ^2 distribution with $k - 1$ d.o.f.

This test is implemented in the following procedure :

`Kruskal_Wallis(Ns, N, X, H, DoF)`

where `Ns` is the number of samples, `N[1..Ns]` is the vector of sizes and `X` the sample matrix (with the samples as columns). The procedure returns the Kruskal-Wallis statistic in `H` and the number of d. o. f. in `DoF`.

13.5 Statistical distribution

A statistical distribution is generated by binning data into a set of statistical classes $]x_i, x_{i+1}]$. Each class is characterized by the following parameters:

- its bounds x_i, x_{i+1}
- the number of values n_i contained in the class
- the frequency $f_i = n_i/N$ where N is the total number of values
- the density $d_i = f_i/(x_{i+1} - x_i)$

This structure is implemented in `TPMath` as:

```
type StatClass = record  { Statistical class }
  Inf : Float;           { Lower bound }
  Sup : Float;           { Upper bound }
  N    : Integer;        { Number of values }
  F    : Float;          { Frequency }
  D    : Float;          { Density }
end;
```

A distribution is generated with the following procedure:

```
Distrib(X, Lb, Ub, A, B, H, C)
```

where $X[Lb..Ub]$ is the original set of values, A and B the lower and upper bounds of the distribution and H the common width of the classes, according to the following scheme:

```

      C[1]      C[2]                                C[M]
  ]-----]-----].....]-----]-----]
  A          A+H    A+2H                                B=A+M*H
```

The distribution is returned in C which is an array of type `StatClass`.

13.6 Comparison of distributions

13.6.1 Observed and theoretical distributions

An observed distribution may be compared to a theoretical one by using the following statistics:

- Pearson's χ^2 :

$$\chi^2 = \sum_{i=1}^p \frac{(O_i - C_i)^2}{C_i}$$

- Woolf's G :

$$G = 2 \sum_{i=1}^p O_i \ln \frac{O_i}{C_i}$$

where O_i and C_i denote the observed and theoretical numbers of values in class i , and p the number of classes.

The null hypothesis is (H_0): the observed distribution conforms to the theoretical one (it is a test for conformity)

Under (H_0), both statistics follow the χ^2 distribution with $(p - 1 - N_e)$ d. o. f., where N_e is the number of parameters which have been estimated to compute the C_i values (e. g. $N_e = 2$ if the mean and standard deviation of the distribution have been estimated).

(H_0) is rejected if the chosen statistic is higher than the critical value $\chi^2_{1-\alpha}$ for the chosen risk α .

Pearson's statistic is an approximation of Woolf's statistic. It is usually recommended to use it only if $C_i \geq 5 \forall i$.

These procedures are implemented as:

```
Khi2_Conform(N_cls, N_estim, Obs, Calc, Khi2, DoF)
```

```
Woolf_Conform(N_cls, N_estim, Obs, Calc, G, DoF)
```

where `N_cls` denotes the number of classes, `N_estim` the number of estimated parameters, `Obs[1..N_cls]` and `Calc[1..N_cls]` the observed and theoretical distributions. The statistic is returned in `Khi2` or `G` and the number of d. o. f. in `DoF`.

13.6.2 Several observed distributions

To compare several observed distributions, we can group them into a *contingency table* \mathbf{O} such that O_{ij} denotes the number of values for class i in the j -th distribution.

The Pearson and Woolf statistics may then be computed as:

$$\chi^2 = \sum_{i=1}^p \sum_{j=1}^q \frac{(O_{ij} - C_{ij})^2}{C_{ij}}$$

$$G = 2 \sum_{i=1}^p \sum_{j=1}^q O_{ij} \ln \frac{O_{ij}}{C_{ij}}$$

where p the number of classes, q the number of distributions, and C_{ij} the theoretical value of O_{ij} , computed as:

$$C_{ij} = \frac{N_{i.} N_{.j}}{N}$$

where $N_{i.}$ is the sum of terms in line i , $N_{.j}$ is the sum of terms in column j , and N the global sum of all terms in the matrix ($N = \sum_i N_{i.} = \sum_j N_{.j}$).

The null hypothesis is (H_0): the observed distributions come from the same population (it is a test for homogeneity or independence).

Under (H_0), both statistics follow the χ^2 distribution with $(p-1)(q-1)$ d. o. f.

These procedures are implemented as:

```
Khi2_Indep(N_lin, N_col, Obs, Khi2, DoF)
```

```
Woolf_Indep(N_lin, N_col, Obs, G, DoF)
```

where `N_lin` and `N_col` are the numbers of lines and columns (i. e. p and q), and `Obs[1..N_lin, 1..N_col]` is the matrix of observed distributions. The statistic is returned in `Khi2` or `G` and the number of d. o. f. in `DoF`.

13.7 Demo programs

These programs are located in the `demo\stat` subdirectory of the `TPMath` directory.

13.7.1 Descriptive statistics, comparison of means and variances

Program `stat.pas` performs a statistical analysis of hemoglobin concentrations in two samples of 30 men and 30 women. The computed parameters are the mean, standard deviation, skewness and kurtosis. The means are compared by Student's test (two-tailed) and Mann-Whitney's test, and the variances are compared by Snedecor's test.

13.7.2 Student's test for paired samples

Program `student.pas` compares the means of two paired samples, using Student's and Wilcoxon's two-tailed tests.

13.7.3 One-way analysis of variance

Program `av1.pas` compares the means of 5 independent samples, each with 12 observations, using one-way ANOVA and the Kruskal-Wallis test. In addition, the variances of the samples are compared with Bartlett's test.

13.7.4 Two-way analysis of variance

- Program `av2.pas` compares the means of 4 samples, depending on two factors, using two-way ANOVA. Each sample contains 12 observations.
- Program `av2a.pas` performs two-way ANOVA with one observation per sample.

13.7.5 Statistical distribution

Program `histo.pas` uses the hemoglobin data from program `stat.bas` to generate a statistical distribution.

The first step determines a suitable range for the data. This is done by calling procedure `Interval` :

```
Interval(X^[1], X^[N], 5, 10, XMin, XMax, XStep);
```

The arguments 5 and 10 represent the minimal and maximal number of classes which is desired.

The second step generates the distribution, using the ranges determined in the previous step:

```

Ncls := Round((Xmax - Xmin) / XStep);
DimStatClassVector(C, Ncls);
Distrib(X, 1, N, Xmin, Xmax, XStep, C);

```

This distribution is then compared with the normal distribution, using both χ^2 and Woolf's tests. The theoretical C_i values are computed from the cumulative probability function for the normal distribution having the same mean and standard deviation than the observed distribution.

The program plots an histogram of the observed distribution, together with the curve corresponding to the normal distribution. This curve is generated from the probability density function:

```

function PltFunc(X : Float) : Float;
begin
  PltFunc := DNorm((X - M) / S) / S;
end;

```

where M, S are the mean and standard deviation of the observed distribution, and DNorm is the probability density of the standard normal distribution (see chapter 5). Note that the histogram is constructed with the class densities as ordinates, so that a comparison with the plotted curve can be made.

13.7.6 Comparison of distributions

Program khi2.pas performs both χ^2 and Woolf's tests, first to compare an observed distribution with a theoretical one, and then to analyse a contingency table.

Chapter 14

Linear regression

This chapter describes the routines available in **TPMath** for fitting a straight line by linear regression. Other types of curve fitting will be described in subsequent chapters.

14.1 Straight line fit

The problem is to determine the equation of the line which comes closest to a set of points.

The model is defined by the equation:

$$y = a + bx$$

- x is the independent (or ‘explicative’) variable
- y is the dependent (or ‘explained’) variable
- a and b are the model parameters

Assume that the n points $(x_1, y_1), (x_2, y_2), \dots (x_n, y_n)$ are perfectly lined, so that each of them verifies the equation of the straight line:

$$y_1 = a + bx_1$$

$$y_2 = a + bx_2$$

.....

$$y_n = a + bx_n$$

Or in matrix form:

$$\mathbf{y} = \mathbf{X}\beta \quad \Longleftrightarrow \quad \mathbf{y} - \mathbf{X}\beta = \mathbf{0}$$

where:

$$\mathbf{y} = \begin{bmatrix} y_1 \\ y_2 \\ \dots \\ y_n \end{bmatrix} \quad \mathbf{X} = \begin{bmatrix} 1 & x_1 \\ 1 & x_2 \\ \dots & \dots \\ 1 & x_n \end{bmatrix} \quad \beta = \begin{bmatrix} a \\ b \end{bmatrix}$$

In the general case, the points are not exactly lined, so that:

$$\mathbf{y} - \mathbf{X}\beta = \mathbf{r}$$

where \mathbf{r} is the vector of residuals:

$$\mathbf{r} = [r_1, r_2 \dots r_n]^\top = \mathbf{y} - \hat{\mathbf{y}}$$

where $\hat{\mathbf{y}} = \mathbf{X}\beta$

It is possible to compute β so that $\|\mathbf{r}\|$ is minimal (*least squares criterion*).

$$\|\mathbf{r}\|^2 = \mathbf{r}^\top \mathbf{r} = r_1^2 + r_2^2 + \dots + r_n^2 = \sum_{i=1}^n r_i^2 = \sum_{i=1}^n (y_i - \hat{y}_i)^2 = SS_r$$

where $\hat{y}_i = a + bx_i$ and SS_r is the *sum of squared residuals*.

Several methods allow the determination of β under the least squares criterion. The QR and SVD algorithms have been described previously. Here we will study the *method of normal equations*.

It may be shown that β is the solution of the system:

$$\mathbf{A}\beta = \mathbf{c}$$

with:

$$\mathbf{A} = \mathbf{X}^\top \mathbf{X} \quad \mathbf{c} = \mathbf{X}^\top \mathbf{y}$$

so:

$$\beta = \mathbf{A}^{-1} \mathbf{c} = (\mathbf{X}^\top \mathbf{X})^{-1} (\mathbf{X}^\top \mathbf{y})$$

The matrices may be expressed in terms of statistical sums:

$$\begin{aligned} \mathbf{A} &= \begin{bmatrix} n & \Sigma x_i \\ \Sigma x_i & \Sigma x_i^2 \end{bmatrix} & \mathbf{c} &= \begin{bmatrix} \Sigma y_i \\ \Sigma x_i y_i \end{bmatrix} \\ \mathbf{A}^{-1} &= \frac{1}{n \Sigma x_i^2 - (\Sigma x_i)^2} \begin{bmatrix} \Sigma x_i^2 & -\Sigma x_i \\ -\Sigma x_i & n \end{bmatrix} \\ \beta &= \frac{1}{n \Sigma x_i^2 - (\Sigma x_i)^2} \begin{bmatrix} \Sigma x_i^2 \Sigma y_i - \Sigma x_i \Sigma x_i y_i \\ \Sigma x_i \Sigma y_i + n \Sigma x_i y_i \end{bmatrix} \end{aligned}$$

14.2 Analysis of variance

The following equation holds:

$$SS_t = SS_e + SS_r \quad (14.1)$$

with:

$$SS_t = \sum_{i=1}^n (y_i - \bar{y})^2 \quad SS_e = \sum_{i=1}^n (\hat{y}_i - \bar{y})^2 \quad SS_r = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

- \bar{y} is the mean of the y values:

$$\bar{y} = \frac{1}{n} \sum_{i=1}^n y_i$$

- SS_t is the *total sum of squares*; it has $(n - 1)$ degrees of freedom
- SS_e is the *explained sum of squares*; it has 1 degree of freedom.
- SS_r is the *residual sum of squares*; it has $(n - 2)$ degrees of freedom

Note that the degrees of freedom (d.o.f.) are additive, just like the sums of squares:

$$(n - 1) = 1 + (n - 2)$$

The *variances* are defined by dividing each sum of squares by the corresponding number of d.o.f.

$$V_t = \frac{SS_t}{n - 1} \quad V_e = \frac{SS_e}{1} \quad V_r = \frac{SS_r}{n - 2}$$

These are the total, explained, and residual variances, respectively. Note that the variances, unlike the sum of squares, are *not* additive!

The following quantities are derived from the above equations:

- the **coefficient of determination** r^2

$$r^2 = \frac{SS_e}{SS_t}$$

r^2 represents the percentage of the variations of y which are ‘explained’ by the independent variable. It is always comprised between 0 and 1. A value of 1 indicates a perfect fit.

- the **correlation coefficient** r

It is the square root of the coefficient of determination, with the sign of the slope b . It is therefore comprised between -1 and 1.

- the **residual standard deviation** s_r

It is the square root of the residual variance ($s_r = \sqrt{V_r}$). It is an estimate of the error made on the measurement of the dependent variable y . It should be 0 for a perfect fit.

- the **variance ratio** F

It is the ratio of the explained variance to the residual variance ($F = V_e/V_r$). It should be infinite for a perfect fit.

14.3 Precision of parameters

The matrix:

$$\mathbf{V} = V_r \cdot \mathbf{A}^{-1} = V_r \cdot (\mathbf{X}^\top \mathbf{X})^{-1}$$

is called the **variance-covariance matrix** of the parameters. It is a symmetric matrix with the following structure:

$$\mathbf{V} = \begin{bmatrix} \text{Var}(a) & \text{Cov}(a, b) \\ \text{Cov}(a, b) & \text{Var}(b) \end{bmatrix}$$

The diagonal terms are the variances of the parameters, from which the standard deviations are computed by:

$$s_a = \sqrt{\text{Var}(a)} \quad s_b = \sqrt{\text{Var}(b)}$$

The off-diagonal term is the covariance of the two parameters, from which the correlation coefficient r_{ab} is computed by:

$$r_{ab} = \frac{\text{Cov}(a, b)}{s_a s_b}$$

14.4 Probabilistic interpretation

It is assumed that the residuals $(y_i - \hat{y}_i)$ are identically and independently distributed according to a normal distribution with mean 0 and standard deviation σ (estimated by s_r).

It may be shown that the regression parameters (a, b) are distributed according to a Student distribution with $(n - 2)$ d.o.f.

It is therefore possible to compute a confidence interval for each parameter, for instance:

$$\left[a - t_{1-\alpha/2} \cdot s_a \quad , \quad a + t_{1-\alpha/2} \cdot s_a \right]$$

where $t_{1-\alpha/2}$ is the value of the Student variable corresponding to the chosen probability α (usually $\alpha = 0.05$). This interval has a probability $(1 - \alpha)$ to contain the ‘true’ value of the parameter.

It is also possible to compute a ‘critical’ value $F_{1-\alpha}$ from the Fisher-Snedecor distribution with 1 and $(n - 2)$ d.o.f. The fit is considered satisfactory if the variance ratio F exceeds 4 times the critical value.

Note : for the straight line fit, $F_{1-\alpha} = \left(t_{1-\alpha/2} \right)^2$

14.5 Weighted regression

It is assumed here that the variance $v_i = \sigma_i^2$ of the measured value y_i is not constant.

The sums of squares become:

$$SS_t = \sum_{i=1}^n w_i (y_i - \bar{y})^2 \quad SS_e = \sum_{i=1}^n w_i (\hat{y}_i - \bar{y})^2 \quad SS_r = \sum_{i=1}^n w_i (y_i - \hat{y}_i)^2$$

where w_i denotes the ‘weight’, equal to $1/v_i$, and \bar{y} denotes the weighted mean:

$$\bar{y} = \frac{\sum_{i=1}^n w_i y_i}{\sum_{i=1}^n w_i}$$

The regression parameters \mathbf{b} are estimated by:

$$\mathbf{b} = (\mathbf{X}^\top \mathbf{W} \mathbf{X})^{-1} (\mathbf{X}^\top \mathbf{W} \mathbf{y})$$

where \mathbf{W} is the diagonal matrix of weights:

$$\mathbf{W} = \text{diag}(w_1, w_2, \dots, w_n) = \begin{bmatrix} w_1 & 0 & \cdots & 0 \\ 0 & w_2 & \cdots & 0 \\ \cdots & \cdots & \cdots & \cdots \\ 0 & 0 & 0 & w_n \end{bmatrix}$$

The values of r_2 , s_r and F , as well as the variance-covariance matrix, are computed as above (§ 14.2). The normalized residual for the i -th observation is:

$$\frac{y_i - \hat{y}_i}{\sigma_i} = (y_i - \hat{y}_i)\sqrt{w_i}$$

These normalized residuals should follow the standard normal distribution.

14.6 Programming

14.6.1 Regression procedures

The following subroutines are available:

- `LinFit(X, Y, Lb, Ub, B, V)` for unweighted linear regression
- `WLinFit(X, Y, S, Lb, Ub, B, V)` for weighted linear regression
- `SVDLinFit(X, Y, Lb, Ub, SVDTol, B, V)`
Same than `LinFit` but uses singular value decomposition instead of normal equations. `SVDTol` is the threshold under which a singular value is considered zero. It is expressed as a fraction of the highest singular value (see paragraph 6.9 for details).
- `WSVDLinFit(X, Y, S, Lb, Ub, SVDTol, B, V)`
Same than `WLinFit` but uses singular value decomposition.

The input parameters are:

- `X[Lb..Ub]`, `Y[Lb..Ub]` : coordinates of points
- `S[Lb..Ub]` : standard deviations of `Y` values (noted σ_i in paragraph 14.5)

The output parameters are:

- `B[0..1]` : regression parameters
- `V[0..1, 0..1]` : inverse of the matrix of normal equations (noted \mathbf{A}^{-1} in paragraph 14.3). This is **not** the variance-covariance matrix. This one will be computed by the routines described in the next paragraph.

After a call to one of these procedures, function `MathErr` returns one of the following error codes:

- `MatOk` if no error occurred
- `MatSing` if the matrix of normal equations is quasi-singular

14.6.2 Quality of fit

The parameters used to test the quality of the fit are grouped in a user-defined type:

```
type
  TRegTest = record      { Test of regression }
    Vr      : Float;     { Residual variance }
    R2      : Float;     { Coefficient of determination }
    R2a     : Float;     { Adjusted coeff. of determination }
    F       : Float;     { Variance ratio (explained/residual) }
    Nu1, Nu2 : Integer;  { Degrees of freedom }
  end;
```

They are computed by the following subroutines:

- `RegTest(Y, Ycalc, LbY, UbY, V, LbV, UbV, Test)` for unweighted regression
- `WRegTest(Y, Ycalc, S, LbY, UbY, V, LbV, UbV, Test)` for weighted regression

The input parameters are:

- `Y[LbY..UbY]` : ordinates of points
- `Ycalc[LbY..UbY]` : Y values computed from the regression equation, using the fitted parameters B. This computation must be done before calling `RegTest` or `WRegTest`.
- `V[LbV..UbV, LbV..UbV]` : the inverse matrix of the normal equations, as returned by the regression procedures.

The output parameters are:

- `V` : the variance-covariance matrix of the fitted parameters
- `Test` : variable of type `TRegTest`, as defined above.

14.7 Demo programs

These programs are located in the `demo\curfit` subdirectory of the `TPMath` directory.

14.7.1 Unweighted linear regression

Program `reglin.pas` performs the least squares fit of a straight line, according to the following equation:

$$Y = B(0) + B(1) * X$$

The parameter vector and variance-covariance matrix are therefore declared as:

```
DimVector(B, 1);  
DimMatrix(V, 1, 1);
```

The program calls procedure `LinFit`, then computes the theoretical Y values:

```
for I := 1 to N do  
  Ycalc^[I] := B^[0] + B^[1] * XX^[I];
```

Note that this computation must be done before calling procedure `RegTest`

The critical values of Student's t and Snedecor's F are computed for the chosen probability `Alpha` by using the functions from chapter 5.

```
Tc := InvStudent(N - 2, 1 - 0.5 * Alpha);  
Fc := InvSnedecor(1, N - 2, 1 - Alpha);
```

The output shows the standardized residuals, equal to $(y_i - \hat{y}_i)/\sigma$, where σ is estimated by s_r . They should be distributed according to the standard normal distribution.

14.7.2 Weighted linear regression

Program `wreglin.bas` performs the weighted least squares fit of a straight line. Here the standard deviations σ_i of the observed y values are stored in a vector `S` defined by the user.

The computations involve the same steps as with the previous program, except that procedures `WLinFit` and `WRegTest` are used, and that the standardized residuals are computed as $(y_i - \hat{y}_i)/\sigma_i$

The plot shows the error bars, corresponding to $y_i \pm \sigma_i$ for each point.

Chapter 15

Multilinear regression and principal component analysis

This chapter describes the routines available in `TPMath` for multilinear regression, polynomial regression and principal component analysis.

15.1 Multilinear regression

15.1.1 Normal equations

The regression model is:

$$y = a + bx_1 + cx_2 + \cdots$$

where the x_i are m independent variables.

The method of normal equations, studied in chapter 14, is still applicable with:

$$\mathbf{X} = \begin{bmatrix} 1 & x_{11} & x_{12} & \cdots & x_{1m} \\ 1 & x_{21} & x_{22} & \cdots & x_{2m} \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ 1 & x_{n1} & x_{n2} & \cdots & x_{nm} \end{bmatrix}$$

There are $p = m + 1$ parameters. The number of observations n must be such that $n > p$.

Special case: The x_i may be functions of another variable x , as long as these functions do not contain parameters.

Examples:

- Polynomial: $y = a + bx + cx^2 + \cdots$

- Fourier series: $y = a + b \sin x + c \sin 2x + \dots$

In such cases, the matrix \mathbf{X} , the matrix of normal equations $\mathbf{A} = \mathbf{X}^\top \mathbf{X}$ and the constant vector $\mathbf{c} = \mathbf{X}^\top \mathbf{y}$ will have special forms. For instance with polynomial regression, if d is the degree of the polynomial:

$$\mathbf{X} = \begin{bmatrix} 1 & x_1 & x_1^2 & \dots & x_1^d \\ 1 & x_2 & x_2^2 & \dots & x_2^d \\ \dots & \dots & \dots & \dots & \dots \\ 1 & x_n & x_n^2 & \dots & x_n^d \end{bmatrix}$$

$$\mathbf{A} = \begin{bmatrix} n & \Sigma x_i & \Sigma x_i^2 & \dots & \Sigma x_i^d \\ \Sigma x_i & \Sigma x_i^2 & \Sigma x_i^3 & \dots & \Sigma x_i^{d+1} \\ \dots & \dots & \dots & \dots & \dots \\ \Sigma x_i^d & \Sigma x_i^{d+1} & \Sigma x_i^{d+2} & \dots & \Sigma x_i^{2d} \end{bmatrix}$$

$$\mathbf{c} = \begin{bmatrix} \Sigma y_i \\ \Sigma x_i y_i \\ \dots \\ \Sigma x_i^d y_i \end{bmatrix}$$

It is possible to use these special forms to simplify the computations. For instance, only the first line and the last column of the above matrix \mathbf{A} need to be computed; the others terms are deduced by shifting.

15.1.2 Analysis of variance

Equation 14.1 still holds with the following modifications:

- the explained sum of squares SS_e has $(p - 1)$ degrees of freedom.
- the residual sum of squares SS_r has $(n - p)$ degrees of freedom

Note that the degrees of freedom are still additive:

$$(n - 1) = (p - 1) + (n - p)$$

The explained and residual variances become:

$$V_e = \frac{SS_e}{p - 1} \quad V_r = \frac{SS_r}{n - p}$$

The quantities r^2, s_r, F are derived as in § 14.1, but here the correlation coefficient r is always positive.

In multilinear regression, the use of r^2 may be misleading because it is always possible to artificially increase its value by adding more independent variables or using a higher degree polynomial. To overcome this drawback, the **adjusted coefficient of determination** may be used instead:

$$r_a^2 = 1 - (1 - r^2) \frac{n - 1}{n - p}$$

15.1.3 Precision of parameters

The variance-covariance matrix \mathbf{V} is computed as in chapter 14. It is a $p \times p$ symmetric matrix such that:

- the diagonal term V_{ii} is the variance of the i -th parameter
- the off-diagonal term V_{ij} is the covariance of the i -th and j -th parameters

The correlation coefficient r_{ij} is computed by:

$$r_{ij} = \frac{V_{ij}}{\sqrt{V_{ii}V_{jj}}}$$

15.1.4 Probabilistic interpretation

Assuming that the residuals are identically and independently distributed according to a normal distribution, the regression parameters are distributed according to a Student distribution with $(n - p)$ d.o.f. Confidence intervals may be computed as in chapter 14.

The ‘critical’ value $F_{1-\alpha}$ is computed from the Fisher-Snedecor distribution with $(p-1)$ and $(n-p)$ d.o.f. However, the relationship $F_{1-\alpha} = \left(t_{1-\alpha/2}\right)^2$ does not hold if $p > 2$.

15.1.5 Weighted regression

Weighted multilinear regression may be performed as for the simple linear case (chap. 14).

15.1.6 Programming

The following subroutines are available:

- `MulFit(X, Y, Lb, Ub, Nvar, ConsTerm, B, V)` for unweighted multilinear regression

`X[Lb..Ub, 1..Nvar]` is the matrix of independent variables, `Y[Lb..Ub]` is the vector of dependent variable, and `ConsTerm` is a boolean parameter which indicates the presence of a constant term b_0 . The regression parameters are returned in `B` and the inverse matrix in `V`.

- `WMulFit(X, Y, S, Lb, Ub, Nvar, ConsTerm, B, V)` for weighted multilinear regression

The additional parameter `S` is a vector containing the standard deviations of the observations.

- `SVDFit(X, Y, Lb, Ub, Nvar, ConsTerm, SVDTol, B, V)`

Same than `MulFit` but uses singular value decomposition instead of normal equations. `SVDTol` is the threshold under which a singular value is considered zero. It is expressed as a fraction of the highest singular value (see paragraph 6.9 for details).

- `WSVDFit(X, Y, Lb, Ub, Nvar, ConsTerm, SVDTol, B, V)`

Same than `WMulFit` but uses singular value decomposition.

- `PolFit(X, Y, Lb, Ub, Deg, B, V)` for unweighted polynomial regression

Here `X[Lb..Ub]` and `Y[Lb..Ub]` are the point coordinates and `Deg` is the degree of the polynomial.

- `WPolFit(X, Y, S, Lb, Ub, Deg, B, V)` for weighted polynomial regression

- `SVDPolFit(X, Y, Lb, Ub, Deg, SVDTol, B, V)`

Same than `PolFit` but uses singular value decomposition.

- `WSVDPolFit(X, Y, S, Lb, Ub, Deg, SVDTol, B, V)`

Same than `WPolFit` but uses singular value decomposition.

After a call to one of these procedures, function `MathErr` returns one of the following error codes:

- MatOk if no error occurred
- MatSing if the matrix of normal equations is quasi-singular
- MatErrDim if the array dimensions do not match

15.2 Principal component analysis

15.2.1 Theory

The goal of Principal Component Analysis (PCA) is to replace a set of m variables $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m$, which may be correlated, by another set $\mathbf{f}_1, \mathbf{f}_2, \dots, \mathbf{f}_m$, called the *principal components* or *principal factors*. These factors are independent (uncorrelated) variables.

Usually, the algorithm starts with the *correlation matrix* \mathbf{R} which is a $m \times m$ symmetric matrix such that R_{ij} is the correlation coefficient between variable \mathbf{x}_i and variable \mathbf{x}_j .

The eigenvalues $\lambda_1, \lambda_2, \dots, \lambda_m$ (in decreasing order) of matrix \mathbf{R} are the variances of the principal factors. Their sum $\sum_{i=1}^m \lambda_i$ is equal to m . So, the percentage of variance associated with the i -th factor is equal to λ_i/m .

If \mathbf{C} is the matrix of eigenvectors of \mathbf{R} , the correlation coefficient between variable \mathbf{x}_i and factor \mathbf{f}_j (sometimes called *loading*) is:

$$R_{C_{ij}} = C_{ij} \sqrt{\lambda_j}$$

The coordinates of the principal factors (sometimes called *scores*) are such that:

$$\mathbf{F} = \mathbf{ZC}$$

where \mathbf{Z} denotes the matrix of scaled original variables:

$$Z_{ij} = \frac{X_{ij} - m_j}{s_j}$$

where m_j and s_j are the mean and standard deviation of the j -th variable.

Note that the reduced variables have means 0 and variances 1, while the principal factors have means 0 and variances λ_i .

In most cases, a limited number of principal factors represent the most part of the total variance. It is therefore possible to neglect the other factors and to replace the m original (partially correlated) variables by a smaller set of independent variables. These variables can then be used in a regression analysis instead of the original ones (*orthogonalized regression*).

15.2.2 Programming

The following subroutines are available:

- **VecMean**(X, Lb, Ub, Nvar, M) computes the mean vector M[1..Nvar] from matrix X[Lb..Ub, 1..Nvar].
- **VecSD**(X, Lb, Ub, Nvar, M, S) computes the standard deviations S[1..Nvar] from matrix X and mean vector M.
- **ScaleVar**(X, Lb, Ub, Nvar, M, S, Z) computes the scaled variables Z[Lb..Ub, 1..Nvar] from the original variables X, the means M and the standard deviations S.
- **MatVarCov**(X, Lb, Ub, Nvar, M, V) computes the variance-covariance matrix V[1..Nvar, 1..Nvar] from matrix X and mean vector M.
- **MatCorrel**(V, Nvar, R) computes the correlation matrix R[1..Nvar, 1..Nvar] from the variance-covariance matrix V.
- **PCA**(R, Nvar, Lambda, C, Rc) performs the principal component analysis of the correlation matrix R, which is destroyed. The eigenvalues are returned in vector Lambda[1..Nvar], the eigenvectors in the columns of matrix C[1..Nvar, 1..Nvar]. The matrix Rc[1..Nvar, 1..Nvar] contains the correlation coefficients (loadings) between the original variables (rows) and the principal factors (columns).
- **PrinFac**(Z, Lb, Ub, Nvar, C, F) computes the principal factors (scores) F[Lb..Ub, 1..Nvar] from the scaled variables Z and the matrix of eigenvectors C.

After a call to these procedures, function **MathErr** returns one of the following error codes:

- **MatOk** if no error occurred
- **MatErrDim** if the array dimensions do not match
- **MatNonConv** if the iterative procedure (Jacobi method) did not converge in subroutine PCA

15.3 Demo programs

These programs are located in the `demo\curfit` subdirectory of the `TPMath` directory.

15.3.1 Multilinear regression

Program `regmult.pas` performs a multilinear least squares fit with `Nvar = 4` independent variables, according to the following equation:

$$Y = B(0) + B(1) * X1 + B(2) * X2 + B(3) * X3 + B(4) * X4$$

The data are stored in a matrix `X` and a vector `Y`.

The parameter vector and variance-covariance matrix are declared as:

```
DimVector(B, Nvar);  
DimMatrix(V, Nvar, Nvar);
```

The program calls procedure `MulFit` or `SVDFit`, then computes the theoretical `Y` values:

```
for I := 1 to N do  
  begin  
    if ConstTerm then Ycalc^[I] := B^[0] else Ycalc^[I] := 0.0;  
    for J := 1 to Nvar do  
      Ycalc^[I] := Ycalc^[I] + B^[J] * XX^[I]^[J];  
    end;
```

Note that this computation must be done before calling procedure `RegTest`

The critical values of Student's t and Snedecor's F are computed for the chosen probability `Alpha` by using the functions from chapter 5.

```
Tc := InvStudent(Test.Nu2, 1 - 0.5 * Alpha);  
Fc := InvSnedecor(Test.Nu1, Test.Nu2, 1 - Alpha);
```

where `Test.Nu1` and `Test.Nu2` are the numbers of d.o.f., returned by procedure `RegTest`.

The output shows the standardized residuals, equal to $(y_i - \hat{y}_i)/\sigma$, where σ is estimated by s_r . They should be distributed according to the standard normal distribution.

Due to the multi-dimensional nature of the relationship, a plot of y as a function of the x 's is not possible. Rather, the program plots a diagram of the observed and computed values of y , together with the theoretical line $\hat{y} = y$.

15.3.2 Polynomial regression

Program `regpoly.pas` performs a polynomial least squares fit. The structure of the program is very similar to the previous one, with the degree of the polynomial (`Deg`) playing the role of the number of variables (`Nvar`).

Here, only a vector `X` is needed to store the values of the independent variable, since the powers of x are computed by the polynomial regression routine `PolFit`.

The theoretical `Y` values are computed by means of function `Poly`, studied in chapter 9.

The program plots the fitted curve by calling the plotting subroutine `PlotFunc`. The function which is passed to this subroutine is defined as:

```
function PltFunc(X : Float) : Float;  
begin  
  PltFunc := Poly(X, B, Deg);  
end;
```

The definition of procedure `PlotFunc` does not allow additional parameters for `PltFunc`. This is the only reason why the parameter vector `B` is declared as a global variable.

15.3.3 Principal component analysis

Program `pcatest.pas` performs a principal component analysis on a set of 4 variables (Example taken from: P. DAGNELIE, *Analyse statistique à plusieurs variables*, Presses Agronomiques de Gembloux, Belgique, 1982). The program prints:

- The mean vector and variance-covariance matrix of the original variables
- The correlation coefficients between the original variables
- The eigenvalues and eigenvectors of the correlation matrix
- The correlation coefficients between the principal factors and the original variables
- The values of the principal factors for each point

It may be seen that:

- High correlations exist between the original variables, which are therefore not independent
- According to the eigenvalues, the last two principal factors may be neglected since they represent less than 11 % of the total variance. So, the original variables depend mainly on the first two factors
- The first principal factor is negatively correlated with the second and fourth variables, and positively correlated with the third variable
- The second principal factor is positively correlated with the first variable
- The table of principal factors show that the highest scores are usually associated with the first two principal factors, in agreement with the previous results

Chapter 16

Nonlinear regression

This chapter describes the routines available in **TPMath** for fitting models which are nonlinear with respect to their parameters. For instance, the exponential model $y = ae^{-bx}$ is nonlinear with respect to the parameter b .

16.1 Theory

The regression model is:

$$y = f(x; a, b \dots)$$

where f is a nonlinear function of the parameters $a, b \dots$

Assume that we have a first estimate $(a^0, b^0 \dots)$ of the parameters. Let us write the Taylor series expansion of y in the vicinity of this estimate:

$$y = y^0 + y'_a \cdot (a - a^0) + y'_b \cdot (b - b^0) + \dots$$

where:

$$\begin{aligned} y^0 &= f(x; a^0, b^0 \dots) \\ y'_a &= \frac{\partial f}{\partial a}(x; a^0, b^0 \dots) \\ y'_b &= \frac{\partial f}{\partial b}(x; a^0, b^0 \dots) \\ &\dots\dots\dots \end{aligned}$$

The equation may be rewritten as:

$$y - y^0 = y'_a \cdot (a - a^0) + y'_b \cdot (b - b^0) + \dots$$

which corresponds to the linear regression problem:

$$\mathbf{z} = \mathbf{J} \cdot \delta$$

with:

$$\mathbf{z} = \begin{bmatrix} y_1 - y_1^0 \\ y_2 - y_2^0 \\ \dots \\ y_n - y_n^0 \end{bmatrix} \quad \mathbf{J} = \begin{bmatrix} y'_{a1} & y'_{b1} & \dots \\ y'_{a2} & y'_{b2} & \dots \\ \dots & \dots & \dots \\ y'_{an} & y'_{bn} & \dots \end{bmatrix} \quad \delta = \begin{bmatrix} a - a^0 \\ b - b^0 \\ \dots \end{bmatrix}$$

where \mathbf{J} is the *Jacobian matrix*, such that $y'_{ai} = \partial f(x_i; a^0, b^0 \dots) / \partial a$ etc.

Application of the linear regression relationships leads to:

$$\delta = (\mathbf{J}^\top \mathbf{J})^{-1} (\mathbf{J}^\top \mathbf{z}) \quad (16.1)$$

Knowing the correction vector δ , it is possible to compute better estimates a and b of the parameters. The process is repeated until convergence of the parameter estimates.

The method so described is known as the *Gauss-Newton* method. It is usually combined with nonlinear optimization, usually Marquardt's method, in order to minimize the sum of squared residuals:

$$SS_r = \sum_{i=1}^n (y_i - \hat{y}_i)^2 = \Phi(a, b \dots)$$

In this case, the gradient vector \mathbf{g} and hessian matrix \mathbf{H} of function Φ are computed by the following relationships:

$$\mathbf{g} = -\mathbf{J}^\top \mathbf{z} \quad \mathbf{H} = \mathbf{J}^\top \mathbf{J} \quad (16.2)$$

so that the Gauss-Newton formula (16.1) becomes equivalent to the Newton-Raphson formula for nonlinear optimization (p. 53).

Note that, in the previous formula:

1. \mathbf{g} and \mathbf{H} are scaled by a factor 1/2 since this factor cancels during the computations.
2. The expression of \mathbf{H} is only approximate, since a factor containing the term $(y_i - \hat{y}_i)$ is neglected during the computation of the second partial derivatives:

$$\frac{\partial^2 \Phi}{\partial a \partial b} = \sum_{i=1}^n \left[\frac{\partial \hat{y}_i}{\partial a} \frac{\partial \hat{y}_i}{\partial b} - (y_i - \hat{y}_i) \frac{\partial^2 \hat{y}_i}{\partial a \partial b} \right]$$

The residual variance is:

$$V_r = \frac{SS_r}{n - p}$$

where p is the number of parameters in the model.

It is still possible to compute r^2 and F , as well as confidence intervals, but their interpretation is less straightforward since the ANOVA relationship (§ 14.1) does not hold for nonlinear models. In this case, r^2 may be > 1 ! Moreover, the distribution of the parameters is only approximately described by the Student distribution.

16.2 Monte-Carlo simulation

The distribution of the regression parameters may be simulated by the MCMC method discussed in § 12.2 (p. 87).

Let β denote the vector of model parameters. According to Bayes' theorem, the posterior probability density $\pi(\beta)$ of these parameters is given by:

$$\pi(\beta) = \frac{L(\beta)P(\beta)}{\int L(\beta)P(\beta)d\beta} = \frac{L(\beta)P(\beta)}{N}$$

where $P(\beta)$ denotes the prior probability density of the parameters and $L(\beta)$ denotes the likelihood, i.e. the probability of observing the experimental results (x_i, y_i) given the parameters.

The integral which appears in the denominator is usually too complex to be calculated and is therefore treated as a normalizing constant N .

Assuming that, for a given β , the residuals $(y_i - \hat{y}_i)$ are identically and independently distributed according to a normal distribution with variance σ^2 , the likelihood is given by:

$$L(\beta) = \prod_{i=1}^n \left(\frac{1}{\sigma\sqrt{2\pi}} \exp \left[-\frac{(y_i - \hat{y}_i)^2}{2\sigma^2} \right] \right)$$

If we choose a uniform prior probability $P(\beta)$ over an interval \mathcal{B} , the posterior probability becomes:

$$\pi(\beta) = C \prod_{i=1}^n \exp \left[-\frac{(y_i - \hat{y}_i)^2}{2\sigma^2} \right]$$

where C is a constant.

In order to use the Metropolis-Hastings algorithm, as described in chapter 12.2, we define the function:

$$F(\beta) = \begin{cases} -2 \ln \frac{\pi(\beta)}{C} = \sum_{i=1}^n (y_i - \hat{y}_i)^2 & \text{if } \beta \in \mathcal{B} \\ \infty & \text{otherwise} \end{cases} \quad (16.3)$$

It is the same objective function than for the nonlinear regression algorithm, except that it is bounded on the interval \mathcal{B} .

16.3 Regression procedures

16.3.1 Optimization methods

TPMath offers three deterministic optimizers: Marquardt, Simplex and BFGS (see chapter 7) and two stochastic optimizers: Simulated Annealing and Genetic Algorithm (see chapter 12)

The Marquardt method is selected by default. This selection can be changed with the statement `SetOptAlgo(Algo)` where `Algo` may have one of the following values:

<code>NL_MARQ</code>	for Marquardt
<code>NL_SIMP</code>	for Simplex
<code>NL_BFGS</code>	for BFGS
<code>NL_SA</code>	for Simulated Annealing
<code>NL_GA</code>	for Genetic Algorithm

The current algorithm is returned by function `GetOptAlgo`

16.3.2 Maximal number of parameters

By default, the maximal number of regression parameters is set to 10. This value may be changed with the statement `SetMaxParam(N)` where `N` is a number up to 255.

16.3.3 Parameter bounds

It is assumed that each regression parameter varies within an interval $[a, b]$. By default, this interval is set to $[-10^6, 10^6]$ which is way too large for most applications. It is possible to change this interval with the statement:

```
SetParamBounds(I, ParamMin, ParamMax)
```

where I is the index of the parameter and `ParamMin` and `ParamMax` are the bounds.

Defining realistic intervals for the parameters is essential when using stochastic optimizers.

16.3.4 Nonlinear regression

Nonlinear regression is performed by the two procedures:

- `NLFit(RegFunc, DerivProc, X, Y, Lb, Ub, MaxIter, Tol, B, FirstPar, LastPar, V)` for unweighted regression
- `WNLFit(RegFunc, DerivProc, X, Y, S, Lb, Ub, MaxIter, Tol, B, FirstPar, LastPar, V)` for weighted regression

where:

- `RegFunc` is the function to be fitted, defined as:

```
function RegFunc(X : Float; B : PVector) : Float;
```

where X is the independent variable and B the vector of regression parameters. This function is of type `TRegFunc`.

- `DerivProc` is the procedure used to compute the partial derivatives of the regression function with respect to the parameters. It is defined as:

```
procedure DerivProc(X, Y : Float; B, D : PVector);
```

where D is the vector of derivatives at point (X, Y) (one row of the Jacobian). This procedure is of type `TDerivProc`.

- $X[Lb..Ub]$, $Y[Lb..Ub]$ are the point coordinates and $S[Lb..Ub]$ are the standard deviations
- `MaxIter` is the maximum number of iterations for the optimization procedure
- `Tol` is the required precision for the regression parameters
- $B[FirstPar..LastPar]$ is the vector of fitted parameters
- $V[FirstPar..LastPar, FirstPar..LastPar]$ is the inverse matrix $(\mathbf{J}^T \mathbf{J})^{-1}$

16.3.5 Monte-Carlo simulation

The statistical distribution of the regression parameters is simulated by the following procedures:

- `SimFit(RegFunc, X, Y, Lb, Ub, B, FirstPar, LastPar, V)` for un-weighted regression
- `WSimFit(RegFunc, X, Y, S, Lb, Ub, B, FirstPar, LastPar, V)` for weighted regression

where the parameters have the same meaning than in the nonlinear regression procedures, except that here `V` is the variance-covariance matrix.

The results of the last simulation cycle are saved in an ASCII file. The name of this file may be defined by the statement `SetMCFile(FileName)`. The default file name is `mcmc.txt`

16.4 Demo programs

These programs are located in the `demo\curfit` subdirectory.

16.4.1 Nonlinear regression

Program `regnlin.pas` performs a nonlinear least squares fit of the exponential model:

$$y = ae^{-bx}$$

The partial derivatives used to compute the Jacobian are:

$$\frac{\partial y}{\partial a} = e^{-bx} \quad \frac{\partial y}{\partial b} = -axe^{-bx}$$

Initial estimates of the parameters `B` are obtained by linearization:

$$\ln y = \ln a - bx$$

However, this transformation modifies the standard deviations of the independent variables:

$$\sigma(\ln y) \approx d \ln y = \frac{dy}{y} \approx \frac{\sigma(y)}{y}$$

It is therefore recommended to use weighted linear regression for this step.

Subroutine **ApproxFit** selects the data points for which the transformation is appropriate (i. e. $y > 0$) and stores the transformed coordinates and their standard deviations in 3 vectors **X1**, **Y1**, **S1** which are passed to the weighted linear regression subroutine **WLinFit**. The fitted parameters are returned in vector **A**[0..1]. They are then transformed back to the original form of the model:

```
B^[1] := Exp(A^[0]);
B^[2] := - A^[1];
```

Marquardt's method is then used to perform nonlinear minimization of the residual sum of squares, by means of subroutine **NLFit**. Function **RegFunc** and procedure **DerivProc** are defined as follows:

```
function RegFunc(X : Float; B : PVector) : Float;
begin
  RegFunc := B^[1] * Exp(- B^[2] * X);
end;

procedure DerivProc(X, Y : Float; B, D : PVector);
begin
  D^[1] := Exp(- B^[2] * X);
  D^[2] := - B^[1] * X * D^[1];
end;
```

Since the parameter lists of these procedures cannot be modified, the other variables which they must access are made global.

The results of the minimization are printed as with the linear regression programs, except that the correlation coefficients are shown only if $r \leq 1$.

The program may be adapted to another regression model by changing the following parts:

- the function name (constant **FuncName**)
- the constants **FirstPar** and **LastPar** which define the bounds of the parameter array **B**
- the subroutine **ApproxFit** which computes the initial estimates of the parameters
- the definition of the regression model in function **RegFunc**
- the definition of derivatives in subroutine **DerivProc**

16.4.2 Monte-Carlo simulation

Program `mcsim.pas` simulates the posterior distribution of the regression parameters for the previous exponential model.

The settings for the MCMC procedure are defined as follows:

```
const
  NCycles = 10;           { Number of cycles }
  MaxSim   = 1000;        { Max nb of simulations at each cycle }
  SavedSim = 1000;        { Nb of simulations to be saved }
  MCFile   = 'mcsim.txt'; { File for storing simulation results }
```

The algorithm is initialized with:

```
InitMHPParams(NCycles, MaxSim, SavedSim);
SetMCFile(MCFile);
```

Proper intervals are defined for the two parameters:

```
SetParamBounds(1, 100, 1000);
SetParamBounds(2, 0.1, 1);
```

The `SimFit` procedure is then called. After the computation is done, the program plots a graph showing the distribution of the parameters.

Chapter 17

Library of nonlinear regression models

TPMath has a set of predefined nonlinear regression models which can be fitted just like the polynomial or multilinear models.

At this time, the following models are implemented:

- Rational fractions
- Sums of exponentials
- Increasing exponential
- Exponential + linear
- Logistic equations
- Power function
- Gamma distribution
- Michaelis equation
- Integrated Michaelis equation
- Hill equation
- Acid-base titration curve

17.1 Common features

17.1.1 Procedures

For each model, two fitting procedures are provided, for unweighted and weighted regression:

- `<model>Fit(X, Y, Lb, Ub, [...], MaxIter, Tol, B, V)`
- `W<model>Fit(X, Y, S, Lb, Ub, [...], MaxIter, Tol, B, V)`

where:

- `<model>` stands for model name
- `X[Lb..Ub]`, `Y[Lb..Ub]` are the point coordinates and `S[Lb..Ub]` are the standard deviations
- `[...]` stands for the additional parameters required by some models
- `MaxIter` is the maximum number of iterations for the optimization procedure
- `Tol` is the required precision for the regression parameters
- `B` is the vector of fitted parameters
- `V` is the inverse matrix

In addition, there exists a function `<model>Fit_Func(X, B)` which returns the value of the fitted function at point `X`, given the parameters `B`. This function should be called *after* the model has been fitted.

17.1.2 Optimization methods and initial parameters

As with the general nonlinear regression procedures studied in the previous chapter, the specific procedures can use the three local optimizers (Marquardt, BFGS, simplex) and the two global ones (simulated annealing and genetic algorithm), according to the choice performed by procedure `SetOptAlgo`.

Moreover, the maximal number of regression parameters and their bounds can still be modified by using procedures `SetMaxParam` and `SetParamBounds`, as described in the previous chapter.

If a local optimizer is selected, the fitting procedure will look at the current values of the regression parameters **B**. If *all* these values are non-zero, they will be used to start the algorithm. Otherwise, a built-in specific procedure will be called to generate approximate starting values (most often, using a linearized form of the model).

If a global optimizer is selected, the initial parameters will be randomly chosen within the parameter bounds.

17.2 Regression models

17.2.1 Rational fractions

The model has the form:

$$y = \frac{p_0 + p_1x + p_2x^2 + \cdots + p_{d_1}x^{d_1}}{1 + q_1x + q_2x^2 + \cdots + q_{d_2}x^{d_2}}$$

The fitted parameters are:

$$B_0 = p_0 \quad B_1 = p_1 \quad B_2 = p_2 \quad \cdots \quad B_{d_1} = p_{d_1}$$

$$B_{d_1+1} = q_1 \quad B_{d_1+2} = q_2 \quad \cdots \quad B_{d_1+d_2} = q_{d_2}$$

where d_1 and d_2 are the degrees of the numerator and denominator, respectively.

The fitting procedures are:

- `FracFit(X, Y, Lb, Ub, Deg1, Deg2, ConsTerm, MaxIter, Tol, B, V)`
- `WFracFit(X, Y, S, Lb, Ub, Deg1, Deg2, ConsTerm, MaxIter, Tol, B, V)`

where **Deg1**, **Deg2** are the degrees of the numerator and denominator, and **ConsTerm** is a boolean indicator which flags the presence of the constant term p_0 .

The regression function is `FracFit.Func(X, B)`

17.2.2 Sums of exponentials

The model has the form:

$$y = Y_0 + A_1 e^{-a_1 x} + A_2 e^{-a_2 x} + \dots$$

The fitted parameters are:

$$B_0 = Y_0$$

$$B_1 = A_1 \quad B_2 = a_1$$

.....

$$B_{2i-1} = A_i \quad B_{2i} = a_i \quad i = 1..N_{exp}$$

where N_{exp} is the number of exponentials.

The fitting procedures are:

- ExpFit(X, Y, Lb, Ub, Nexp, ConstTerm, MaxIter, Tol, B, V)
- WExpFit(X, Y, S, Lb, Ub, Nexp, ConstTerm, MaxIter, Tol, B, V)

where \mathbf{Nexp} is the number of exponentials, and $\mathbf{ConstTerm}$ is a boolean indicator which flags the presence of the constant term Y_0 .

The regression function is `ExpFit_Func(X, B)`

17.2.3 Increasing exponential

The model has the form:

$$y = Y_{min} + A(1 - e^{-kx})$$

The fitted parameters are:

$$B_0 = Y_{min} \quad B_1 = A \quad B_2 = k$$

The fitting procedures are:

- IncExpFit(X, Y, Lb, Ub, ConstTerm, MaxIter, Tol, B, V)
- WIncExpFit(X, Y, S, Lb, Ub, ConstTerm, MaxIter, Tol, B, V)

where **ConsTerm** is a boolean indicator which flags the presence of the constant term Y_{min} .

The regression function is IncExpFit_Func(X, B)

17.2.4 Exponential + Linear

The model has the form:

$$y = A(1 - e^{-kx}) + Bx$$

The fitted parameters are:

$$B_0 = A \quad B_1 = k \quad B_2 = B$$

The fitting procedures are:

- `ExpLinFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)`
- `WExpLinFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)`

The regression function is `ExpLinFit_Func(X, B)`

17.2.5 Logistic functions

The model has the form:

$$y = A + \frac{B - A}{1 - e^{-ax+b}}$$

The fitted parameters are:

$$B_0 = A \quad B_1 = B \quad B_2 = a \quad B_3 = b$$

The generalized logistic function has the form:

$$y = A + \frac{B - A}{(1 - e^{-ax+b})^n}$$

with the additional parameter $B_4 = n$

The fitting procedures are:

- `LogiFit(X, Y, Lb, Ub, ConstTerm, General, MaxIter, Tol, B, V)`
- `WLogiFit(X, Y, S, Lb, Ub, ConstTerm, General, MaxIter, Tol, B, V)`

where `ConstTerm` is a boolean indicator which flags the presence of the constant term A , and `General` is a boolean indicator which selects the generalized logistic.

The regression function is `LogiFit_Func(X, B)`

17.2.6 Power function

The model has the form:

$$y = Ax^n$$

The fitted parameters are:

$$B_0 = A \quad B_1 = n$$

The fitting procedures are:

- `PowFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)`
- `WPowFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)`

The regression function is `PowFit_Func(X, B)`

17.2.7 Gamma distribution

The model has the form:

$$y = a(x - b)^c \exp \left[-\frac{x - b}{d} \right]$$

The fitted parameters are:

$$B_1 = a \quad B_2 = b \quad B_3 = c \quad B_4 = d$$

The fitting procedures are:

- `GammaFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)`
- `WGammaFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)`

The regression function is `GammaFit_Func(X, B)`

17.2.8 Michaelis equation

The model has the form:

$$y = \frac{Y_{max}x}{K_m + x}$$

The fitted parameters are:

$$B_0 = Y_{max} \quad B_1 = K_m$$

where K_m is the Michaelis constant.

This equation is widely used in enzyme kinetics, with x being the substrate concentration and y the reaction rate. Therefore, Y_{max} is the maximal velocity, such that $Y_{max} = k_{cat}e_0$ where k_{cat} is the catalytic constant and e_0 the total enzyme concentration.

The fitting procedures are:

- `MichFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)`
- `WMichFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)`

The regression function is `MichFit.Func(X, B)`

17.2.9 Integrated Michaelis equation

The integrated Michaelis equation is the solution to the differential equation:

$$\frac{dp}{dt} = \frac{Y_{max}(s_0 - p)}{K_m + s_0 - p}$$

with the initial condition: $p = 0$ at $t = 0$.

It is also used in enzyme kinetics, with p being the product concentration at time t and s_0 the initial substrate concentration.

The solution is expressed in terms of Lambert's W-function, studied in chapter 4:

$$p = s_0 - K_m W \left[\frac{s_0}{K_m} \exp \left(\frac{s_0 - k_{cat}e_0 t}{K_m} \right) \right]$$

The independent variable may be t , s_0 or e_0 .

The fitting procedures are:

- `MintFit(X, Y, Lb, Ub, MintVar, Fit_S0, MaxIter, Tol, B, V)`

- `WMintFit(X, Y, S, Lb, Ub, MintVar, Fit_S0, MaxIter, Tol, B, V)`

where:

- `MintVar` denotes the independent variable (may be `Var_T`, `Var_S` or `Var_E`)
- `Fit_S0` indicates if s_0 must be fitted (for `Var_T` or `Var_E` only)

So, the fitted parameters are as follows:

Indep. var.	MintVar	B_0	B_1	B_2
t	<code>Var_T</code>	s_0	K_m	Y_{max}
s_0	<code>Var_S</code>		K_m	$Y_{max}t$
e_0	<code>Var_E</code>	s_0	K_m	$k_{cat}t$

The regression function is `MintFit_Func(X, B)`

17.2.10 Hill equation

The Hill equation can be viewed as an extension of the Michaelis equation:

$$y = \frac{Y_{max}x^n}{K + x^n}$$

The fitted parameters are:

$$B_0 = Y_{max} \quad B_1 = K \quad B_2 = n$$

The fitting procedures are:

- `HillFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)`
- `WHillFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)`

The regression function is `HillFit_Func(X, B)`

17.2.11 Acid-base titration curve

The model has the form:

$$y = A + \frac{B - A}{1 - 10^{pK_a - x}}$$

The fitted parameters are:

$$B_0 = A \quad B_1 = B \quad B_2 = pK_a$$

It is used in chemistry, where x is the pH, y is some property (e.g. absorbance) which depends on the ratio of the acidic and basic forms of a compound, A is the property for the pure acidic form, B is the property for the pure basic form and pK_a is the acidity constant.

The fitting procedures are:

- PKFit(X, Y, Lb, Ub, MaxIter, Tol, B, V)
- WPKFit(X, Y, S, Lb, Ub, MaxIter, Tol, B, V)

The regression function is PKFit.Func(X, B)

17.3 Demo programs

17.3.1 Examples

There are several programs in the `demo\regmodel` subdirectory:

Program	Model	Data files	Ref.
<code>regfrac.pas</code>	Rational fraction	<code>frac.dat</code>	(¹)
<code>regexpo.pas</code>	Sum of exponentials	<code>iv2.dat</code>	(²)
		<code>oral1.dat</code>	(²)
		<code>oral2.dat</code>	(²)
<code>regiexpo.pas</code>	Increasing exponential	<code>iexpo.dat</code>	(¹)
<code>regexlin.pas</code>	Exponential + linear	<code>exlin.dat</code>	(¹)
<code>reglogi.pas</code>	Logistic function	<code>logist.dat</code>	(³)
<code>regmich.pas</code>	Michaelis equation	<code>michael.dat</code>	(¹)
<code>regmint.pas</code>	Integrated Michaelis equation	<code>michint.dat</code>	(¹)
<code>reghill.pas</code>	Hill equation	<code>hill.dat</code>	(¹)

The data were taken from the following references:

1. Enzyme kinetic data from the author's laboratory
2. Pharmacokinetic data from M. GIBALDI & D. PERRIER, Pharmacokinetics, 2nd edition, Dekker 1982
3. Biochemical data from S. HUET *et al.*, Statistical Tools for Nonlinear Regression, Springer 1996

Each program reads the data file, then sets the indices of the parameters, the maximal number of regression parameters and the parameter bounds. For instance, for the rational fraction:

```
if ConstTerm then FirstPar := 0 else FirstPar := 1;
LastPar := Deg1 + Deg2;

SetMaxParam(LastPar);

for I := 0 to LastPar do
  SetParamBounds(I, -1000, 1000);
```

where `FirstPar` and `LastPar` are the indices of the first and last regression parameters.

The program then fits the model and plots the resulting curve.

17.3.2 Validation program

Program `nist.pas`, located in the `demo\nist` subdirectory, performs a validation of some of the regression routines in `TPMath` by using reference data from the NIST (National Institute of Standards and Technology, <http://www.itl.nist.gov/div898/strd/general/dataarchive.html>).

The best results are obtained in extended precision. For this reason, the program links to the individual units rather than to the whole library (since the library is compiled in double precision by default).

The program uses an independent unit, `umodels.pas` which defines the regression models and calls the appropriate regression routines.

For each model, the precision of the fit is estimated, for each fitted parameter, by computing the relative difference ϵ_i between the value found by the program and the reference value given by the NIST. The highest relative difference $\epsilon_{max} = \max(|\epsilon_i|)$ is then selected to compute the precision as $p = -\log_{10} \epsilon_{max}$, which corresponds approximately to the number of correct

digits found by the program. A plot of the precision obtained for the different models is displayed.

According to the NIST, a precision of at least 4 digits is acceptable. In our tests, precisions ranging from 4 to 14 digits were obtained by selecting the algorithms as follows:

- for multilinear and polynomial regressions, the Singular Value Decomposition (SVD) algorithm was used, with a threshold for the singular values set at $N * \text{MachEp}$ where N is the number of points (see paragraph 6.9 for details).
- for nonlinear regression, the Simplex algorithm was applied first, followed by Marquardt's method. The initial values of the parameters were computed by the built-in `TPMath` routines. The tolerance for the fitted parameters was the same than for SVD.

The results are saved in a file `nist.out`. For each model, the relative difference (ϵ_i) is computed for:

- the regression parameters b_i
- their standard deviations s_i
- the residual standard deviation s_r
- the coefficient of determination r^2
- the variance ratio F

Note that reference values for the last two tests are not available for all models.

Chapter 18

String functions

Some string functions have been added to TPMath, mainly to help printing results.

18.1 Trim functions

- function `LTrim(S)` removes the leading blanks in string `S`
- function `RTrim(S)` removes the trailing blanks in string `S`
- function `Trim(S)` removes the leading and trailing blanks in string `S`

18.2 Fill functions

- function `RFill(S, L)` returns string `S` completed with trailing blanks for a total length `L`
- function `LFill(S, L)` returns string `S` completed with leading blanks for a total length `L`
- function `CFill(S, L)` returns string `S` completed with leading blanks so as to center the string on a total length `L`
- function `StrChar(N, C)` returns a string made of character `C` repeated `N` times

18.3 Character replacement

Subroutine `Replace(S, C1, C2)` replaces in string `S` all the occurrences of character `C1` by character `C2`

18.4 Parsing

- function `Extract(S, Index, Delim)` extracts a field from string `S`. `Index` is the position of the first character of the field. `Delim` is the character used to separate fields (e.g. blank, comma or tabulation). Blanks immediately following `Delim` are ignored. `Index` is updated to the position of the next field.
- procedure `Parse(S, Delim, Field, N)` parses string `S` into its constitutive fields. `Delim` is the field separator. The number of fields is returned in `N`. The fields are returned in `Field[0]..Field[N - 1]`. `Field` must be dimensioned in the calling program.

18.5 Formatting functions

These functions allow to convert numbers to strings.

- procedure `SetFormat(NumLength, MaxDec, FloatPoint, NSZero)` defines the numeric format, according to the following parameters:
 - `NumLength` : Length of numeric field (default 10)
 - `MaxDec` : Max. number of decimal places (default 4)
 - `FloatPoint` : Select floating point notation (default `False`)
 - `NSZero` : Write non significant zero's (default `True`)
- function `FloatStr(X)` converts the real number `X` to a string according to the numeric format specified by `SetFormat`
- function `IntStr(N)` converts the integer `N` to a string.
- function `CompStr(Z : Complex)` converts the complex number `Z` to a string.

Chapter 19

Graphic functions

19.1 Introduction

TPMath provides some graphic routines to help plotting curves. They are available in three versions :

- a BGI version, based on Borland's Graph unit. It can be used with TP, FPC or GPC.

The BGI drivers and fonts are not distributed with TPMath. They must be obtained from one of the Borland compilers which are freely available on the Internet, for instance Turbo Pascal 7 : <http://pascal.developpez.com/compileurs/tp7/>

- a Delphi version
- a \LaTeX version, which uses the `pstricks` extension to allow the creation of PostScript files.

According to the compiler, the library will contain either the BGI or Delphi version, along with the \LaTeX version.

19.2 BGI graphics

19.2.1 Initializing graphics

- Function `InitGraphics(Pilot, Mode, BGIPath)` will place the computer in the graphic mode defined by the parameters `Pilot` (which corresponds to the graphic driver) and `Mode`. `BGIPath` is a string defining the directory in which the BGI drivers and fonts are stored.

The function returns `True` if the initialization is successful.

Example : `InitGraphics(9, 2, 'C:\TP\BGI')` will select the VGA mode, 640×480 resolution with 16 colors (see the documentation of the Graph unit for a list of available modes).

- Procedure `SetWindow(X1, X2, Y1, Y2, GraphBorder)` defines the size of the graphic window.

`X1, X2, Y1, Y2` are the window coordinates in %

`GraphBorder` is a boolean parameter which must be set to `True` for plotting a border around the window.

This function must be called *after* `InitGraphics`

Example : `SetWindow(15, 85, 15, 85, True)`

19.2.2 Coordinate axes

TPMath allows to plot curves in either linear or logarithmic coordinates. The type of scale may be selected by using the predefined symbols `LinScale` or `LogScale`

For each axis, the scale is specified by:

- `SetOxScale(Scale, OxMin, OxMax, OxStep)`
- `SetOyScale(Scale, OyMin, OyMax, OyStep)`

where `Scale` may be either `LinScale` or `LogScale`, and the other parameters define the bounds and step on the axis.

Default values are: linear scale from 0 to 1 with a step of 0.2. These values will be used automatically if the calls to `SetOxScale` or `SetOyScale` are omitted.

An automatic scale, suitable for plotting all the values in an array `X[Lb..Ub]`, may be determined by:

`AutoScale(X, Lb, Ub, Scale, XMin, XMax, XStep)`

where `Scale` defines the type of scale. The results are returned in `XMin`, `XMax`, `XStep`.

Note that, for a logarithmic scale, the bounds must be powers of 10 and the step is always 10.

Once the scales have been specified, the axes may be plotted with the statements `PlotOxAxis` and `PlotOyAxis`.

In addition, a grid may be plotted with `PlotGrid(Grid)` where `Grid` may be: `HorizGrid` (horizontal lines only), `VertiGrid` (vertical lines only) or `BothGrid` (horizontal and vertical lines).

The current scale parameters can be retrieved for each axis with the procedures:

- `GetOxScale(Scale, OxMin, OxMax, OxStep)`
- `GetOyScale(Scale, OyMin, OyMax, OyStep)`

19.2.3 Titles and fonts

The default titles are 'X' and 'Y' for the axes, and none for the main graph. This may be changed with the statements:

- `SetOxTitle(Title)`
- `SetOyTitle(Title)`
- `SetGraphTitle(Title)`

where `Title` is the relevant string.

The current titles are returned by the corresponding functions: `GetOxTitle`, `GetOyTitle`, `GetGraphTitle`.

The fonts used to print the titles and axis labels are the BGI fonts (*.chr files). The default font is the small font. It can be changed with the following procedures:

<code>SetTitleFont(FontIndex, Width, Height)</code>	for main graph
<code>SetOxFont(FontIndex, Width, Height)</code>	for Ox axis
<code>SetOyFont(FontIndex, Width, Height)</code>	for Oy axis
<code>SetLgdFont(FontIndex, Width, Height)</code>	for curve legends

`FontIndex` is the index of the font, as specified by the Graph unit (e. g. 2 for the small font). `Width` and `Height` define the font size. In the case of the axes, these settings will affect both the titles and labels.

Plotting the axes will automatically print the titles and labels. For the main graph title, the statement `WriteGraphTitle` should be used.

19.2.4 Clipping

Procedure **SetClipping(Clip)**, where **Clip** is a boolean parameter, is used to decide if the subsequent graphics will be clipped to the boundaries of the current viewport (defined by **SetWindows**).

19.2.5 Curves

Curve properties

Each curve is comprised of:

- a set of points, defined by their coordinates (x_i, y_i)
- a line connecting the points

It is possible to plot the points only, the line only, or both.

The points have the following properties:

- **Symbol** : index of the symbol to be plotted, according to the following convention:
 - 0 : point (1 pixel)
 - 1 : solid circle
 - 2 : open circle
 - 3 : solid square
 - 4 : open square
 - 5 : solid triangle
 - 6 : open triangle
 - 7 : plus (+)
 - 8 : multiply (\times)
 - 9 : star (*)
- **Size** : size in pixels (will have no effect if **Symbol** = 0)
- **Color** : index of color, according to the current palette

The lines have the following properties:

- **Style** : line style, according to the Graph unit

- 0 : none
- 1 : solid
- 2 : dotted
- 3 : centered
- 4 : dashed

- **Width** : line width, according to the Graph unit

- 1 : normal
- 3 : thick

- **Color** : index of color

The curves have two additional properties :

- a legend (30 characters max.)
- a step, which defines how many points will be plotted (plot 1 point every step points)

By default, 9 curves may be plotted, with the following default parameters:

- symbol = index of curve
- point size = 2
- line style = 1 (solid)
- line width = 1 (normal)
- legend = 'Y1', 'Y2', ...
- step = 1
- color set for a 16-color palette (VGA mode)

Curve index	Color index	Color
1	12	LightRed
2	14	Yellow
3	10	LightGreen
4	9	LightBlue
5	11	LightCyan
6	13	LightMagenta
7	4	Red
8	2	Green
9	1	Blue

The maximal number of curves may be changed with `SetMaxCurv(NCurv)` where `NCurv` is a number between 1 and 255. The current number of curves is returned by function `GetMaxCurv`.

The settings for the curve `CurvIndex` may be changed with the following procedures:

- `SetPointParam(CurvIndex, Symbol, Size, Color)`
- `SetLineParam(CurvIndex, Style, Width, Color)`
- `SetCurvLegend(CurvIndex, Legend)`
- `SetCurvStep(CurvIndex, Step)`

The current settings are retrieved by the two procedures:

- `GetPointParam(CurvIndex, Symbol, Size, Color)`
- `GetLineParam(CurvIndex, Style, Width, Color)`

and the two functions:

- `GetCurvLegend(CurvIndex)`
- `GetCurvStep(CurvIndex)`

Plotting curves

- Procedure `PlotCurve(X, Y, Lb, Ub, CurvIndex)` plots a curve defined by the point coordinates `X[Lb..Ub]`, `Y[Lb..Ub]`, according to the parameters of curve `#CurvIndex`. The coordinates are expressed in user units (not in pixels).
- `PlotCurveWithErrorBars(X, Y, S, Ns, Lb, Ub, CurvIndex)` plots the curve and adds a vertical error bar to each point. The individual errors (usually expressed as standard deviations) are stored in vector `S[Lb..Ub]`. `Ns` is an integer such that the total height of the bar is $2 * Ns * S[I]$ (e. g. set `Ns` to 3 for plotting 6 standard deviations).
- Procedure `PlotPoint(Xp, Yp, CurvIndex)` plots a single point. Here the coordinates `Xp`, `Yp` must be in **pixels**. This procedure is mainly used internally by the two previous ones.

19.2.6 Function plot

Procedure `PlotFunc(Func, X1, X2, CurvIndex)` plots the graph of function `Func` from `X1` to `X2` according to the parameters of curve `#CurvIndex`.

`Func` is of type `TFunc` and is declared as:

```
function Func(X : Float) : Float;
```

19.2.7 Legends

Procedure `WriteLegend(NCurv, ShowPoints, ShowLines)` draws a box at the right side of the screen, with the legends of the plotted curves. `NCurv` is the number of curves. `ShowPoints` and `ShowLines` are boolean parameters selecting which symbols are displayed to identify the curves.

19.2.8 Contour plots

Procedure `ConRec(Nx, Ny, Nc, X, Y, Z, F)` generates a contour plot of a two-dimensional function $f(x, y)$. The algorithm is adapted from Paul Bourke (<http://astronomy.swin.edu.au/~pbourke/projection/conrec/>)

`Nx` and `Ny` are the number of steps on `Ox` and `Oy`. `Nc` is the number of contour levels. The point coordinates (in pixels) are stored in vectors `X[0..Nx]` and `Y[0..Ny]`. The contour levels (in increasing order) are stored in vector `Z[0..(Nc - 1)]`. The function values are stored in matrix `F[0..Nx, 0..Ny]`, such that `F[I, J]` is the function value at point `(X[I], Y[J])`.

19.2.9 Coordinate conversion

Functions `Xpixel(X)` and `Ypixel(Y)` convert the user coordinates `X` and `Y` to the corresponding screen coordinates (pixels). Functions `Xuser(X)` and `Yuser(Y)` do the inverse.

19.2.10 Leaving graphics

Procedure `LeaveGraphics` quits the graphic mode and returns to the text mode.

19.3 Delphi graphics

In this section we will present the Delphi graphics with respect to their BGI counterparts. The main difference is the presence, in some functions, of an additional parameter `Canvas` which denotes the component on which the graphic is drawn. When present, this parameter is always the first one.

19.3.1 Initializing graphics

- Function `InitGraphics(Width, Height)` enters graphic mode. The parameters `Width` and `Height` refer to the canvas on which the graphic is plotted.

Examples:

- To draw on a `TImage` object:

```
InitGraph(Image1.Width, Image1.Height)
```

- To print the graphic:

```
InitGraph(Printer.PageWidth, Printer.PageHeight)
```

The function returns `True` if the initialization is successful.

- Procedure `SetWindow` behaves as its BGI equivalent, except for the additional parameter `Canvas`.

Example : `SetWindow(Image1.Canvas, 15, 85, 15, 85, True)`

19.3.2 Coordinate axes

- Procedures `AutoScale`, `SetOxScale`, `SetOyScale`, `GetOxScale`, `GetOyScale` are identical to their BGI counterparts.
- Procedures `PlotOxAxis`, `PlotOyAxis`, `PlotGrid` have the additional parameter `Canvas`.

19.3.3 Titles and fonts

- The fonts are specified by the property of the canvas. Hence, there is no need for specific functions in `tpmath` to change them.
- Procedures `SetGraphTitle`, `SetOxTitle`, `SetOyTitle` and their corresponding functions `GetGraphTitle`, `GetOxTitle`, `GetOyTitle` are identical to their BGI counterparts.
- Procedure `WriteGraphTitle` has the additional parameter `Canvas`.

19.3.4 Curves

- The curves have the same properties than in the BGI version, except that `Style` is of type `TPenStyle` and `Color` is of type `TColor`.

The default colors are as follows:

Curve index	Color
1	clRed
2	clGreen
3	clBlue
4	clFuchsia
5	clAqua
6	clLime
7	clNavy
8	clOlive
9	clPurple

- Procedures `SetMaxCurv`, `SetCurvLegend`, `SetCurvStep` and their corresponding functions `GetMaxCurv`, `GetCurvLegend`, `GetCurvStep` are identical to their BGI counterparts.
- Procedures `SetPointParam`, `SetLineParam`, `GetPointParam`, `GetLineParam` are identical to their BGI counterparts, except for the types of parameters `Style` and `Color`.

- Procedures `PlotCurve` and `PlotCurveWithErrorBars` have the additional parameter `Canvas`.
- Procedure `PlotPoint` has the additional parameter `Canvas`. Moreover, the point coordinates must be specified in user units instead of pixels.

19.3.5 Other functions

- Procedure `PlotFunc(Canvas, Func, Xmin, Xmax, Npt, CurvIndex)` has a specific parameter `Npt` which denotes the number of points to be plotted.
- Procedures `WriteLegend` and `ConRec` have the additional parameter `Canvas`.
- Functions `Xpixel`, `Ypixel`, `Xuser`, `Yuser`, as well as procedure `LeaveGraphics`, are identical to their BGI counterparts.

19.4 L^AT_EX graphics

Most graphic statements have a L^AT_EX counterpart with a name beginning with ‘TeX’, e.g. `TeX_InitGraphics`.

However, colors and fonts are not handled at this time. So, the resulting plot will be black and white and all labels will be printed with the default font.

19.4.1 Initializing graphics

- Function `TeX_InitGraphics(FileName, PgWidth, PgHeight, Header)` initializes the L^AT_EX file.
 - `FileName` is the name of the L^AT_EX file (e. g. ‘figure.tex’)
 - `PgWidth`, `PgHeight` are the dimensions of the graphic area in cm
 - `Header` is a boolean parameter which allows to create a new file and write the following preamble:

```
\documentclass[12pt,a4paper]{article}
\usepackage{pst-plot}
\pagestyle{empty}
\begin{document}
```

If `Header` is `False`, no preamble will be written.

Symmetrically, the statement `TeX_LeaveGraphics` has a boolean parameter `Footer` which allows to print the `\end{document}` section and close the file.

So, you can place several plots in a single document by calling the two procedures with the relevant boolean parameters. For instance, the following sequence will place two plots on the same page:

```
{ Create new file and write preamble }
if TeX_InitGraphics('figure.tex', 15, 10, True) then
  begin
    TeX_SetWindow(10, 90, 10, 90, True);
    .....

    (* Close file but don't write the '\end{document}' section *)
    TeX_LeaveGraphics(False);
  end;

{ Append to existing file and don't write preamble }
if TeX_InitGraphics('figure.tex', 15, 10, False) then
  begin
    TeX_SetWindow(10, 90, 10, 90, True);
    .....

    (* Close file and write the '\end{document}' section *)
    TeX_LeaveGraphics(True);
  end;
```

- Procedure `TeX_SetWindow` behaves as its BGI equivalent.

19.4.2 Axes and titles

The following procedures behave as their BGI equivalents:

- `TeX_SetOxScale`
- `TeX_SetOyScale`
- `TeX_SetGraphTitle`
- `TeX_SetOxTitle`

- `TeX_SetOyTitle`
- `TeX_PlotOxAxis`
- `TeX_PlotOyAxis`
- `TeX_PlotGrid`
- `TeX_WriteGraphTitle`

19.4.3 Curves

- The curves have the same properties than in the BGI version, except that:
 - there is no `Color` parameter;
 - there is an additional boolean property `Smooth` which indicates if the curve must be smoothed.

These properties are set with the following procedures:

- `TeX_SetPointParam(CurvIndex, Symbol, Size)`
- `TeX_SetLineParam(CurvIndex, Style, Width, Smooth)`
- The following procedures behave as their BGI equivalents:
 - `TeX_SetMaxCurv`
 - `TeX_SetCurvLegend`
 - `TeX_SetCurvStep`
 - `TeX_PlotCurve`
 - `TeX_PlotCurveWithErrorBars`
 - `TeX_WriteLegend`
 - `TeX_ConRec`
- Procedure `TeX_PlotFunc(Func, X1, X2, Npt, CurvIndex)` has an additional parameter `Npt` which denotes the number of points to be plotted.

19.4.4 Other functions

Functions `Xcm(X)` and `Ycm(Y)` convert the user coordinates `X` and `Y` to their equivalent in cm.

19.5 Demo programs

19.5.1 BGI programs

The following programs are provided for BGI graphics. Most of them have already been described in the previous chapters.

Directory	Program	Description	Chapter
demo\curfit	*.pas	Curve fit	14-16
demo\fmath	contour.pas plot.pas	Contour plot Function plot	
demo\fourier	testfft.pas	Fast Fourier Transform	11
demo\nist	nist.pas	Validation of curve-fitting routines	17
demo\regmodel	*.pas	Library of regression models	17
demo\stat	histo.pas	Histogram	13

19.5.2 Delphi programs

These programs are in the `demo\delphi` directory. To avoid possible bugs, they are linked to the individual units instead of the DLL.

Function plotter

Program `fplot.dpr` (in `demo\delphi\fplot`) allows to plot most of the elementary or special functions defined in `TPMath`.

Quadratic iterator

Program `quadrit.dpr` (in `demo\delphi\quadrit`) demonstrates a chaotic system: the quadratic iterator.

The system is defined by the relationship:

$$x_{n+1} = ax_n(1 - x_n)$$

According to the value of a the sequence may be:

- periodic (e.g. for $a = 3.5$ the period is 4)
- chaotic (e.g. $a = 4$)
- presenting an alternance of periodic and chaotic phases, a phenomenon known as *intermittency* (e.g. $a = 3.82812$)

The program can plot two types of diagrams:

- an *orbit diagram*, in which the value of x_n is plotted vs. n
- a *bifurcation diagram*, in which the values of x_n are plotted for each value of a (after an initial run of 200 iterations). The bifurcation diagram shows the progressive transition from order to chaos via a period-doubling route as a increases. It also shows the existence of periodic regions inside the chaotic domain. Magnifying these regions reveals a structure similar to the whole plot (i.e. the fractal nature of the bifurcation diagram).

For more information about the quadratic iterator and other chaotic systems, see *The Chaos Hypertextbook* by Glenn Elert (<http://hypertextbook.com/chaos/>).

19.5.3 L^AT_EX program

Program `texdemo.pas`, placed in the `demo\fmath` directory, creates a L^AT_EX file `figure.tex` which plots a Fourier series:

$$F_1 = 0.75(1 + \cos \phi)$$

$$F_2 = 2.5[1 + \cos(2\phi - \pi)]$$

$$F_3 = F_1 + F_2$$

(This function is used in chemistry to describe the torsional energy of an amide bond.)

The resulting file must be processed with `latex`. The graphics can be converted to PostScript by the `dvips` utility:

```
latex figure
dvips figure
```

Chapter 20

Expression evaluation

TPMath provides a math parser for evaluating expressions at run time. The expression is a character string which may contain numbers, operators, parentheses, variables and functions as described below.

20.1 Numbers

Integers (32-bit, signed) and reals (Float type) must be entered in decimal. The exponential notation (e. g. 6.62E-34) is not accepted. You must write `6.62 * 10^(- 34)`.

20.2 Operators

+	addition, unary plus
-	subtraction, unary minus
*	multiplication
/	division
\	integer division
%	modulus operator
^	exponentiation
>	shift bit right
<	shift bit left
&	bitwise AND
	bitwise OR
\$	bitwise XOR
!	bitwise NOT
@	bitwise IMP
=	bitwise EQV

Operator precedence

!	bitwise NOT (highest precedence, evaluated first)
&	bitwise AND
	bitwise OR
\$	bitwise XOR
=	bitwise EQV
@	bitwise IMP
^	exponentiation
+ -	unary plus, unary minus
* /	multiplication, division
\	integer division
%	modulus operator
<>	shift bit left, shift bit right
+ -	addition, subtraction (lowest precedence, evaluated last)

20.3 Parentheses

Parentheses can be used to override operator precedence, but within parentheses operator precedence is used.

20.4 Variables

There are 26 variables from A to Z

20.5 Functions

Function arguments must be enclosed within parentheses. These parentheses must be present even if there is no argument passed to the function.

A maximum of 26 arguments is allowed for each function.

There are 30 built-in functions available. Most of them are described in the TPMath documentation. There are, however, some differences which are documented below.

- Standard functions : `Abs(X)`, `Sgn(X)`, `Int(X)`, `Sqrt(X)`, `Exp(X)`, `Ln(X)`, `Log10(X)`, `Fact(X)`, `Rnd()`

`Rnd()` returns a 32-bit real random number in $[0, 1)$ from the ‘Mersenne Twister’ generator (see chapter 12).

- Trigonometric functions: `Deg(X)`, `Rad(X)`, `Sin(X)`, `Cos(X)`, `Tan(X)`, `ArcSin(X)`, `ArcCos(X)`, `ArcTan(X)`, `ArcTan2(Y, X)`
`Deg(X)` and `Rad(X)` convert their argument to degrees and radians, respectively.
- Hyperbolic functions : `Sinh(X)`, `Cosh(X)`, `Tanh(X)`, `ArcSinh(X)`, `ArcCosh(X)`, `ArcTanh(X)`
- Special functions: `Gamma(X)`, `IGamma(A, X)`, `Beta(X, Y)`, `IBeta(A, B, X)`, `Erf(X)`, `LambertW(X)`
`LambertW(X)` returns only the upper branch of the Lambert function.

20.6 Exported functions

20.6.1 InitEval

This function initializes the built-in functions and returns their number. It also re-initializes the random number generator. It is mandatory to call this function before using any of the built-in functions.

```
var
  N : Integer;
begin
  N := InitEval;
  Writeln(N, ' functions initialized');
  ...
```

20.6.2 Eval

This function evaluates an expression passed as a character string and returns its value.

```
var
  X : Float;
  S : String;
begin
  InitEval;
  Write('Enter an expression : ');
  Readln(S);
  X := Eval(S);
  Writeln(' = ', X);
  ...
```

20.6.3 SetVariable

This procedure assigns a value to a variable. The name of the variable is case-insensitive.

```
SetVariable('x', 1);
```

20.6.4 SetFunction

This procedure adds a new function to the library. Up to 20 functions can be added. The function declaration must conform to the internal type:

```
type TWrapper = function(ArgC : TArgC; ArgV : PVector) : Float;
```

where `ArgC` is the argument count, `TArgC` denotes the interval 1..26 and `ArgV` contains the argument values, from `ArgV[1]` to `ArgV[ArgC]`.

```
function Average(N : TArgC; X : PVector) : Float;
var
  I : Integer;
  S : Float;
begin
  S := 0.0;
  for I := 1 to N do
    S := S + X[I];
  Average := S / N;
end;

begin
  SetFunction('Average', Average);
  Writeln(Eval('Average(1, 2, 3)'));
  ....
```

20.7 Demo programs

- Program `eval1.pas` (in `demo\fmath`) evaluates a mathematical expression entered at run time.
- Program `eval2.pas` (in `demo\fmath`) demonstrates the math parser and shows how to add variables and functions at run time.
- Program `calc.pas` (in `demo\delphi\calc`) is a Delphi application which implements a simple calculator with 4 variables.